1625 N. French Dr., Hobbs, NM 88240 1301 W. Grand Avenue, Artesia, NM 88210 2 5 2011 District III District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505ECENED

State of New Mexico **Energy Minerals and Natural Resources** Department

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

July 21, 2008

Form C-144 CLEZ

For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.

Closed-Loop System Permit or Closure Plan Application

(that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)

Type of action: Permit Closure

Instructions: Please submit one application (Form C-144 CLEZ) per individual closed-loop system request. For any application request other than for a closed-loop system that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure, please submit a Form C-144.

Please be advised that approval of this request does not relieve the operator of liability should operations result in pollution of surface water, ground water or the environment. Nor does approval relieve the operator of its responsibility to comply with any other applicable governmental authority's rules, regulations or ordinances.		
i. Operator: Barry D. Lee dba Barry Lee Investments	OGRID# 273546	
Address: HC 65 Box 222 Crossroads, New Mexico 88114		
Facility or well name: Western Reserves 34 Federal # 4		
API Number: 30-005-20760	OCD Permit Number: <u>P1-03512</u>	
U/L or Qtr/Qtr D Section 34 Township		
Center of Proposed Design: Latitude 33.6690920148	Longitude -103.767318452 NAD: 1927 1983	
Surface Owner: Federal State Private Tribal Trust or Indian Allotment		
2. ☐ Closed-loop System: Subsection H of 19.15.17.11 NMAC Operation: ☐ Drilling a new well ☐ Workover or Drilling (Applie ☐ Above Ground Steel Tanks or ☐ Haul-off Bins	s to activities which require prior approval of a permit or notice of intent) P&A	
Signs: Subsection C of 19.15.17.11 NMAC 12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers Signed in compliance with 19.15.3.103 NMAC		
Closed-loop Systems Permit Application Attachment Checklist: Subsection B of 19.15.17.9 NMAC Instructions: Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached. □ Design Plan - based upon the appropriate requirements of 19.15.17.11 NMAC □ Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC □ Closure Plan (Please complete Box 5) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC □ Previously Approved Design (attach copy of design) API Number: □ Previously Approved Operating and Maintenance Plan API Number:		
5. Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: (19.15.17.13.D NMAC) Instructions: Please indentify the facility or facilities for the disposal of liquids, drilling fluids and drill cuttings. Use attachment if more than two facilities are required.		
Disposal Facility Name: Gandy Marley	Disposal Facility Permit Number: NM01-0019	
Disposal Facility Name:		
Site Reclamation Plan - based upon the appropriate requireme	ents of Subsection G of 19.15.17.13 NMAC	
Operator Application Certification: I hereby certify that the information submitted with this application is true, accurate and complete to the best of my knowledge and belief.		
Name (Print): Barry D. Lee	Title: 0 wes/operator Date: 06-20-2011	
Signature:	Date: 06 - 20 - 2011	
e-mail address: Karlee 21@ Yatoco Com	Telephone: 575-675-2323	

OCD Approval: Permit Application (including closure plan) U Closure Plan (only)		
OCD Representative Signature:	Approval Date: 7-26-2011	
Title: STASS NAME (OCD Permit Number: P) -03512	
8. Closure Report (required within 60 days of closure completion):	Subsection K of 19.15.17.13 NMAC	
Instructions: Operators are required to obtain an approved closure	nlan prior to implementing any closure activities and submitting the closure report.	
The closure report is required to be submitted to the division within section of the form until an approved closure plan has been obtained.	60 days of the completion of the closure activities. Please do not complete this	
section of the form until an approved closure plan has been obtained		
	Closure Completion Date:	
9. Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only:		
Instructions: Please indentify the facility or facilities for where the	liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than	
two facilities were utilized.	Disposal Facility Permit Number:	
Disposal Facility Name: Disposal Facility Name:	Disposal Facility Period Number.	
Disposal Facility Name:	Disposal Facility Permit Number:	
Were the closed-loop system operations and associated activities per Yes (If yes, please demonstrate compliance to the items below	formed on or in areas that will not be used for future service and operations? ○ □ No	
Required for impacted areas which will not be used for future service	e and operations:	
Site Reclamation (Photo Documentation) Soil Backfilling and Cover Installation		
Re-vegetation Application Rates and Seeding Technique		
10.		
Operator Closure Certification:		
I hereby certify that the information and attachments submitted with	this closure report is true, accurate and complete to the best of my knowledge and	
, 3 1	sure requirements and conditions specified in the approved closure plan.	
Name (Print): Rarry D. Lee	Title: Owner operator	
Signature: 5	Date: 66. 20. 2011	
e-mail address: barles 21@ Yahoo: Com	Telephone: 575-675-2323	
	•	

Barry D. Lee dba Barry Lee Investments Western Reserves 34 Federal # 4 API 30-005-20760 Chaves County, New Mexico

EQUIPMENT DESIGN:

Barry Lee Investments will use a closed loop system in the plug and abandonment of this well. The following equipment will be on location:

Steel Pit (1) 130 bbl vacuum trucks.

OPERATION AND MAINTENANCE:

During each day of operation, the crew will inspect and monitor the fluids contained within the steel tank and visually monitor any release that may occur. Should a release, spill or leak occur, the NMOCD District 1 office Hobbs (575-393-6161) will be notified as required in NMOCD's rule 19.15.29.8.

CLOSURE:

After plugging operations are complete, all fluids and any solids will be hauled to Gandy Marley
Permit # NM01-0019

BUREAU OF LAND MANAGEMENT

Roswell Field Office 2909 West Second Street Roswell, New Mexico 88201 (575) 627-0272

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

- 1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon. If you are unable to plug the well by the 90th day provide the BLM Roswell Field Office, prior to the 90th day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action.
- 2. <u>Notification</u>: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours call (575) 627-0205 or after office hours call (575) 420-2832. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.
- 3. <u>Blowout Preventers:</u> A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement:</u> Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

- 6. Monument: Upon abandonment of the well, all casing shall be cut-off at the base of the cellar or 3-feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).
- 7. Timing Limitation Lease Stipulation / Condition of Approval For Lesser Prairie-Chicken: Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1 through June 15 annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, geophysical exploration or 3-D seismic operations, and pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.
- 8. <u>Subsequent Plugging Reporting:</u> Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of casing left in the well. <u>Show date well was plugged.</u>

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.