Office	State of New Mexico			Form C-103
District I	econtenergy, Minerals and Natural Res	ources		May 27, 2004
1625 N. French Dr., Hobbs, NM 88240	BS OCE Thergy, Minerals and Natural Res	WEI	LL API NO.	
District II	a a QUIL CONSERVATION DIVI	SION -	30-041-00119	/
District III	0 8 2011 CONSERVATION DIVIS 1220 South St. Francis Dr	5. Ii	ndicate Type of Lease	57
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 87505	·	STATE FEE	
District IV		6.	State Oil & Gas Lease No.	•
1220 S. St. Francis Dr., Santa Fe, NI		7 1	NI II-it A	NI
(DO NOT USE THIS FORM FOR PROP	TICES AND REPORTS ON WELLS OSALS TO DRILL OR TO DEEPEN OR PLUG BACK		ease Name or Unit Agreer nesand Unit	nent Name:
DIFFERENT RESERVOIR, USE "APPL  PROPOSALS.)	ICATION FOR PERMIT" (FORM C-101) FOR SUCH		,	
1. Type of Well: Oil Well	Gas Well Other	8. V	Vell No. 172	
2. Name of Operator		9. O	GRID Number	
EOR Operating Compa	any /	ľ	257420	
3. Address of Operator		10.	Pool name or Wildcat	
200 N. Loraine, Ste. 14	40, Midland, TX 79701		Milnesand, San And	dres
4. Well Location		,		ſ
Unit Letter <b>G</b>	: 1980 feet from the N li		feet from the E	line
Section 14	Township 8-S Range 34		IPM County R	Roosevelt
	11. Elevation (Show whether DR, RKB, R	T; GR, etc.)	FOR THE STATE OF	
Pit or Below-grade Tank Applie	cation or Closure			•
	indwater Distance from nearest fresh wat			iter
Pit Liner Thickness:	mil Below-Grade Tank: Volume	bbls; Co	nstruction Material	
12. Check	Appropriate Box to Indicate Nature o	Notice, Repo	ort or Other Data	
		•		_
• •	INTENTION TO:		QUENT <u>R</u> EPORT OF	
PERFORM REMEDIAL WORK		DIAL WORK	☐ · ALTERING (	CASING 📙
TEMPORARILY ABANDON [	☐ CHANGE PLANS ☐ COMM ☐ MULTIPLE ☐ CASIN	ENCE DRILLING	OPNS. P AND A	
PULL OR ALTER CASING [	<del>-</del>	G/CEMENT JOB	LJ ' '.	
	COMPLETION			
OTHER:	OTHER	reduc. }•		
	eted operations. (Clearly state all pertinent de	ails and give her	rtinent dates including esti	mated date of
13. Describe brobosed of contible			HIHER GAIES, INCIDENTS EST	
starting any proposed work).	SEE RULE 1103. For Multiple Completions			
starting any proposed work). recompletion.	SEE RULE 1103. For Multiple Completions			
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip	SEE RULE 1103. For Multiple Completions  oment	: Attach wellbor	re diagram of proposed cor	npletion or
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI	SEE RULE 1103. For Multiple Completions  oment  P. RIH and tagged CIBP @ 4550'. Circulate	: Attach wellbor	re diagram of proposed cor	npletion or
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'.	: Attach wellbored hole w/ mud l	re diagram of proposed cor aiden fluid. Spotted 35 sx	npletion or
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'.	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500	: Attach wellboned hole w/ mud losi. RIH to 6065	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c	npletion or class C ement @
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 julate hole w/ mud laiden fluid. POH w/ tbg.	ed hole w/ mud losi. RIH to 6065	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg.	ement @ @ 1515'.
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 julate hole w/ mud laiden fluid. POH w/ tbgl csg. @ 520'. Pressured up to 1500 psi. RIF	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg. . Spotted 45 sx class C ce	ement @ @ 1515'.
starting any proposed work). recompletion. 07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 julate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg. . Spotted 45 sx class C ce	eclass C  ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved of	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 julate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx cff.	ed hole w/ mud losi. RIH to 6065 WOC. Tagged [w/ tbg to 1565' ass C cement @	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg. . Spotted 45 sx class C ce 570' to surface.	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circl Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF OC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead an	ed hole w/ mud losi. RIH to 6065 WOC. Tagged [w/ tbg to 1565' ass C cement @	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg. . Spotted 45 sx class C ce 570' to surface.	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved of	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead and oved off.	ed hole w/ mud losi. RIH to 6065 WOC. Tagged [w/ tbg to 1565' ass C cement @	re diagram of proposed cor aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg. . Spotted 45 sx class C ce 570' to surface. Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circl Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead at loved off.  Approved for plu Liability under by	ed hole w/ mud losi. RIH to 6065 WOC. Tagged [w/ tbg to 1565' ass C cement @ ad weld on Dry loging of well bore onlind is retained pendir	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under be of C-103 (Subseq	ed hole w/ mud losi. RIH to 6065 WOC. Tagged w/ tbg to 1565' ass C cement @ d weld on Dry loging of well bore onlind is retained pendinent Report of Well I	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circl Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under be of C-103 (Subseq which may be fou	ed hole w/ mud losi. RIH to 6065 WOC. Tagged w/ tbg to 1565' lass C cement @ d weld on Dry loging of well bore onlind is retained pendirent Report of Well Induct OCD Web Page	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx cff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under be of C-103 (Subseq which may be fou	ed hole w/ mud losi. RIH to 6065 WOC. Tagged w/ tbg to 1565' ass C cement @ d weld on Dry loging of well bore onlind is retained pendinent Report of Well I	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIH DC. Tagged plug @ 1387'. Spotted 120 sx c off. I welder. Dig out cellar. Cut off wellhead and loved off.  Approved for plu Liability under be of C-103 (Subseq which may be fou Forms, www.cmm)	ed hole w/ mud losi. RIH to 6065 WOC. Tagged   w/ tbg to 1565' lass C cement @ ad weld on Dry loging of well bore online is retained pendir lent Report of Well Find at OCD Web Paged d.state.nm.us/ocd.	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel	eclass C ement @ @ 1515'. ment @
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c. ff. I welder. Dig out cellar. Cut off wellhead an loved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled.	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565' lass C cement @ ad weld on Dry loging of well bore online is retained pendir tent Report of Well Find at OCD Web Paged.state.nm.us/ocd.	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel ly. log receipt Plugging) r under	eclass C  ement @ @ 1515'. ment @  clar. Cut off
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	SEE RULE 1103. For Multiple Completions oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIH DC. Tagged plug @ 1387'. Spotted 120 sx c off. I welder. Dig out cellar. Cut off wellhead and loved off.  Approved for plu Liability under be of C-103 (Subseq which may be fou Forms, www.cmm)	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565' lass C cement @ ad weld on Dry loging of well bore online is retained pendir tent Report of Well Find at OCD Web Paged.state.nm.us/ocd.	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel ly. log receipt Plugging) r under	eclass C  ement @ @ 1515'. ment @  clar. Cut off
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circl Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'.  Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx c ff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under be of C-103 (Subseq which may be four Forms, www.cmn).  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565' lass C cement @ ad weld on Dry loging of well bore online is retained pendir tent Report of Well Find at OCD Web Paged.state.nm.us/ocd.	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel (y. ng receipt Plugging) y under  arther certify that any pit or be ached) alternative OCD-appro	eclass C  ement @ @ 1515'. ment @  clar. Cut off
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c. ff. I welder. Dig out cellar. Cut off wellhead an loved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled.	ed hole w/ mud losi. RIH to 6065 WOC. Tagged of w/ tbg to 1565' lass C cement @ ad weld on Dry loging of well bore online is retained pendir tent Report of Well Find at OCD Web Paged.state.nm.us/ocd.	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel ly. log receipt Plugging) r under	eclass C  ement @ @ 1515'. ment @  clar. Cut off
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'ct 1565-1344. POH. ND BOP. WC 07/21/11 Rigged down moved on 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c ff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged W/ tbg to 1565' ass C cement @  Id weld on Dry loging of well bore online is retained pendirent Report of Well India to OCD Web Paged distate.nm.us/ocd.  Idge and belief. I fuermit  or an (atta	aiden fluid. Spotted 35 sx  '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel  ly.  ng receipt Plugging)  under  DATE	elow-grade tank
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'ct 1565-1344. POH. ND BOP. WC 07/21/11 Rigged down moved on 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c ff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged W/ tbg to 1565' ass C cement @  Id weld on Dry loging of well bore online is retained pendirent Report of Well India to OCD Web Paged distarte.nm.us/ocd.  Idge and belief. I fuermit  or an (atta	aiden fluid. Spotted 35 sx  '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel  ly.  ng receipt Plugging)  under  DATE	elow-grade tank
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOD cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circi Pressured up to 1500 psi. Perf'ct 1565-1344. POH. ND BOP. WC 07/21/11 Rigged down moved on 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c ff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged W/ tbg to 1565' ass C cement @  Id weld on Dry loging of well bore online is retained pendirent Report of Well India to OCD Web Paged distarte.nm.us/ocd.  Idge and belief. I fuermit  or an (atta	aiden fluid. Spotted 35 sx '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel (y. ng receipt Plugging) y under  arther certify that any pit or be ached) alternative OCD-appro	elow-grade tank
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	SEE RULE 1103. For Multiple Completions  ment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 pulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx coff. I welder. Dig out cellar. Cut off wellhead and labelity under hof C-103 (Subseq which may be four Forms, www.cmm)  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged W/ tbg to 1565' ass C cement @  Id weld on Dry loging of well bore online is retained pendirent Report of Well India to OCD Web Paged distarte.nm.us/ocd.  Idge and belief. I fuermit  or an (atta	aiden fluid. Spotted 35 sx  '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel  by.  ng receipt Plugging) r under  DATE Spotted Affector Company of the compan	elow-grade tank oved plan
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	oment P. RIH and tagged CIBP @ 4550'. Circulate 2000'. Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIFDC. Tagged plug @ 1387'. Spotted 120 sx c ff. I welder. Dig out cellar. Cut off wellhead and oved off.  Approved for plu Liability under hof C-103 (Subseq which may be four Forms, www.cmm).  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud losi. RIH to 6065 WOC. Tagged W/ tbg to 1565' ass C cement @  Id weld on Dry loging of well bore online is retained pendirent Report of Well India to OCD Web Paged distarte.nm.us/ocd.  Idge and belief. I fuermit  or an (atta	aiden fluid. Spotted 35 sx  '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel  by.  ng receipt Plugging) r under  DATE Spotted Affector Company of the compan	elow-grade tank
starting any proposed work). recompletion.  07/18/11 MIRU plugging Equip 07/19/11 ND wellhead, NU BOI cement @ 4550-4196. POH to 07/20/11 Tagged plug @ 4361'. 3065-2893. POH to 2300'. Circu Pressured up to 1500 psi. Perf'd 1565-1344. POH. ND BOP. WO 07/21/11 Rigged down moved o 07/22/11 Moved in backhoe and dead men and clean location. M	SEE RULE 1103. For Multiple Completions  ment P. RIH and tagged CIBP @ 4550'. Circulate 2000'.  Perf'd csg. @ 3015'. Pressured up to 500 ulate hole w/ mud laiden fluid. POH w/ tbg. I csg. @ 520'. Pressured up to 1500 psi. RIF DC. Tagged plug @ 1387'. Spotted 120 sx c  ff. I welder. Dig out cellar. Cut off wellhead and loved off.  Approved for plu Liability under boof C-103 (Subseq which may be four Forms, www.cmni  bove is true and complete to the best of my knowled according to NMOCD guidelines, a general p	ed hole w/ mud lessi. RIH to 6065 WOC. Tagged work to 1565' ass C cement and weld on Dry leging of well bore only not be retained pendir tent Report of Well I and at OCD Web Paged distate.nm.us/ocd.  I we work to an (attain the pendir control of the pendir control	aiden fluid. Spotted 35 sx  '. Spotted 35 sx class C c plug @ 2902'. Perf'd csg Spotted 45 sx class C ce 570' to surface.  Hole Marker. Backfill cel  by.  ng receipt Plugging) r under  DATE Spotted Affector Company of the compan	class C ement @ @ 1515'. ment @ llar. Cut off  clow-grade tank oved plan  32.687-0303