| | | Bobwhit | e 12 Sta | ‡2H | 0CD - HOBBS 05/13/2016 RECEIVED | | |
|---------|--------------|---------|----------|-------|---------------------------------------|-----|--|
| Surface | Hole Size | Casing | Wt | Depth | Cmt | тос | |

| Surrace | 17.5 | 12 2/0 | 54.5 | 1920 | 1320 | U |
|---------|-------|--------|------|--------------|------|---|
| Intrmd | 12.25 | 9 5/8 | 40 | 4500' | 700 | 0 |
| | 12.25 | 9 5/8 | 40 | 5700' | 1300 | |
| Prod | 8.75 | 5.5 | 17 | 19128' | 1750 | 0 |
| | | | | | | |

Plan to drill a 17.5" hole to 1850' with fresh water. Run 13 3/8", 54.5# J-55 csg and cmt to surface. Drill a 12.25" hole to 5700' with brine, and run 9 5/8" 40# J55/L80 and cement to surface in two stages with ECP at 4037'. Drill out, kick off and drill an 8.75" curve and lateral to 19,128' with cut brine. Run 5-1/2" 17# P110 production string and cement to surface.

Well Control

| Туре | Pressure | Test | Manufacture |
|------------|----------|------|-------------|
| Double Ram | 5000 | 5000 | Cameron |