

OCD - HOBBS
06/26/2017
RECEIVED



McElvain Energy, Inc.

Sec. 30 T18S R34E

EK Federal Com 30

EK 30 BS2 Federal Com 2H

Wellbore #1

Plan: Design #1 21Jul16 kjs

Standard Planning Report - Geographic

01 August, 2016



Planning Report - Geographic

Database: EDM 5000.1 Single User Db
Company: McElvain Energy, Inc.
Project: Sec. 30 T16S R34E
Site: EK Federal Com 30
Well: EK 30 BS2 Federal Com 2H
Wellbore: Wellbore #1
Design: Design #1 21Jul16 kjs

Local Co-ordinate Reference: Well EK 30 BS2 Federal Com 2H
TVD Reference: WELL @ 3919.0usft (Original Well Elev)
MD Reference: WELL @ 3918.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Project	Sec. 30 T16S R34E, Lea County, NM		
Map System:	US State Plane 1603	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	EK Federal Com 30		
Site Position:		Northing:	623,533.80 usft
From:	Map	Easting:	769,543.80 usft
Position Uncertainty:	0.0 usft	Slot Radius:	13-2/16 "
		Grid Convergence:	0.40 "

Well	EK 30 BS2 Federal Com 2H		
Well Position	+N-S	0.0 usft	Northing: 623,503.80 usft
	+E-W	0.0 usft	Easting: 769,769.20 usft
Position Uncertainty	0.0 usft	Wellhead Elevation:	Ground Level: 3,894.0 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	07/21/16	7.00	80.50	49,392

Design	Design #1 21Jul16 kjs			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N-S (usft)	+E-W (usft)	Direction (°)
	0.0	0.0	0.0	559.00

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,874.0	0.00	0.00	1,874.0	0.0	0.0	0.00	0.00	0.00	0.00	
2,456.6	8.74	261.72	2,454.3	-6.4	-43.6	1.50	1.50	0.00	261.72	
6,958.4	8.74	261.72	6,678.7	-148.6	-1,021.1	0.00	0.00	0.00	0.00	
8,538.0	0.00	0.00	8,489.0	-155.0	-1,065.0	1.50	-1.50	0.00	180.00	
10,308.0	92.04	359.00	9,936.2	339.4	-1,073.6	12.00	12.00	-0.13	359.00	
14,662.4	92.04	359.00	9,774.0	4,892.2	-1,152.7	0.00	0.00	0.00	0.00	TD / PSHL EK 30 BS2



Planning Report - Geographic

Database: EOM 5000.1 Single User Db
Company: McElvain Energy, Inc.
Project: Sec. 30 T18S R34E
Site: EK Federal Com 20
Well: EK 30 BS2 Federal Com 2H
Wellbore: Wellbore #1
Design: Design #1 21Jul18 kjs

Local Co-ordinate Reference: Well EK 30 BS2 Federal Com 2H
TVD Reference: WELL @ 3919.0ush (Original Well Elev)
MD Reference: WELL @ 3819.0ush (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
200.0	0.00	0.00	200.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
400.0	0.00	0.00	400.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
600.0	0.00	0.00	600.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
800.0	0.00	0.00	800.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,000.0	0.00	0.00	1,000.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,200.0	0.00	0.00	1,200.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,400.0	0.00	0.00	1,400.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,600.0	0.00	0.00	1,600.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,719.0	0.00	0.00	1,719.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
Rustler									
1,779.0	0.00	0.00	1,779.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
Salt									
1,800.0	0.00	0.00	1,800.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
1,874.0	0.00	0.00	1,874.0	0.0	0.0	823,503.60	788,788.20	32° 42' 42.740 N	103° 35' 38.028 W
Start Build 1.60									
2,000.0	1.88	261.72	2,000.0	-0.3	-2.1	823,503.30	788,788.14	32° 42' 42.737 N	103° 35' 38.050 W
2,200.0	4.88	261.72	2,189.8	-2.0	-13.8	823,501.80	788,754.44	32° 42' 42.721 N	103° 35' 38.187 W
2,400.0	7.89	261.72	2,398.3	-6.2	-35.8	823,498.40	788,732.41	32° 42' 42.691 N	103° 35' 38.445 W
2,458.8	8.74	261.72	2,454.3	-8.4	-43.9	823,497.22	788,724.32	32° 42' 42.679 N	103° 35' 38.540 W
Hold 8.74 Inc, 261.72 Az									
2,600.0	8.74	261.72	2,598.1	-9.5	-85.4	823,494.06	788,702.78	32° 42' 42.650 N	103° 35' 38.763 W
2,800.0	8.74	261.72	2,783.8	-13.8	-85.5	823,486.70	788,672.08	32° 42' 42.608 N	103° 35' 39.145 W
3,000.0	8.74	261.72	2,981.4	-18.3	-125.6	823,486.33	788,642.82	32° 42' 42.587 N	103° 35' 39.497 W
3,200.0	8.74	261.72	3,189.1	-22.7	-155.7	823,480.95	788,612.66	32° 42' 42.528 N	103° 35' 39.850 W
3,261.6	8.74	261.72	3,268.8	-24.4	-187.9	823,479.16	788,600.28	32° 42' 42.508 N	103° 35' 39.883 W
Yates									
3,400.0	8.74	261.72	3,386.8	-27.0	-185.7	823,475.57	788,582.48	32° 42' 42.485 N	103° 35' 40.202 W
3,600.0	8.74	261.72	3,564.5	-31.4	-215.8	823,472.20	788,562.41	32° 42' 42.444 N	103° 35' 40.554 W
3,737.2	8.74	261.72	3,720.1	-34.4	-238.4	823,469.20	788,531.78	32° 42' 42.415 N	103° 35' 40.798 W
Seven Rivers									
3,800.0	8.74	261.72	3,782.1	-35.8	-245.9	823,467.82	788,522.34	32° 42' 42.403 N	103° 35' 40.907 W
4,000.0	8.74	261.72	3,979.8	-40.2	-275.9	823,463.44	788,492.27	32° 42' 42.381 N	103° 35' 41.259 W
4,200.0	8.74	261.72	4,177.5	-44.5	-306.0	823,459.07	788,462.20	32° 42' 42.320 N	103° 35' 41.611 W
4,400.0	8.74	261.72	4,375.2	-48.9	-336.1	823,454.69	788,432.13	32° 42' 42.279 N	103° 35' 41.883 W
4,445.9	8.74	261.72	4,420.5	-49.9	-343.0	823,453.58	788,425.22	32° 42' 42.269 N	103° 35' 42.044 W
Osage									
4,600.0	8.74	261.72	4,572.9	-53.3	-366.1	823,450.32	788,402.08	32° 42' 42.238 N	103° 35' 42.316 W
4,898.0	8.74	261.72	4,870.7	-55.5	-381.0	823,448.15	788,387.17	32° 42' 42.217 N	103° 35' 42.480 W
Penrose									
4,800.0	8.74	261.72	4,770.5	-57.7	-386.2	823,445.94	788,371.99	32° 42' 42.196 N	103° 35' 42.688 W
4,931.0	8.74	261.72	4,800.0	-60.6	-415.8	823,443.07	788,352.29	32° 42' 42.189 N	103° 35' 42.889 W
Intermediate Cap									
5,000.0	8.74	261.72	4,988.2	-62.0	-426.3	823,441.59	788,341.82	32° 42' 42.168 N	103° 35' 43.020 W
5,200.0	8.74	261.72	5,185.9	-66.4	-458.4	823,437.19	788,311.65	32° 42' 42.114 N	103° 35' 43.375 W
5,281.2	8.74	261.72	5,246.1	-68.2	-488.6	823,435.41	788,299.84	32° 42' 42.097 N	103° 35' 43.516 W
San Andres									
5,400.0	8.74	261.72	5,363.6	-70.8	-488.4	823,432.61	788,281.78	32° 42' 42.073 N	103° 35' 43.725 W
5,509.0	8.74	261.72	5,471.3	-73.2	-502.8	823,430.43	788,268.39	32° 42' 42.060 N	103° 35' 43.917 W
Delaware									
5,519.1	8.74	261.72	5,481.3	-73.4	-504.3	823,430.20	788,263.87	32° 42' 42.048 N	103° 35' 43.935 W
1st Delaware Sand									
5,600.0	8.74	261.72	5,561.3	-75.2	-516.5	823,428.43	788,261.71	32° 42' 42.031 N	103° 35' 44.077 W



Planning Report - Geographic

Database: EDM 5000.1 Single User Db
Company: McElvain Energy, Inc.
Project: Sec. 30 T18S R34E
Site: EK Federal Com 30
Well: EK 30 B&S2 Federal Com 2H
Wellbore: Wellbore #1
Design: Design #1 21 Jul 16 k/a

Local Co-ordinate Reference: Well EK 30 B&S2 Federal Com 2H
TVD Reference: WELL @ 3919.00ft (Original Well Elev)
MD Reference: WELL @ 3919.00ft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
5,800.0	8.74	261.72	5,758.8	-79.5	-548.8	823,424.06	788,221.84	32° 42' 41.890 N	103° 35' 44.428 W
5,863.3	8.74	261.72	5,821.5	-80.8	-556.1	823,422.67	788,212.11	32° 42' 41.877 N	103° 35' 44.541 W
2nd Delaware Sand									
6,000.0	8.74	261.72	6,058.8	-83.9	-575.6	823,419.68	788,191.57	32° 42' 41.849 N	103° 35' 44.782 W
6,200.0	8.74	261.72	6,154.3	-88.3	-606.7	823,415.30	788,161.50	32° 42' 41.808 N	103° 35' 45.134 W
6,400.0	8.74	261.72	6,352.0	-92.7	-636.8	823,410.83	788,131.43	32° 42' 41.867 N	103° 35' 45.486 W
6,600.0	8.74	261.72	6,549.6	-97.1	-668.6	823,406.55	788,101.36	32° 42' 41.825 N	103° 35' 45.839 W
6,800.0	8.74	261.72	6,747.3	-101.4	-698.9	823,402.16	788,071.29	32° 42' 41.784 N	103° 35' 46.191 W
7,000.0	8.74	261.72	6,945.0	-105.8	-727.0	823,397.80	788,041.22	32° 42' 41.743 N	103° 35' 46.543 W
7,200.0	8.74	261.72	7,142.7	-110.2	-757.0	823,393.42	788,011.15	32° 42' 41.702 N	103° 35' 46.895 W
7,400.0	8.74	261.72	7,340.4	-114.6	-787.1	823,389.05	787,981.08	32° 42' 41.660 N	103° 35' 47.248 W
7,600.0	8.74	261.72	7,538.0	-118.9	-817.2	823,384.67	787,951.01	32° 42' 41.619 N	103° 35' 47.600 W
7,711.1	8.74	261.72	7,647.8	-121.4	-833.8	823,382.24	787,934.31	32° 42' 41.596 N	103° 35' 47.788 W
Bone Spring									
7,800.0	8.74	261.72	7,735.7	-123.3	-847.3	823,380.29	787,920.84	32° 42' 41.576 N	103° 35' 47.862 W
8,000.0	8.74	261.72	7,933.4	-127.7	-877.3	823,375.92	787,890.87	32° 42' 41.537 N	103° 35' 48.305 W
8,200.0	8.74	261.72	8,131.1	-132.1	-907.4	823,371.54	787,860.80	32° 42' 41.495 N	103° 35' 48.667 W
8,400.0	8.74	261.72	8,328.7	-136.4	-937.5	823,367.16	787,830.73	32° 42' 41.454 N	103° 35' 49.029 W
8,600.0	8.74	261.72	8,526.4	-140.8	-967.5	823,362.78	787,800.66	32° 42' 41.413 N	103° 35' 49.391 W
8,800.0	8.74	261.72	8,724.1	-145.2	-997.8	823,358.41	787,770.59	32° 42' 41.372 N	103° 35' 49.744 W
8,958.4	8.74	261.72	8,878.7	-149.6	-1,021.1	823,354.03	787,747.08	32° 42' 41.339 N	103° 35' 49.899 W
Start Drop -1.50									
9,000.0	8.08	261.72	8,821.8	-149.5	-1,027.4	823,354.07	787,740.76	32° 42' 41.331 N	103° 35' 50.063 W
9,037.2	7.53	261.72	8,958.7	-150.3	-1,032.4	823,353.34	787,736.76	32° 42' 41.324 N	103° 35' 50.122 W
1st Bone Spring Sand									
9,200.0	5.06	261.72	9,120.5	-152.8	-1,050.1	823,350.77	787,718.07	32° 42' 41.300 N	103° 35' 50.329 W
9,400.0	2.08	261.72	9,320.1	-154.6	-1,062.5	823,348.97	787,706.70	32° 42' 41.283 N	103° 35' 50.474 W
9,638.0	0.00	0.00	9,458.0	-156.0	-1,065.0	823,348.80	787,703.20	32° 42' 41.279 N	103° 35' 50.503 W
KOP 12/100									
9,588.8	5.98	359.00	9,508.8	-152.4	-1,085.0	823,351.20	787,703.15	32° 42' 41.305 N	103° 35' 50.504 W
2nd Bone Spring Sand									
9,900.0	7.32	359.00	9,518.8	-151.1	-1,055.1	823,352.50	787,703.13	32° 42' 41.319 N	103° 35' 50.504 W
9,800.0	31.32	359.00	9,707.2	-85.4	-1,068.2	823,418.19	787,701.99	32° 42' 41.988 N	103° 35' 50.512 W
10,000.0	55.32	359.00	9,891.7	50.8	-1,088.8	823,534.39	787,888.62	32° 42' 43.316 N	103° 35' 50.528 W
10,151.1	73.45	359.00	9,916.7	186.4	-1,070.9	823,690.04	787,687.26	32° 42' 44.656 N	103° 35' 50.543 W
Top Target - TOP TARGET WINDOW									
10,200.0	79.32	359.00	9,928.2	234.0	-1,071.8	823,737.56	787,698.44	32° 42' 45.128 N	103° 35' 50.551 W
10,306.0	82.04	359.00	9,938.2	339.4	-1,073.6	823,842.89	787,694.61	32° 42' 46.172 N	103° 35' 50.584 W
Landing Pt 82.04 Inc. 359 Az									
10,400.0	82.04	359.00	9,932.8	433.3	-1,075.2	823,838.95	787,682.87	32° 42' 47.101 N	103° 35' 50.575 W
10,600.0	82.04	359.00	9,925.7	833.2	-1,078.7	824,138.79	787,689.50	32° 42' 49.079 N	103° 35' 50.598 W
10,800.0	82.04	359.00	9,918.6	833.0	-1,082.2	824,336.63	787,688.03	32° 42' 51.058 N	103° 35' 50.624 W
11,000.0	82.04	359.00	9,911.5	1,032.8	-1,085.8	824,538.48	787,682.56	32° 42' 53.034 N	103° 35' 50.648 W
11,200.0	82.04	359.00	9,904.3	1,232.7	-1,089.1	824,736.32	787,679.08	32° 42' 55.012 N	103° 35' 50.673 W
11,400.0	82.04	359.00	9,897.2	1,432.8	-1,092.6	824,936.16	787,675.61	32° 42' 56.989 N	103° 35' 50.697 W
11,600.0	82.04	359.00	9,890.1	1,632.4	-1,096.1	825,136.01	787,672.14	32° 42' 58.967 N	103° 35' 50.721 W
11,800.0	82.04	359.00	9,883.0	1,832.2	-1,099.6	825,335.85	787,668.67	32° 43' 0.944 N	103° 35' 50.746 W
12,000.0	82.04	359.00	9,875.9	2,032.1	-1,103.0	825,535.69	787,665.19	32° 43' 2.922 N	103° 35' 50.770 W
12,200.0	82.04	359.00	9,868.6	2,231.9	-1,106.5	825,735.53	787,661.72	32° 43' 4.900 N	103° 35' 50.795 W
12,400.0	82.04	359.00	9,861.8	2,431.8	-1,109.9	825,935.38	787,658.25	32° 43' 6.877 N	103° 35' 50.818 W
12,600.0	82.04	359.00	9,854.5	2,631.6	-1,113.4	826,135.22	787,654.78	32° 43' 8.855 N	103° 35' 50.844 W
12,800.0	82.04	359.00	9,847.4	2,831.5	-1,116.9	826,335.06	787,651.30	32° 43' 10.832 N	103° 35' 50.868 W
13,000.0	82.04	359.00	9,840.3	3,031.3	-1,120.4	826,534.91	787,647.83	32° 43' 12.810 N	103° 35' 50.892 W
13,200.0	82.04	359.00	9,833.2	3,231.1	-1,123.8	826,734.75	787,644.36	32° 43' 14.787 N	103° 35' 50.917 W



Planning Report - Geographic

Database: EDM 5000.1 Single User Db
Company: McElvain Energy, Inc.
Project: Sec. 30 T16S R34E
Site: EK Federal Com 30
Well: EK 30 BS2 Federal Com 2H
Wellbore: Wellbore #1
Design: Design #1 21Jul16 kjs

Local Co-ordinate Reference: Well EK 30 BS2 Federal Com 2H
TVD Reference: WELL @ 3818.0usft (Original Well Elev)
MD Reference: WELL @ 3919.0usft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N-S (usft)	+E-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
13,400.0	92.04	358.00	9,820.0	3,431.0	-1,127.3	626,834.50	767,640.88	32° 43' 16.765 N	103° 35' 50.941 W
13,800.0	92.04	358.00	9,818.8	3,630.8	-1,130.8	627,134.44	767,637.41	32° 43' 18.743 N	103° 35' 50.968 W
13,800.0	92.04	359.00	9,811.8	3,830.7	-1,134.3	627,334.28	767,633.94	32° 43' 20.720 N	103° 35' 50.990 W
14,000.0	92.04	359.00	9,804.7	4,030.5	-1,137.7	627,534.12	767,630.47	32° 43' 22.698 N	103° 35' 51.014 W
14,200.0	92.04	358.00	9,787.8	4,230.4	-1,141.2	627,733.87	767,627.00	32° 43' 24.675 N	103° 35' 51.039 W
14,400.0	92.04	359.00	9,790.5	4,430.2	-1,144.7	627,933.81	767,623.52	32° 43' 26.653 N	103° 35' 51.063 W
14,600.0	92.04	359.00	9,783.3	4,630.0	-1,148.1	628,133.85	767,620.05	32° 43' 28.631 N	103° 35' 51.088 W
14,800.0	92.04	359.00	9,776.2	4,829.9	-1,151.6	628,333.50	767,616.58	32° 43' 30.608 N	103° 35' 51.112 W
14,862.4	92.04	359.00	9,774.0	4,882.2	-1,152.7	628,395.80	767,615.50	32° 43' 31.225 N	103° 35' 51.120 W

TD at 14862.4 - TD / PBHL EK 30 BS2 FC 2H

Design Targets

Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N-S (usft)	+E-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- initial target									
- Shape									
TD / PBHL EK 30 BS2 F	0.00	0.00	9,774.0	4,882.2	-1,152.7	628,395.80	767,615.50	32° 43' 31.225 N	103° 35' 51.120 W
- plan this target center									
- Point									

Casing Points

Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")
4,931.0	4,906.0	Intermediate Ceg	5-5/8	6-5/8

Formations

Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
1,718.0	1,718.0	Rustler		-2.04	359.00
1,779.0	1,779.0	Salt		-2.04	358.00
3,281.8	3,268.8	Yates		-2.04	358.00
3,737.2	3,720.1	Seven Rivers		-2.04	358.00
4,445.9	4,420.6	Queen		-2.04	359.00
4,698.0	4,670.7	Penrose		-2.04	359.00
5,281.2	5,248.1	San Andrea		-2.04	359.00
5,509.0	5,471.3	Delaware		-2.04	359.00
5,518.1	5,481.3	1st Delaware Sand		-2.04	358.00
5,883.3	5,821.5	2nd Delaware Sand		-2.04	358.00
7,711.1	7,647.8	Bone Spring		-2.04	358.00
8,037.2	8,958.7	1st Bone Spring Sand		-2.04	359.00
8,588.8	8,508.8	2nd Bone Spring Sand		-2.04	359.00
10,151.1	9,016.7	TOP TARGET WINDOW		-2.04	359.00



Planning Report - Geographic

Database: EDM 5000.1 Single User Db
Company: McElvick Energy, Inc.
Project: Sec. 30 T18S R34E
Site: EK Federal Com 30
Well: EK 30 BS2 Federal Com 2H
Wellbore: Wellbore #1
Design: Design #1 21Jul10 kja

Local Co-ordinate Reference: Well EK 30 BS2 Federal Com 2H
TVD Reference: WELL @ 3818.00ft (Original Well Elev)
MD Reference: WELL @ 3818.00ft (Original Well Elev)
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
1,874.0	1,874.0	0.0	0.0	Start Build 1.50
2,458.8	2,454.3	-8.4	-43.9	Held 8.74 Inc, 281.72 Az
8,958.4	8,878.7	-148.8	-1,021.1	Start Drop -1.50
9,539.0	9,459.0	-155.0	-1,065.0	KOP 12/100
10,151.1	9,916.7	185.5	-1,070.8	Top Target
10,308.0	9,836.2	339.4	-1,073.8	Landing Pt 92.04 Inc, 358 Az
14,882.4	9,774.0	4,892.2	-1,152.7	TD at 14882.4