

Submit 3 Copies To Appropriate District  
Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

June 19, 2008

NOBBS OCD  
AUG 22 2011

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. <b>30-025-30489</b>
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: <b>Snyder C</b>
8. Well Number <b>3</b>
9. OGRID Number <b>162928</b>
10. Pool name or Wildcat <b>Townsend, Perno Upper Penn</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3945.2' GR</b>

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	2. Name of Operator <b>Energen Resources Corporation</b>
3. Address of Operator <b>3300 N A St., Bldg. 4, Ste. 100, Midland, TX 79705</b>	4. Well Location Unit Letter <b>E</b> : <b>2006</b> feet from the <b>North</b> line and <b>990</b> feet from the <b>West</b> line Section <b>5</b> Township <b>16S</b> Range <b>36E</b> NMPM County <b>Lea</b>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <b>3945.2' GR</b>	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☒  
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See attached.

Approved for plugging of well bore only.  
Liability under bond is retained pending receipt  
of C-103 (Subsequent Report of Well Plugging)  
which may be found at OCD Web Page under  
Forms, www.cmnrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tracie J Cherry TITLE Asst. Supv. Regulatory/Admin DATE 08-18-11  
Type or print name Tracie J Cherry E-mail address: tracie.cherry@energen.com PHONE (432) 684-3692

For State Use Only

APPROVED BY [Signature] TITLE Staff Mgr DATE 8-23-2011  
Conditions of Approval (if any):

AUG 23 2011

ENERGEN RESOURCES CORPORATION

Snyder C #3  
2006' FNL and 990' FWL  
Sec 5, T-16-S, R-36-E  
Lea, Co. NM  
Saunders Permo Upper Penn Field  
P&A Well

07-06-11

MIRU. Pump 35 bbls b/w w/kil. truck, well on vacuum. Pull and lay down rods.

07-07-11

RU to cmt pump, well on vacuum. Wait for OCD rep. Mix & spot 50 sx cmt. Displace to 8448'. SI well.

07-08-11

RU to pump, slight blow on 2-3/8" & 5-1/2". Pump 25 bbls b/w down 2-3/8" tbg. Mix & displace 100 sx cmt to 6400'. S/I 800 psi per Maxie Brown. SDFWE.

07-11-11

Test 2-3/8" & 5-1/2" casing to 500 psi. RU wireline and tag down thru 2-3/8", find TOC @ 6015'. Notify OCD. Cut 2-3/8" @ 6000'. Not free, cut again. SDFN.

07-12-11

Run freepoint @ 5194. Notify OCD, collar @ 5199'. Cut 2 3/8 @ 5194'. NDWH, NUBOP. POOH w/tbg, set 5-1/2" CIBP @ 5192'. RIH cap CIBP w/25 sx cmt. POOH w/tbg, perf @ 4773'. SDFN

07-13-11

Tag cmt @ 4915'. Run pkr to 4315'. Test perf & no inj rate. POOH w/pkr, RIH w/tbg OE to 4851', spot 25 sx cmt @ 4851' per OCD. Circ MLF to surf, WOC 4 hrs, tag @ 4590'. Perf @ 1600', set pkr @ 1260' test perf & sqz 35 sx cmt. SDFN.

07-14-11

Tag TOC @ 1495'. Perf 350'. Sqz 93 sx cmt, circ out 8 5/8". SI, WOC, top off 5-1/2. Well P&A