

Submit 1 Copy To Appropriate District  
Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505  
Rec 03/30/2020

WELL API NO. 30-025-45401
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Dolly Varden 25/24 B2FC St Com
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Grama Ridge; Bone Spring 28435
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3641' GL

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
PO Box 5270, Hobbs NM 88241

4. Well Location

Unit Letter G : 2435 feet from the North line and 2435 feet from the East line  
Section 25 Township 21S Range 34E NMPM Lea County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☒  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/11/2020

Spud 17 1/2" hole @ 1825'. Ran 1810' of 13 3/8" 54.5# J55 ST&C csg. Cemented w/1275 sks Class C LitePoz (65:35) w/additives. Mixed @ 12.8#/g w/1.81 yd. Tail w/200 sks Class C. Mixed @ 14.8#/g w/1.33 yd. Displaced w/273 bbls of BW. Plug down @ 4:00 A.M. 03/14/2020. Circ 480 sks of cmt to the pits. Test BOPE to 5000# & Annular to 3500#. At 1:30 P.M. 03/16/20, tested csg to 1500# for 30 mins, held OK. FIT to 10.5 PPG EMW. Drilled out with 12 1/4" bit.

03/20/2020

TD'd 12 1/4" hole @ 5800'. Ran 5785' of 9 5/8" 36# J55 & 40# N80 LT&C Csg. Cemented 1<sup>st</sup> stage with 450 sks Lite Poz C (50:50) w/additives. Mixed @ 11.5#/g w/2.36 yd. Tail w/200 sks Class C w/0.2% retarder. Mixed @ 14.8#/g w/1.33 yd. Plug down @ 4:15 A.M. 03/21/20. Set ECP w/2120#. Drop bomb & open DV tool w/870#. Circ 5 sks of cmt off DV tool. Cmt 2<sup>nd</sup> stage lead w/900 sks Lite Poz Class C (50:50) w/additives. Mixed @ 11.5#/g w/2.36 yd. Tail w/200 sks Class C w/additives. Mixed @ 14.8#/g w/1.33 yd. Plug down @ 8:00 A.M. 03/21/20. Circ 57 sks of cmt to the pit. Set Cameron mandrel hanger through BOP w/150k#. At 2:30 A.M. 03/22/20, tested csg to 1500# for 30 mins, held OK. FIT test to EMW of 9.5 PPG. Drilled out with 8 3/4" bit.

Spud Date: 03/11/20

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R. Caballero TITLE Regulatory DATE 03/30/20

Type or print name Ruby Caballero E-mail address: rcaballero@mewbourne.com PHONE: 575-393-5905

**For State Use Only**

APPROVED BY: [Signature] TITLE  DATE 04/01/2020

Conditions of Approval (if any):