

OCD - HOBBS
05/13/2020
RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input checked="" type="checkbox"/> Multiple Zone		5. Lease Serial No. NMNM122620 6. If Indian, Allottee or Tribe Name 7. If Unit or CA Agreement, Name and No. 8. Lease Name and Well No. RED HILLS FEDERAL [5467] 206H 9. API Well No. 30-025-47182
2. Name of Operator KAISER FRANCIS OIL COMPANY [12361]		10. Field and Pool, or Exploratory [97903] BELL LAKE/BONE SPRING, SOUTH
3a. Address 6733 S. Yale Ave., Tulsa, OK 74121	3b. Phone No. (include area code) (918) 491-0000	11. Sec., T. R. M. or Blk. and Survey or Area SEC 31/T25S/R33E/NMP
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NENE / 300 FNL / 1095 FEL / LAT 32.093495 / LONG -103.6063905 At proposed prod. zone SESE / 100 FSL / 400 FEL / LAT 32.0655728 / LONG -103.6041408		
14. Distance in miles and direction from nearest town or post office* 25 miles		12. County or Parish LEA 13. State NM
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 300 feet	16. No of acres in lease 440.2	17. Spacing Unit dedicated to this well 320.0
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20 feet	19. Proposed Depth 10940 feet / 21683 feet	20. BLM/BIA Bond No. in file FED: WYB000055
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3400 feet	22. Approximate date work will start* 03/01/2020	23. Estimated duration 40 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature (Electronic Submission)	Name (Printed/Typed) Melanie Wilson / Ph: (918) 491-0000	Date 01/08/2020
Title Regulatory Analyst		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Christopher Walls / Ph: (575) 234-2234	Date 04/30/2020
Title Petroleum Engineer Office Carlsbad Field Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GCP Rec 05/13/2020

APPROVED WITH CONDITIONS
Approval Date: 04/30/2020

Kz
05/15/2020

SL

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	KAISER FRANCIS OIL COMPANY
WELL NAME & NO.:	RED HILLS FEDERAL 206H
SURFACE HOLE FOOTAGE:	300'/N & 1095'/E
BOTTOM HOLE FOOTAGE:	100'/S & 400'/E
LOCATION:	Section 31, T.25 S., R.33 E., NMP
COUNTY:	Lea County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input type="checkbox"/> COM	<input type="checkbox"/> Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

Casing Design:

1. The 13-3/8 inch surface casing shall be set at approximately **950 feet** (a minimum of **25 feet (Lea County)**) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The **9-5/8** inch intermediate casing shall be set at approximately **4972** feet. The minimum required fill of cement behind the **9-5/8** inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **10,000 (10M) psi. Variance is approved to use a 5000 (5M) Annular which shall be tested to 5000 (5M) psi.**
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.

- e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County
Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County
Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.

3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a

larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been

done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test

does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

RI04242020

Operator Certification

I hereby certify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions which currently exist; that I have full knowledge of state and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements.

NAME: Melanie Wilson**Signed on:** 01/08/2020**Title:** Regulatory Analyst**Street Address:** 106 W. Riverside Drive**City:** Carlsbad**State:** NM**Zip:** 88220**Phone:** (575)914-1461**Email address:** nmogrservices@gmail.com**Field Representative****Representative Name:****Street Address:****City:****State:****Zip:****Phone:****Email address:**

APD ID: 10400052994

Submission Date: 01/08/2020

Highlighted data reflects the most recent changes

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - General

APD ID: 10400052994

Tie to previous NOS? N

Submission Date: 01/08/2020

BLM Office: CARLSBAD

User: Melanie Wilson

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM122620

Lease Acres: 440.2

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? NO

Federal or Indian agreement:

Agreement number:

Agreement name:

Keep application confidential? Y

Permitting Agent? NO

APD Operator: KAISER FRANCIS OIL COMPANY

Operator letter of designation:

Operator Info

Operator Organization Name: KAISER FRANCIS OIL COMPANY

Operator Address: 6733 S. Yale Ave.

Zip: 74121

Operator PO Box: PO Box 21468

Operator City: Tulsa

State: OK

Operator Phone: (918)491-0000

Operator Internet Address:

Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: RED HILLS FEDERAL

Well Number: 206H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: BELL LAKE

Pool Name: BONE SPRING, SOUTH

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,OIL

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Is the proposed well in an area containing other mineral resources? USEABLE WATER,NATURAL GAS,OIL

Is the proposed well in a Helium production area? N **Use Existing Well Pad?** N **New surface disturbance?**

Type of Well Pad: MULTIPLE WELL

Multiple Well Pad Name: RED HILLS **Number:** 8

Well Class: HORIZONTAL

Number of Legs: 1

Well Work Type: Drill

Well Type: OIL WELL

Describe Well Type:

Well sub-Type: EXPLORATORY (WILDCAT)

Describe sub-type:

Distance to town: 25 Miles

Distance to nearest well: 20 FT

Distance to lease line: 300 FT

Reservoir well spacing assigned acres Measurement: 320 Acres

Well plat: Red_Hills_Fed_206H_C102_20200108074310.pdf

RED_HILLS__PAYMENT_CONF_20200108093152.pdf

Well work start Date: 03/01/2020

Duration: 40 DAYS

Section 3 - Well Location Table

Survey Type: RECTANGULAR

Describe Survey Type:

Datum: NAD83

Vertical Datum: NAVD88

Survey number: 7589B

Reference Datum: GROUND LEVEL

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg #1	300	FNL	1095	FEL	25S	33E	31	Aliquot NENE	32.093495	-103.6063905	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 122620	3400	0	0	Y
KOP Leg #1	475	FSL	450	FEL	25S	33E	30	Aliquot SESE	32.095615	-103.6042915	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 110838	-6920	10375	10320	N

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
PPP Leg #1-1	1320	FSL	400	FEL	25S	33E	31	Aliquot SESE	32.083393	-103.604144	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 015321	-7540	15184	10940	Y
PPP Leg #1-2	100	FNL	400	FEL	25S	33E	31	Aliquot NENE	32.094045	-103.604146	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 122620	-7540	11324	10940	Y
PPP Leg #1-3	0	FNL	405	FEL	25S	33E	31	Aliquot NENE	32.094305	-103.604149	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 122620	-7531	11225	10931	Y
EXIT Leg #1	100	FSL	400	FEL	26S	33E	6	Aliquot SESE	32.0655728	-103.6041408	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 015321	-7540	21683	10940	Y
BHL Leg #1	100	FSL	400	FEL	26S	33E	6	Aliquot SESE	32.0655728	-103.6041408	LEA	NEW MEXICO	NEW MEXICO	F	NMNM 015321	-7540	21683	10940	Y

CONFIDENTIAL

We value your feedback!

Let us know how we did. Complete our [short two minute survey](#).

Tracking Information

Pay.gov Tracking ID: 26MM0MMM

Agency Tracking ID: 75923295565

Form Name: Bureau of Land Management (BLM) Application for Permit to Drill (APD) Fee

Application Name: BLM Oil and Gas Online Payment

Payment Information

Payment Type: Bank account (ACH)

Payment Amount: \$112,530.00

Transaction Date: 01/07/2020 06:06:24 PM EST

Payment Date: 01/08/2020

Company: KAISER FRANCIS OIL COMPANY

APD IDs: 10400052977, 10400052992, 10400053005, 10400053006, 10400052983, 10400053001, 10400053004, 10400052994, 10400053000, 10400052998, 10400052997

Lease Numbers: NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620, NMNM-122620

Well Numbers: 201H, 701H, 203H, 703H, 604H, 605H, 705H, 206H, 506H, 606H, 706H

Note: You will need your Pay.gov Tracking ID to complete your APD transaction in AFMSS II. Please ensure you write this number down upon completion of payment.

Account Information

Account Holder Name: Kaiser-Francis Oil Co

Routing Number: 103900036

Account Number: *****1125

APD ID: 10400052994

Submission Date: 01/08/2020

Highlighted data reflects the most recent changes

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
628606	---	3400	0	0	OTHER : Surface	NONE	N
628607	RUSTLER	2540	860	860	SANDSTONE	NONE	N
628608	SALADO	2200	1200	1200	SALT	NONE	N
628609	TOP SALT	1395	2005	2005	SALT	NONE	N
628610	BASE OF SALT	-1050	4450	4450	SALT	NONE	N
628611	LAMAR	-1350	4750	4750	SANDSTONE	NATURAL GAS, OIL	N
628612	BELL CANYON	-1470	4870	4870	SANDSTONE	NATURAL GAS, OIL	N
628613	CHERRY CANYON	-2460	5860	5860	SANDSTONE	NATURAL GAS, OIL	N
628614	BRUSHY CANYON	-5200	8600	8600	SANDSTONE	NATURAL GAS, OIL	N
628624	BONE SPRING	-5400	8800	8800	SANDSTONE	NATURAL GAS, OIL	N
628623	AVALON SAND	-5610	9010	9010	SANDSTONE	NATURAL GAS, OIL	Y
629348	BONE SPRING 1ST	-6550	9950	9950	SANDSTONE	NATURAL GAS, OIL	N
628625	BONE SPRING 2ND	-7110	10510	10510	SANDSTONE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Pressure Rating (PSI): 5M

Rating Depth: 13000

Equipment: A 10M system will be installed according to Onshore Order #2 consisting of an Annular Preventer, BOP with two rams, a blind ram and safety valves and appropriate handles located on the rig floor. BOP will be equipped with 2 side outlets (choke side shall be a minimum 3 line, and kill side will be a minimum 2 line). Kill line will be installed with (2) valves and a check valve (2 min) of proper pressure rating for the system. Remote kill line (2 min) will be installed and ran to the outer edge of the substructure and be unobstructed. A manual and hydraulic valve (3 min) will be installed on the choke line, 3 chokes will be used with one being remotely controlled. Fill up line will be installed above the uppermost preventer. Pressure gauge of proper pressure rating will be installed on choke manifold. Upper and lower kelly cocks will be utilized with handles readily available in plain sight. A float sub will be available at all times. All connections subject to well pressure will be flanged, welded, or clamped.

Requesting Variance? YES

Variance request: Flex Hose Variance

Testing Procedure: BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure stated. If the system is upgraded all the components installed will be functional and tested. Pipe rams will be operationally checked each 24 hour period. The Annular shall be functionally operated at least weekly. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets.

Choke Diagram Attachment:

Red_Hills_Fed_206H_Choke_Manifold_20200108084439.pdf

BOP Diagram Attachment:

Red_Hills_Fed_206H_BOP_20200108084504.pdf

Red_Hills_Fed_206H_Flex_Hose_20200108084504.pdf

Red_Hills_Fed_206H_Wellhead_20200108084505.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	950	0	950	3400	2450	950	J-55	54.5	BUTT	2.5	6.1	DRY	17.6	DRY	16.5
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	4972	0	4950		-1550	4972	L-80	40	LT&C	1.2	2.2	DRY	3.7	DRY	4.6
3	PRODUCTION	8.5	5.5	NEW	API	N	0	21683	0	10940		-7540	21683	P-110	20	OTHER - GBCD	2.1	2.4	DRY	3	DRY	2.9

Casing Attachments

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Red_Hills_Fed_206H_Csg_Assumptions_20200108085051.pdf

Casing ID: 2 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Red_Hills_Fed_206H_Csg_Assumptions_20200108084650.pdf

Casing ID: 3 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

Red_Hills_Fed_206H_Prod_Csg_Specs_20200108085140.pdf

Section 4 - Cement

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	950	480	1.75	13.5	741	50	Halcem	Kol Seal
SURFACE	Tail		0	950	117	1.33	14.8	156	50	Halcem	Poly Flake
INTERMEDIATE	Lead		0	4972	778	2.09	12.5	1626	30	Econocem	Salt/Kol Seal
INTERMEDIATE	Tail		0	4972	310	1.33	14.8	412.3	30	Halcem	none
PRODUCTION	Lead		3800	2168 3	715	3.49	10.5	2493	10	Neo Cem	Kol Seal / PolyEFlake
PRODUCTION	Tail		3800	2168 3	2190	1.22	14.5	2678	10	Versacem	Halad R-344 / HR-610

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times

Describe the mud monitoring system utilized: PVT/Pason/Visual Monitoring

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
950	4950	OTHER : BRINE	9.8	10.2							
4950	1094 0	OTHER : CUT BRINE	8.8	9.2							
0	950	OTHER : FRESH WATER	8.4	9							

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

Top of cement on production casing will be determined by calculation.

List of open and cased hole logs run in the well:

DIRECTIONAL SURVEY, GAMMA RAY LOG, MUD LOG/GEOLOGIC LITHOLOGY LOG,

Coring operation description for the well:

None planned

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 5234

Anticipated Surface Pressure: 2827

Anticipated Bottom Hole Temperature(F): 191

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

Red_Hills_Federal_H2S_Plan_20200107132250.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

Red_Hills_Fed_206H_Directional_Plan_20200108085821.pdf

Other proposed operations facets description:

Gas Capture Plan attached

Other proposed operations facets attachment:


Red_Hills_Pad_8_Gas_Capture_Plan_20200108085834.pdf

Other Variance attachment:

Red_Hills_Fed_206H_Wellhead_20200108085845.pdf

Red_Hills_Fed_206H_Flex_Hose_20200108085849.pdf

**10M Choke Manifold
Cactus Rig 171
Kaiser Francis Oil Company**



Line in from Choke Manifold

Vent Line to flair

Line out to Mud Tanks

Line to Gas Buster

Panic Line

4 1/16 5M Manual valves

Line in from Flowline

Buffer Chamber

Line to Trip Tank


3 1/16" 10M adjustable choke Manual

2 1/16" 10M Manual choke to pressure guage

10M Line from BOP's

4 1/16" 10M Manual valves

3 1/16" 10M adjustable choke Hydraulic





Certificate of Registration

APIQR® REGISTRATION NUMBER

3042

This certifies that the quality management system of

**COPPER STATE RUBBER, INC.
10485 W. Roosevelt Street
Avondale, AZ**

has been assessed by the American Petroleum Institute Quality Registrar (APIQR®) and found it to be in conformance with the following standard:

ISO 9001:2015

The scope of this registration and the approved quality management system applies to the
Design and Manufacture of Oilfield, Marine and Other Industrial Hoses

APIQR® approves the organization's justification for excluding:

No Exclusions Identified as Applicable

Effective Date: APRIL 21, 2019
Expiration Date: APRIL 21, 2022
Registered Since: APRIL 21, 2016

*Vice President of Global
Industry Services*

Accredited by Member of
the International
Accreditation Forum
Multilateral Recognition
Arrangement for Quality
Management Systems



This certificate is valid for the period specified herein. The registered organization must continually meet all requirements of APIQR's Registration Program and the requirements of the Registration Agreement. Registration is maintained and regularly monitored through annual full system audits. Further clarifications regarding the scope of this certificate and the applicability of ISO 9001 standard requirements may be obtained by consulting the registered organization. This certificate has been issued from APIQR offices located at 200 Massachusetts Avenue, NW Suite 1100, Washington, DC 20001-5571, U.S.A., it is the property of APIQR, and must be returned upon request. To verify the authenticity of this certificate, go to www.api.org/compositelist.



2018-152 | 02.19
Digital



REGISTRATION NO. Q1-3217

Certificate of Registration

The American Petroleum Institute certifies that the quality management system of

COPPER STATE RUBBER, INC.
10485 W. Roosevelt Street
Avondale, AZ

has been assessed by the American Petroleum Institute and found to be in conformance with the following:


API Specification Q1

The scope of this registration and the approved quality management system applies to the:

Design and Manufacture of Oilfield, Marine and Other Industrial Hoses

API approves the organization's justification for excluding:

No Exclusions Identified as Applicable



Effective Date: APRIL 21, 2019
Expiration Date: APRIL 21, 2022
Registered Since: MAY 4, 2016

Vice President of Global Industry Services

This certificate is valid for the period specified herein. The registered organization must continually meet all requirements of API Spec Q1, *Specification for Quality Programs for the Petroleum, Petrochemical and Natural Gas Industry*, and the requirements of the Registration Agreement. Registration is maintained and regularly monitored through annual full system audits. This certificate has been issued from API offices located at 200 Massachusetts Avenue, NW Suite 1100, Washington, DC 20001-5571, U.S.A. It is the property of API, and must be returned upon request. **To verify the authenticity of this certificate, go to www.api.org/compositelist.**

CASING DETAILS


TVD	MD	Name
950.00	950.00	13 3/8"
4950.00	4972.28	9 5/8"



Azimuths to Grid North
 True North: -0.39°
 Magnetic North: 6.23°
 Magnetic Field
 Strength: 47470.4snT
 Dip Angle: 59.79°
 Date: 11/26/2020
 Model: IGRF2020

US State Plane 1983
 New Mexico Eastern Zone
 32° 5' 36.585 N
 103° 36' 23.006 W

West(-)/East(+) (2000 usft/in)
 -2000 -1000 0 1000 2000




31

FORMATION DETAILS

TVDPATH	MDPATH	FORMATION
860.00	860.00	Rustler
1200.00	1200.01	Salado
2000.00	2003.85	Top of Salt
4450.00	4469.16	Base of Salt
4750.00	4771.03	Lamar
4870.00	4891.78	Bell Canyon
5860.00	5887.97	Cherry Canyon
8600.00	8645.09	Brushy Canyon
8800.00	8846.34	Lwr Brushy Canyon
9010.00	9057.66	Avalon
9950.00	10003.53	1 BSS
10510.00	10567.88	2 BSS

OFFSETS
 100' FNL/FSL
 330' FEL

6



Vertical Section at 175.69° (2000 usft/in)

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
RH 206H SL	0.00	0.00	0.00	398509.34	766454.80	32° 5' 36.585 N	103° 36' 23.006 W
RH 206H FTP	10940.00	204.83	693.54	398714.16	767148.32	32° 5' 38.565 N	103° 36' 14.928 W
RH 206H PBHL	10940.00	-10153.61	765.38	388356.06	767220.15	32° 3' 56.062 N	103° 36' 14.907 W

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Target
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	1100.00	0.00	0.00	1100.00	0.00	0.00	0.00	0.00	0.00	
3	1525.91	6.39	39.75	1525.03	18.24	15.17	1.50	39.75	-17.05	S31-T25S-R33E SL 300'FNL 1095'FEL
4	10375.76	6.39	39.75	10319.92	775.38	644.82	0.00	0.00	-724.72	S31-T25S-R33E FTP 100'FNL 400'FEL
5	11324.56	90.00	179.60	10940.00	204.83	693.54	10.00	139.68	-152.12	RH 206H FTP
6	21683.25	90.00	179.60	10940.00	-10153.61	765.38	0.00	0.00	10182.42	RH 206H PBHL S6-T26S-R33E PBHL 100'FSL 400'FEL

Titan Directional Drilling

Survey Report

Company: Kaiser-Francis Oil Company	Local Co-ordinate Reference: Well Red Hills 206H - Slot B
Project: Permian NM E'83	TVD Reference: est.GL+KB @ 3426.00usft (planning)
Site: Red Hills Pad 8	MD Reference: est.GL+KB @ 3426.00usft (planning)
Well: Red Hills 206H	North Reference: Grid
Wellbore: #206H OH	Survey Calculation Method: Minimum Curvature
Design: Plan #1	Database: EDM 5k-14

Project Permian NM E'83		
Map System: US State Plane 1983	System Datum: Mean Sea Level	
Geo Datum: North American Datum 1983		
Map Zone: New Mexico Eastern Zone	Using geodetic scale factor	

Site Red Hills Pad 8, Centered on 706H			
Site Position:	Northing: 398,509.21 usft	Latitude: 32° 5' 36.585 N	
From: Map	Easting: 766,434.78 usft	Longitude: 103° 36' 23.238 W	
Position Uncertainty: 0.00 usft	Slot Radius: 13-3/16 "	Grid Convergence: 0.39 °	

Well Red Hills 206H - Slot B			
Well Position	+N/-S 0.00 usft	Northing: 398,509.34 usft	Latitude: 32° 5' 36.585 N
	+E/-W 0.00 usft	Easting: 766,454.80 usft	Longitude: 103° 36' 23.006 W
Position Uncertainty	0.00 usft	Wellhead Elevation: usft	Ground Level: 3,400.80 usft

Wellbore #206H OH					
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2020	11/26/20	6.62	59.79	47,470.39751436

Design Plan #1				
Audit Notes:				
Version:	Phase: PROTOTYPE	Tie On Depth:	0.00	
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	175.69

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
860.00	0.00	0.00	860.00	0.00	0.00	0.00	0.00	0.00	0.00	
Rustler										
950.00	0.00	0.00	950.00	0.00	0.00	0.00	0.00	0.00	0.00	
13 3/8"										
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,200.00	1.50	39.75	1,199.99	1.01	0.84	-0.94	1.50	1.50	0.00	
1,200.01	1.50	39.75	1,200.00	1.01	0.84	-0.94	0.00	0.00	0.00	
Salado										
1,300.00	3.00	39.75	1,299.91	4.02	3.35	-3.76	1.50	1.50	0.00	
1,400.00	4.50	39.75	1,399.69	9.05	7.53	-8.46	1.50	1.50	0.00	
1,500.00	6.00	39.75	1,499.27	16.09	13.38	-15.04	1.50	1.50	0.00	
1,525.91	6.39	39.75	1,525.03	18.24	15.17	-17.05	1.50	1.50	0.00	
1,600.00	6.39	39.75	1,598.66	24.58	20.44	-22.97	0.00	0.00	0.00	
1,700.00	6.39	39.75	1,698.04	33.13	27.55	-30.97	0.00	0.00	0.00	
1,800.00	6.39	39.75	1,797.42	41.69	34.67	-38.96	0.00	0.00	0.00	

Titan Directional Drilling

Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,900.00	6.39	39.75	1,896.79	50.24	41.78	-46.96	0.00	0.00	0.00
2,000.00	6.39	39.75	1,996.17	58.80	48.90	-54.96	0.00	0.00	0.00
2,003.85	6.39	39.75	2,000.00	59.13	49.17	-55.26	0.00	0.00	0.00
Top of Salt									
2,100.00	6.39	39.75	2,095.55	67.35	56.01	-62.95	0.00	0.00	0.00
2,200.00	6.39	39.75	2,194.93	75.91	63.13	-70.95	0.00	0.00	0.00
2,300.00	6.39	39.75	2,294.31	84.46	70.24	-78.95	0.00	0.00	0.00
2,400.00	6.39	39.75	2,393.69	93.02	77.36	-86.94	0.00	0.00	0.00
2,500.00	6.39	39.75	2,493.07	101.58	84.47	-94.94	0.00	0.00	0.00
2,600.00	6.39	39.75	2,592.45	110.13	91.59	-102.94	0.00	0.00	0.00
2,700.00	6.39	39.75	2,691.83	118.69	98.70	-110.93	0.00	0.00	0.00
2,800.00	6.39	39.75	2,791.21	127.24	105.82	-118.93	0.00	0.00	0.00
2,900.00	6.39	39.75	2,890.58	135.80	112.93	-126.92	0.00	0.00	0.00
3,000.00	6.39	39.75	2,989.96	144.35	120.05	-134.92	0.00	0.00	0.00
3,100.00	6.39	39.75	3,089.34	152.91	127.16	-142.92	0.00	0.00	0.00
3,200.00	6.39	39.75	3,188.72	161.46	134.28	-150.91	0.00	0.00	0.00
3,300.00	6.39	39.75	3,288.10	170.02	141.39	-158.91	0.00	0.00	0.00
3,400.00	6.39	39.75	3,387.48	178.58	148.51	-166.91	0.00	0.00	0.00
3,500.00	6.39	39.75	3,486.86	187.13	155.62	-174.90	0.00	0.00	0.00
3,600.00	6.39	39.75	3,586.24	195.69	162.74	-182.90	0.00	0.00	0.00
3,700.00	6.39	39.75	3,685.62	204.24	169.85	-190.90	0.00	0.00	0.00
3,800.00	6.39	39.75	3,785.00	212.80	176.97	-198.89	0.00	0.00	0.00
3,900.00	6.39	39.75	3,884.37	221.35	184.08	-206.89	0.00	0.00	0.00
4,000.00	6.39	39.75	3,983.75	229.91	191.20	-214.89	0.00	0.00	0.00
4,100.00	6.39	39.75	4,083.13	238.46	198.31	-222.88	0.00	0.00	0.00
4,200.00	6.39	39.75	4,182.51	247.02	205.43	-230.88	0.00	0.00	0.00
4,300.00	6.39	39.75	4,281.89	255.57	212.54	-238.88	0.00	0.00	0.00
4,400.00	6.39	39.75	4,381.27	264.13	219.65	-246.87	0.00	0.00	0.00
4,469.16	6.39	39.75	4,450.00	270.05	224.58	-252.40	0.00	0.00	0.00
Base of Salt									
4,500.00	6.39	39.75	4,480.65	272.69	226.77	-254.87	0.00	0.00	0.00
4,600.00	6.39	39.75	4,580.03	281.24	233.88	-262.86	0.00	0.00	0.00
4,700.00	6.39	39.75	4,679.41	289.80	241.00	-270.86	0.00	0.00	0.00
4,771.03	6.39	39.75	4,750.00	295.87	246.05	-276.54	0.00	0.00	0.00
Lamar									
4,800.00	6.39	39.75	4,778.79	298.35	248.11	-278.86	0.00	0.00	0.00
4,891.78	6.39	39.75	4,870.00	306.20	254.64	-286.20	0.00	0.00	0.00
Bell Canyon									
4,900.00	6.39	39.75	4,878.16	306.91	255.23	-286.85	0.00	0.00	0.00
4,972.28	6.39	39.75	4,950.00	313.09	260.37	-292.63	0.00	0.00	0.00
9 5/8"									
5,000.00	6.39	39.75	4,977.54	315.46	262.34	-294.85	0.00	0.00	0.00
5,100.00	6.39	39.75	5,076.92	324.02	269.46	-302.85	0.00	0.00	0.00
5,200.00	6.39	39.75	5,176.30	332.57	276.57	-310.84	0.00	0.00	0.00

Titan Directional Drilling

Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,300.00	6.39	39.75	5,275.68	341.13	283.69	-318.84	0.00	0.00	0.00
5,400.00	6.39	39.75	5,375.06	349.68	290.80	-326.84	0.00	0.00	0.00
5,500.00	6.39	39.75	5,474.44	358.24	297.92	-334.83	0.00	0.00	0.00
5,600.00	6.39	39.75	5,573.82	366.80	305.03	-342.83	0.00	0.00	0.00
5,700.00	6.39	39.75	5,673.20	375.35	312.15	-350.83	0.00	0.00	0.00
5,800.00	6.39	39.75	5,772.58	383.91	319.26	-358.82	0.00	0.00	0.00
5,887.97	6.39	39.75	5,860.00	391.43	325.52	-365.86	0.00	0.00	0.00
Cherry Canyon									
5,900.00	6.39	39.75	5,871.95	392.46	326.38	-366.82	0.00	0.00	0.00
6,000.00	6.39	39.75	5,971.33	401.02	333.49	-374.82	0.00	0.00	0.00
6,100.00	6.39	39.75	6,070.71	409.57	340.61	-382.81	0.00	0.00	0.00
6,200.00	6.39	39.75	6,170.09	418.13	347.72	-390.81	0.00	0.00	0.00
6,300.00	6.39	39.75	6,269.47	426.68	354.84	-398.80	0.00	0.00	0.00
6,400.00	6.39	39.75	6,368.85	435.24	361.95	-406.80	0.00	0.00	0.00
6,500.00	6.39	39.75	6,468.23	443.79	369.07	-414.80	0.00	0.00	0.00
6,600.00	6.39	39.75	6,567.61	452.35	376.18	-422.79	0.00	0.00	0.00
6,700.00	6.39	39.75	6,666.99	460.91	383.30	-430.79	0.00	0.00	0.00
6,800.00	6.39	39.75	6,766.37	469.46	390.41	-438.79	0.00	0.00	0.00
6,900.00	6.39	39.75	6,865.74	478.02	397.53	-446.78	0.00	0.00	0.00
7,000.00	6.39	39.75	6,965.12	486.57	404.64	-454.78	0.00	0.00	0.00
7,100.00	6.39	39.75	7,064.50	495.13	411.76	-462.78	0.00	0.00	0.00
7,200.00	6.39	39.75	7,163.88	503.68	418.87	-470.77	0.00	0.00	0.00
7,300.00	6.39	39.75	7,263.26	512.24	425.99	-478.77	0.00	0.00	0.00
7,400.00	6.39	39.75	7,362.64	520.79	433.10	-486.77	0.00	0.00	0.00
7,500.00	6.39	39.75	7,462.02	529.35	440.22	-494.76	0.00	0.00	0.00
7,600.00	6.39	39.75	7,561.40	537.90	447.33	-502.76	0.00	0.00	0.00
7,700.00	6.39	39.75	7,660.78	546.46	454.45	-510.76	0.00	0.00	0.00
7,800.00	6.39	39.75	7,760.16	555.02	461.56	-518.75	0.00	0.00	0.00
7,900.00	6.39	39.75	7,859.53	563.57	468.68	-526.75	0.00	0.00	0.00
8,000.00	6.39	39.75	7,958.91	572.13	475.79	-534.74	0.00	0.00	0.00
8,100.00	6.39	39.75	8,058.29	580.68	482.90	-542.74	0.00	0.00	0.00
8,200.00	6.39	39.75	8,157.67	589.24	490.02	-550.74	0.00	0.00	0.00
8,300.00	6.39	39.75	8,257.05	597.79	497.13	-558.73	0.00	0.00	0.00
8,400.00	6.39	39.75	8,356.43	606.35	504.25	-566.73	0.00	0.00	0.00
8,500.00	6.39	39.75	8,455.81	614.90	511.36	-574.73	0.00	0.00	0.00
8,600.00	6.39	39.75	8,555.19	623.46	518.48	-582.72	0.00	0.00	0.00
8,645.09	6.39	39.75	8,600.00	627.32	521.69	-586.33	0.00	0.00	0.00
Brushy Canyon									
8,700.00	6.39	39.75	8,654.57	632.01	525.59	-590.72	0.00	0.00	0.00
8,800.00	6.39	39.75	8,753.94	640.57	532.71	-598.72	0.00	0.00	0.00
8,846.34	6.39	39.75	8,800.00	644.54	536.01	-602.42	0.00	0.00	0.00
Lwr Brushy Canyon									
8,900.00	6.39	39.75	8,853.32	649.13	539.82	-606.71	0.00	0.00	0.00
9,000.00	6.39	39.75	8,952.70	657.68	546.94	-614.71	0.00	0.00	0.00

Titan Directional Drilling

Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,057.66	6.39	39.75	9,010.00	662.61	551.04	-619.32	0.00	0.00	0.00
Avalon									
9,100.00	6.39	39.75	9,052.08	666.24	554.05	-622.71	0.00	0.00	0.00
9,200.00	6.39	39.75	9,151.46	674.79	561.17	-630.70	0.00	0.00	0.00
9,300.00	6.39	39.75	9,250.84	683.35	568.28	-638.70	0.00	0.00	0.00
9,400.00	6.39	39.75	9,350.22	691.90	575.40	-646.70	0.00	0.00	0.00
9,500.00	6.39	39.75	9,449.60	700.46	582.51	-654.69	0.00	0.00	0.00
9,600.00	6.39	39.75	9,548.98	709.01	589.63	-662.69	0.00	0.00	0.00
9,700.00	6.39	39.75	9,648.36	717.57	596.74	-670.68	0.00	0.00	0.00
9,800.00	6.39	39.75	9,747.73	726.12	603.86	-678.68	0.00	0.00	0.00
9,900.00	6.39	39.75	9,847.11	734.68	610.97	-686.68	0.00	0.00	0.00
10,000.00	6.39	39.75	9,946.49	743.24	618.09	-694.67	0.00	0.00	0.00
10,003.53	6.39	39.75	9,950.00	743.54	618.34	-694.96	0.00	0.00	0.00
1 BSS									
10,100.00	6.39	39.75	10,045.87	751.79	625.20	-702.67	0.00	0.00	0.00
10,200.00	6.39	39.75	10,145.25	760.35	632.32	-710.67	0.00	0.00	0.00
10,300.00	6.39	39.75	10,244.63	768.90	639.43	-718.66	0.00	0.00	0.00
10,375.76	6.39	39.75	10,319.92	775.38	644.82	-724.72	0.00	0.00	0.00
10,400.00	4.80	58.82	10,344.05	776.95	646.55	-726.15	10.00	-6.54	78.71
10,450.00	4.85	121.28	10,393.90	776.93	650.15	-725.87	10.00	0.09	124.92
10,500.00	8.59	151.07	10,443.56	772.56	653.77	-721.24	10.00	7.49	59.57
10,550.00	13.20	161.67	10,492.65	763.87	657.37	-712.30	10.00	9.20	21.20
10,567.88	14.90	163.87	10,510.00	759.72	658.65	-708.06	10.00	9.55	12.26
2 BSS									
10,600.00	18.01	166.77	10,540.80	750.92	660.94	-699.11	10.00	9.67	9.05
10,650.00	22.90	169.76	10,587.63	733.81	664.44	-681.79	10.00	9.78	5.98
10,700.00	27.83	171.74	10,632.80	712.68	667.84	-660.46	10.00	9.86	3.96
10,750.00	32.78	173.17	10,675.95	687.67	671.13	-635.28	10.00	9.90	2.85
10,800.00	37.74	174.25	10,716.77	658.99	674.28	-606.44	10.00	9.92	2.17
10,850.00	42.71	175.12	10,754.94	626.85	677.26	-574.17	10.00	9.94	1.73
10,900.00	47.68	175.83	10,790.16	591.50	680.04	-538.71	10.00	9.95	1.43
10,950.00	52.66	176.45	10,822.18	553.20	682.62	-500.33	10.00	9.96	1.22
11,000.00	57.64	176.98	10,850.74	512.25	684.97	-459.31	10.00	9.96	1.07
11,050.00	62.62	177.46	10,875.63	468.96	687.06	-415.99	10.00	9.97	0.96
11,100.00	67.61	177.90	10,896.67	423.65	688.90	-370.67	10.00	9.97	0.88
11,150.00	72.59	178.31	10,913.68	376.68	690.45	-323.71	10.00	9.97	0.82
11,200.00	77.58	178.69	10,926.55	328.39	691.71	-275.47	10.00	9.97	0.77
11,250.00	82.56	179.06	10,935.17	279.17	692.68	-226.31	10.00	9.97	0.74
11,300.00	87.55	179.43	10,939.48	229.37	693.33	-176.61	10.00	9.97	0.73
11,324.56	90.00	179.60	10,940.00	204.83	693.54	-152.12	10.00	9.97	0.72
11,400.00	90.00	179.60	10,940.00	129.38	694.07	-76.85	0.00	0.00	0.00
11,500.00	90.00	179.60	10,940.00	29.39	694.76	22.92	0.00	0.00	0.00
11,600.00	90.00	179.60	10,940.00	-70.61	695.45	122.69	0.00	0.00	0.00
11,700.00	90.00	179.60	10,940.00	-170.61	696.15	222.45	0.00	0.00	0.00

Titan Directional Drilling

Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
11,800.00	90.00	179.60	10,940.00	-270.61	696.84	322.22	0.00	0.00	0.00	
11,900.00	90.00	179.60	10,940.00	-370.60	697.53	421.99	0.00	0.00	0.00	
12,000.00	90.00	179.60	10,940.00	-470.60	698.23	521.75	0.00	0.00	0.00	
12,100.00	90.00	179.60	10,940.00	-570.60	698.92	621.52	0.00	0.00	0.00	
12,200.00	90.00	179.60	10,940.00	-670.60	699.61	721.29	0.00	0.00	0.00	
12,300.00	90.00	179.60	10,940.00	-770.59	700.31	821.05	0.00	0.00	0.00	
12,400.00	90.00	179.60	10,940.00	-870.59	701.00	920.82	0.00	0.00	0.00	
12,500.00	90.00	179.60	10,940.00	-970.59	701.69	1,020.59	0.00	0.00	0.00	
12,600.00	90.00	179.60	10,940.00	-1,070.59	702.39	1,120.35	0.00	0.00	0.00	
12,700.00	90.00	179.60	10,940.00	-1,170.58	703.08	1,220.12	0.00	0.00	0.00	
12,800.00	90.00	179.60	10,940.00	-1,270.58	703.77	1,319.89	0.00	0.00	0.00	
12,900.00	90.00	179.60	10,940.00	-1,370.58	704.47	1,419.65	0.00	0.00	0.00	
13,000.00	90.00	179.60	10,940.00	-1,470.58	705.16	1,519.42	0.00	0.00	0.00	
13,100.00	90.00	179.60	10,940.00	-1,570.57	705.85	1,619.19	0.00	0.00	0.00	
13,200.00	90.00	179.60	10,940.00	-1,670.57	706.55	1,718.96	0.00	0.00	0.00	
13,300.00	90.00	179.60	10,940.00	-1,770.57	707.24	1,818.72	0.00	0.00	0.00	
13,400.00	90.00	179.60	10,940.00	-1,870.57	707.93	1,918.49	0.00	0.00	0.00	
13,500.00	90.00	179.60	10,940.00	-1,970.57	708.63	2,018.26	0.00	0.00	0.00	
13,600.00	90.00	179.60	10,940.00	-2,070.56	709.32	2,118.02	0.00	0.00	0.00	
13,700.00	90.00	179.60	10,940.00	-2,170.56	710.02	2,217.79	0.00	0.00	0.00	
13,800.00	90.00	179.60	10,940.00	-2,270.56	710.71	2,317.56	0.00	0.00	0.00	
13,900.00	90.00	179.60	10,940.00	-2,370.56	711.40	2,417.32	0.00	0.00	0.00	
14,000.00	90.00	179.60	10,940.00	-2,470.55	712.10	2,517.09	0.00	0.00	0.00	
14,100.00	90.00	179.60	10,940.00	-2,570.55	712.79	2,616.86	0.00	0.00	0.00	
14,200.00	90.00	179.60	10,940.00	-2,670.55	713.48	2,716.62	0.00	0.00	0.00	
14,300.00	90.00	179.60	10,940.00	-2,770.55	714.18	2,816.39	0.00	0.00	0.00	
14,400.00	90.00	179.60	10,940.00	-2,870.54	714.87	2,916.16	0.00	0.00	0.00	
14,500.00	90.00	179.60	10,940.00	-2,970.54	715.56	3,015.92	0.00	0.00	0.00	
14,600.00	90.00	179.60	10,940.00	-3,070.54	716.26	3,115.69	0.00	0.00	0.00	
14,700.00	90.00	179.60	10,940.00	-3,170.54	716.95	3,215.46	0.00	0.00	0.00	
14,800.00	90.00	179.60	10,940.00	-3,270.53	717.64	3,315.22	0.00	0.00	0.00	
14,900.00	90.00	179.60	10,940.00	-3,370.53	718.34	3,414.99	0.00	0.00	0.00	
15,000.00	90.00	179.60	10,940.00	-3,470.53	719.03	3,514.76	0.00	0.00	0.00	
15,100.00	90.00	179.60	10,940.00	-3,570.53	719.72	3,614.52	0.00	0.00	0.00	
15,200.00	90.00	179.60	10,940.00	-3,670.52	720.42	3,714.29	0.00	0.00	0.00	
15,300.00	90.00	179.60	10,940.00	-3,770.52	721.11	3,814.06	0.00	0.00	0.00	
15,400.00	90.00	179.60	10,940.00	-3,870.52	721.80	3,913.83	0.00	0.00	0.00	
15,500.00	90.00	179.60	10,940.00	-3,970.52	722.50	4,013.59	0.00	0.00	0.00	
15,600.00	90.00	179.60	10,940.00	-4,070.51	723.19	4,113.36	0.00	0.00	0.00	
15,700.00	90.00	179.60	10,940.00	-4,170.51	723.88	4,213.13	0.00	0.00	0.00	
15,800.00	90.00	179.60	10,940.00	-4,270.51	724.58	4,312.89	0.00	0.00	0.00	
15,900.00	90.00	179.60	10,940.00	-4,370.51	725.27	4,412.66	0.00	0.00	0.00	
16,000.00	90.00	179.60	10,940.00	-4,470.51	725.96	4,512.43	0.00	0.00	0.00	

Titan Directional Drilling

Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
16,100.00	90.00	179.60	10,940.00	-4,570.50	726.66	4,612.19	0.00	0.00	0.00	
16,200.00	90.00	179.60	10,940.00	-4,670.50	727.35	4,711.96	0.00	0.00	0.00	
16,300.00	90.00	179.60	10,940.00	-4,770.50	728.05	4,811.73	0.00	0.00	0.00	
16,400.00	90.00	179.60	10,940.00	-4,870.50	728.74	4,911.49	0.00	0.00	0.00	
16,500.00	90.00	179.60	10,940.00	-4,970.49	729.43	5,011.26	0.00	0.00	0.00	
16,600.00	90.00	179.60	10,940.00	-5,070.49	730.13	5,111.03	0.00	0.00	0.00	
16,700.00	90.00	179.60	10,940.00	-5,170.49	730.82	5,210.79	0.00	0.00	0.00	
16,800.00	90.00	179.60	10,940.00	-5,270.49	731.51	5,310.56	0.00	0.00	0.00	
16,900.00	90.00	179.60	10,940.00	-5,370.48	732.21	5,410.33	0.00	0.00	0.00	
17,000.00	90.00	179.60	10,940.00	-5,470.48	732.90	5,510.09	0.00	0.00	0.00	
17,100.00	90.00	179.60	10,940.00	-5,570.48	733.59	5,609.86	0.00	0.00	0.00	
17,200.00	90.00	179.60	10,940.00	-5,670.48	734.29	5,709.63	0.00	0.00	0.00	
17,300.00	90.00	179.60	10,940.00	-5,770.47	734.98	5,809.40	0.00	0.00	0.00	
17,400.00	90.00	179.60	10,940.00	-5,870.47	735.67	5,909.16	0.00	0.00	0.00	
17,500.00	90.00	179.60	10,940.00	-5,970.47	736.37	6,008.93	0.00	0.00	0.00	
17,600.00	90.00	179.60	10,940.00	-6,070.47	737.06	6,108.70	0.00	0.00	0.00	
17,700.00	90.00	179.60	10,940.00	-6,170.46	737.75	6,208.46	0.00	0.00	0.00	
17,800.00	90.00	179.60	10,940.00	-6,270.46	738.45	6,308.23	0.00	0.00	0.00	
17,900.00	90.00	179.60	10,940.00	-6,370.46	739.14	6,408.00	0.00	0.00	0.00	
18,000.00	90.00	179.60	10,940.00	-6,470.46	739.83	6,507.76	0.00	0.00	0.00	
18,100.00	90.00	179.60	10,940.00	-6,570.45	740.53	6,607.53	0.00	0.00	0.00	
18,200.00	90.00	179.60	10,940.00	-6,670.45	741.22	6,707.30	0.00	0.00	0.00	
18,300.00	90.00	179.60	10,940.00	-6,770.45	741.91	6,807.06	0.00	0.00	0.00	
18,400.00	90.00	179.60	10,940.00	-6,870.45	742.61	6,906.83	0.00	0.00	0.00	
18,500.00	90.00	179.60	10,940.00	-6,970.45	743.30	7,006.60	0.00	0.00	0.00	
18,600.00	90.00	179.60	10,940.00	-7,070.44	743.99	7,106.36	0.00	0.00	0.00	
18,700.00	90.00	179.60	10,940.00	-7,170.44	744.69	7,206.13	0.00	0.00	0.00	
18,800.00	90.00	179.60	10,940.00	-7,270.44	745.38	7,305.90	0.00	0.00	0.00	
18,900.00	90.00	179.60	10,940.00	-7,370.44	746.07	7,405.66	0.00	0.00	0.00	
19,000.00	90.00	179.60	10,940.00	-7,470.43	746.77	7,505.43	0.00	0.00	0.00	
19,100.00	90.00	179.60	10,940.00	-7,570.43	747.46	7,605.20	0.00	0.00	0.00	
19,200.00	90.00	179.60	10,940.00	-7,670.43	748.16	7,704.96	0.00	0.00	0.00	
19,300.00	90.00	179.60	10,940.00	-7,770.43	748.85	7,804.73	0.00	0.00	0.00	
19,400.00	90.00	179.60	10,940.00	-7,870.42	749.54	7,904.50	0.00	0.00	0.00	
19,500.00	90.00	179.60	10,940.00	-7,970.42	750.24	8,004.27	0.00	0.00	0.00	
19,600.00	90.00	179.60	10,940.00	-8,070.42	750.93	8,104.03	0.00	0.00	0.00	
19,700.00	90.00	179.60	10,940.00	-8,170.42	751.62	8,203.80	0.00	0.00	0.00	
19,800.00	90.00	179.60	10,940.00	-8,270.41	752.32	8,303.57	0.00	0.00	0.00	
19,900.00	90.00	179.60	10,940.00	-8,370.41	753.01	8,403.33	0.00	0.00	0.00	
20,000.00	90.00	179.60	10,940.00	-8,470.41	753.70	8,503.10	0.00	0.00	0.00	
20,100.00	90.00	179.60	10,940.00	-8,570.41	754.40	8,602.87	0.00	0.00	0.00	
20,200.00	90.00	179.60	10,940.00	-8,670.40	755.09	8,702.63	0.00	0.00	0.00	
20,300.00	90.00	179.60	10,940.00	-8,770.40	755.78	8,802.40	0.00	0.00	0.00	

Titan Directional Drilling


Survey Report

Company:	Kaiser-Francis Oil Company	Local Co-ordinate Reference:	Well Red Hills 206H - Slot B
Project:	Permian NM E'83	TVD Reference:	est.GL+KB @ 3426.00usft (planning)
Site:	Red Hills Pad 8	MD Reference:	est.GL+KB @ 3426.00usft (planning)
Well:	Red Hills 206H	North Reference:	Grid
Wellbore:	#206H OH	Survey Calculation Method:	Minimum Curvature
Design:	Plan #1	Database:	EDM 5k-14

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	
20,400.00	90.00	179.60	10,940.00	-8,870.40	756.48	8,902.17	0.00	0.00	0.00	
20,500.00	90.00	179.60	10,940.00	-8,970.40	757.17	9,001.93	0.00	0.00	0.00	
20,600.00	90.00	179.60	10,940.00	-9,070.39	757.86	9,101.70	0.00	0.00	0.00	
20,700.00	90.00	179.60	10,940.00	-9,170.39	758.56	9,201.47	0.00	0.00	0.00	
20,800.00	90.00	179.60	10,940.00	-9,270.39	759.25	9,301.23	0.00	0.00	0.00	
20,900.00	90.00	179.60	10,940.00	-9,370.39	759.94	9,401.00	0.00	0.00	0.00	
21,000.00	90.00	179.60	10,940.00	-9,470.39	760.64	9,500.77	0.00	0.00	0.00	
21,100.00	90.00	179.60	10,940.00	-9,570.38	761.33	9,600.53	0.00	0.00	0.00	
21,200.00	90.00	179.60	10,940.00	-9,670.38	762.02	9,700.30	0.00	0.00	0.00	
21,300.00	90.00	179.60	10,940.00	-9,770.38	762.72	9,800.07	0.00	0.00	0.00	
21,400.00	90.00	179.60	10,940.00	-9,870.38	763.41	9,899.84	0.00	0.00	0.00	
21,500.00	90.00	179.60	10,940.00	-9,970.37	764.10	9,999.60	0.00	0.00	0.00	
21,600.00	90.00	179.60	10,940.00	-10,070.37	764.80	10,099.37	0.00	0.00	0.00	
21,683.25	90.00	179.60	10,940.00	-10,153.61	765.38	10,182.42	0.00	0.00	0.00	

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")	
950.00	950.00	13 3/8"	13-3/8	17-1/2	
4,972.28	4,950.00	9 5/8"	9-5/8	12-1/4	

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
860.00	860.00	Rustler				
1,200.01	1,200.00	Salado				
2,003.85	2,000.00	Top of Salt				
4,469.16	4,450.00	Base of Salt				
4,771.03	4,750.00	Lamar				
4,891.78	4,870.00	Bell Canyon				
5,887.97	5,860.00	Cherry Canyon				
8,645.09	8,600.00	Brushy Canyon				
8,846.34	8,800.00	Lwr Brushy Canyon				
9,057.66	9,010.00	Avalon				
10,003.53	9,950.00	1 BSS				
10,567.88	10,510.00	2 BSS				



RKI

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Section 5 - Location and Types of Water Supply

Water Source Table

Water source type: OTHER

Describe type: BRINE WATER

Water source use type: INTERMEDIATE/PRODUCTION
CASING

Source latitude:

Source longitude:

Source datum:

Water source permit type: PRIVATE CONTRACT

Water source transport method: TRUCKING

Source land ownership: PRIVATE

Source transportation land ownership: OTHER

Describe transportation land ownership: Water source ownership is a mixture of Federal, State and County.

Water source volume (barrels): 20000

Source volume (acre-feet): 2.577862

Source volume (gal): 840000

Water source type: OTHER

Describe type: FRESH WATER

Water source use type: OTHER
STIMULATION
SURFACE CASING

Describe use type: ROAD & PAD CONSTRUCTION &

Source latitude:

Source longitude:

Source datum:

Water source permit type: PRIVATE CONTRACT

Water source transport method: TRUCKING

Source land ownership: PRIVATE

Source transportation land ownership: OTHER

Describe transportation land ownership: Water source ownership is a mixture of Federal, State and County.

Water source volume (barrels): 250000

Source volume (acre-feet): 32.223274

Source volume (gal): 10500000

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Water source and transportation map:

Red_Hills_Federal_Pad_8_Water_Source_20200107144842.pdf

Water source comments: Water source transportation land ownership is a mixture of Federal, State and County.

New water well? N

New Water Well Info

Well latitude:

Well Longitude:

Well datum:

Well target aquifer:

Est. depth to top of aquifer(ft):

Est thickness of aquifer:

Aquifer comments:

Aquifer documentation:

Well depth (ft):

Well casing type:

Well casing outside diameter (in.):

Well casing inside diameter (in.):

New water well casing?

Used casing source:

Drilling method:

Drill material:

Grout material:

Grout depth:

Casing length (ft.):

Casing top depth (ft.):

Well Production type:

Completion Method:

Water well additional information:

State appropriation permit:

Additional information attachment:

Section 6 - Construction Materials

Using any construction materials: YES

Construction Materials description: On site caliche will be used for construction if sufficient. In the event insufficient quantities of caliche are available onsite, caliche will be trucked in from BLM's caliche pit in NWNW Section 23-T25S-R33E or NWNW Section 1-T25S-R33E

Construction Materials source location attachment:

Section 7 - Methods for Handling Waste

Waste type: GARBAGE

Waste content description: Miscellaneous trash

Amount of waste: 500 pounds

Waste disposal frequency : One Time Only

Safe containment description: Trash produced during drilling and completion operations will be collected in a trash container and disposed of properly

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: Trucked to an approved disposal facility. (Sandpoint Landfill (solid materials dump) NW/4 Section 11-T21S-R28E

Waste type: SEWAGE

Waste content description: Human waste and grey water

Amount of waste: 1000 gallons

Waste disposal frequency : One Time Only

Safe containment description: Waste material will be stored safely and disposed of properly

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: Trucked to an approved disposal facility. (Carlsbad sewer plant SENW Section 10-T22SR27E)

Waste type: DRILLING

Waste content description: Drilling fluids and cuttings

Amount of waste: 3900 barrels

Waste disposal frequency : One Time Only

Safe containment description: All drilling fluids will be stored safely and disposed of properly

Safe containmant attachment:

Waste disposal type: HAUL TO COMMERCIAL FACILITY **Disposal location ownership:** COMMERCIAL

Disposal type description:

Disposal location description: Cuttings will be hauled to R360's facility located in Section 27-T20S-R32E on US 62/180 at Halfway, NM

Reserve Pit

Reserve Pit being used? NO

Temporary disposal of produced water into reserve pit? NO

Reserve pit length (ft.) **Reserve pit width (ft.)**

Reserve pit depth (ft.) **Reserve pit volume (cu. yd.)**

Is at least 50% of the reserve pit in cut?

Reserve pit liner

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Reserve pit liner specifications and installation description

Cuttings Area

Cuttings Area being used? NO

Are you storing cuttings on location? Y

Description of cuttings location Cuttings will be stored in roll off bins and hauled to R360's facility located in Section 27-T20S-R32E on US 62/180 at Halfway, NM

Cuttings area length (ft.)

Cuttings area width (ft.)

Cuttings area depth (ft.)

Cuttings area volume (cu. yd.)

Is at least 50% of the cuttings area in cut?

WCuttings area liner

Cuttings area liner specifications and installation description

Section 8 - Ancillary Facilities

Are you requesting any Ancillary Facilities?: N

Ancillary Facilities attachment:

Comments:

Section 9 - Well Site Layout

Well Site Layout Diagram:

Red_Hills_Fed_206H_Well_Site_Plat_20200108090102.pdf

Red_Hills_Pad_8_Drlg_Layout_20200108090102.PDF

Comments:

Section 10 - Plans for Surface Reclamation

Type of disturbance: New Surface Disturbance

Multiple Well Pad Name: RED HILLS

Multiple Well Pad Number: 8

Recontouring attachment:

Red_Hills_Fed_206H_IR_Plat_20200108090117.pdf

Drainage/Erosion control construction: During construction proper erosion control methods will be used to control erosion, runoff and siltation of the surrounding area.

Drainage/Erosion control reclamation: Proper erosion control methods will be used on the area to control erosion, runoff and siltation of the surrounding area

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Well pad proposed disturbance (acres): 5.05	Well pad interim reclamation (acres): 2.8	Well pad long term disturbance (acres): 2.25
Road proposed disturbance (acres): 0.024	Road interim reclamation (acres): 0	Road long term disturbance (acres): 0.024
Powerline proposed disturbance (acres): 0	Powerline interim reclamation (acres): 0	Powerline long term disturbance (acres): 0
Pipeline proposed disturbance (acres): 0	Pipeline interim reclamation (acres): 0	Pipeline long term disturbance (acres): 0
Other proposed disturbance (acres): 0	Other interim reclamation (acres): 0	Other long term disturbance (acres): 0
Total proposed disturbance: 5.074	Total interim reclamation: 2.8	Total long term disturbance: 2.274

Disturbance Comments:

Reconstruction method: The areas planned for interim reclamation will then be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.

Topsoil redistribution: Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations

Soil treatment: To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.

Existing Vegetation at the well pad: The historic climax plant community is a grassland dominated by black grama, dropseeds, and blue stems with sand sage and shinnery oak distributed evenly throughout. Current landscape displays mesquite, shinnery oak, yucca, desert sage, fourwing saltbush, snakeweed, and bunch grasses

Existing Vegetation at the well pad attachment:

Existing Vegetation Community at the road: Refer to "Existing Vegetation at the well pad"

Existing Vegetation Community at the road attachment:

Existing Vegetation Community at the pipeline: N/A

Existing Vegetation Community at the pipeline attachment:

Existing Vegetation Community at other disturbances: N/A

Existing Vegetation Community at other disturbances attachment:

Non native seed used? N

Non native seed description:

Seedling transplant description:

Will seedlings be transplanted for this project? N

Seedling transplant description attachment:

Will seed be harvested for use in site reclamation? N

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Seed harvest description:

Seed harvest description attachment:

Seed Management

Seed Table

Seed Summary

Total pounds/Acre:

Seed Type

Pounds/Acre

Seed reclamation attachment:

Operator Contact/Responsible Official Contact Info

First Name:

Last Name:

Phone:

Email:

Seedbed prep:

Seed BMP:

Seed method:

Existing invasive species? N

Existing invasive species treatment description:

Existing invasive species treatment attachment:

Weed treatment plan description: No invasive species present. Standard regular maintenance to maintain a clear location and road.

Weed treatment plan attachment:

Monitoring plan description: Identify areas supporting weeds prior to construction; prevent the introduction and spread of weeds from construction equipment during construction; and contain weed seeds and propagules by preventing segregated topsoil from being spread to adjacent areas. No invasive species present. Standard regular maintenance to maintain a clear location and road.

Monitoring plan attachment:

Success standards: To maintain all disturbed areas as per Gold Book standards

Pit closure description: N/A

Pit closure attachment:

Section 11 - Surface Ownership

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Disturbance type: WELL PAD

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Fee Owner: Basin Properties Ranches

Fee Owner Address: 3300 N A St, Bldg 1, Ste 220

Phone: (999)999-9999

Email:

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: Surface Use and Compensation Agreement exists between Kaiser-Francis and Basin Properties Ranches. Memorandum of SUA attached under Section 12 - Other SUPO Attachments.

Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

Disturbance type: NEW ACCESS ROAD

Describe:

Surface Owner: PRIVATE OWNERSHIP

Other surface owner description:

BIA Local Office:

BOR Local Office:

COE Local Office:

DOD Local Office:

NPS Local Office:

State Local Office:

Military Local Office:

USFWS Local Office:

Other Local Office:

USFS Region:

USFS Forest/Grassland:

USFS Ranger District:

Fee Owner: Basin Properties Ranches

Fee Owner Address: 3300 N A St, Bldg 1, Ste 220

Phone: (999)999-9999

Email:

Surface use plan certification: NO

Surface use plan certification document:

Surface access agreement or bond: AGREEMENT

Surface Access Agreement Need description: Surface Use and Compensation Agreement exists between Kaiser-Francis and Basin Properties Ranches

Surface Access Bond BLM or Forest Service:

BLM Surface Access Bond number:

USFS Surface access bond number:

Section 12 - Other Information

Right of Way needed? N

Use APD as ROW?

ROW Type(s):

ROW Applications

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: RED HILLS FEDERAL

Well Number: 206H

SUPO Additional Information:

Use a previously conducted onsite? Y

Previous Onsite information: Onsite conducted 10/22/2019 by Nik MacPhee (BLM), Eric Hanson (Kaiser-Francis) and Frank Jaramillo (Madron Surveying).

Other SUPO Attachment

SUA_for_BLM_APDs_20200108090730.pdf