

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-45844
5. Indicate Type of Lease STATE [X] FEE []
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name ZEUS STATE
8. Well Number 173H
9. OGRID Number 372043
10. Pool name or Wildcat
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3617 GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)
1. Type of Well: Oil Well [X] Gas Well [] Other []
2. Name of Operator TAP ROCK OPERATING, LLC
3. Address of Operator 602 PARK POINT DR, SUITE 200, GOLDEN, CO 80401
4. Well Location Unit Letter O : 593 feet from the S line and 1877 feet from the E line
Section 9 Township 24S Range 33E NMPM County LEA

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK [] PLUG AND ABANDON []
TEMPORARILY ABANDON [] CHANGE PLANS []
PULL OR ALTER CASING [] MULTIPLE COMPL []
DOWNHOLE COMMINGLE []
CLOSED-LOOP SYSTEM []
OTHER: []
SUBSEQUENT REPORT OF:
REMEDIAL WORK [] ALTERING CASING []
COMMENCE DRILLING OPNS. [] P AND A []
CASING/CEMENT JOB []
OTHER: Completions [X]

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/2/2019 TD well at 14671' MD and 9666' TVD.
Plug back depth at 14590'.
12/4/2019: Rig Release.
2/18/2020 to 2/28/2020: Perforate from 9835' to 14504', 3 spf at .39 inch holes with 936 total shots. 24 stage frac with 12,164,270 lbs 100 mesh sand.
3/3/2020 to 3/4/2020: Drill out plugs;
3/8/2020: Ready to Produce.

Accepted for Record - NMOCD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Regulatory Analyst DATE 6/18/2020

Type or print name Bill Ramsey E-mail address: bramsey@taprk.com PHONE: 720-360-4028

For State Use Only

APPROVED BY: TITLE DATE

Conditions of Approval (if any):