

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

OCD - HOBBS  
10/07/2020  
RECEIVED

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM0000587
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No. BELL LAKE / NMNM 068292X
2. Name of Operator KAISER FRANCIS OIL COMPANY [12361]		8. Lease Name and Well No. BELL LAKE UNIT NORTH [316707] 229H
3a. Address 6733 S. Yale Ave., Tulsa, OK 74121	3b. Phone No. (include area code) (918) 491-0000	9. API Well No. 30-025-47846
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NESE / 1980 FSL / 775 FEL / LAT 32.3318253 / LONG -103.5032206 At proposed prod. zone NWNE / 330 FNL / 1410 FEL / LAT 32.3545121 / LONG -103.5052498		10. Field and Pool, or Exploratory [98259] OJO CHISO/WOLFCAMP, SOUTHWEST
14. Distance in miles and direction from nearest town or post office* 20 miles		11. Sec., T, R, M, or Blk. and Survey or Area SEC 6/T23S/R34E/NMP
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 660 feet	16. No of acres in lease 634.55	17. Spacing Unit dedicated to this well 480.0
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 30 feet	19. Proposed Depth 10248 feet / 18423 feet	20. BLM/BIA Bond No. in file FED: WYB000055
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3454 feet	22. Approximate date work will start* 03/01/2020	23. Estimated duration 40 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

25. Signature (Electronic Submission)	Name (Printed/Typed) MELANIE WILSON / Ph: (918) 491-0000	Date 08/26/2020
Title Regulatory Analyst		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575) 234-5959	Date 09/29/2020
Title Assistant Field Manager Lands & Minerals Carlsbad Field Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GCP Rec 10/07/2020

SL

(Continued on page 2)

APPROVED WITH CONDITIONS  
Approval Date: 09/29/2020

KZ  
10/19/2020

\*(Instructions on page 2)

## INSTRUCTIONS

**GENERAL:** This form is designed for submitting proposals to perform certain well operations, as indicated on Federal and Indian lands and leases for action by appropriate Federal agencies, pursuant to applicable Federal laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from local Federal offices.

**ITEM I:** If the proposal is to redrill to the same reservoir at a different subsurface location or to a new reservoir, use this form with appropriate notations. Consult applicable Federal regulations concerning subsequent work proposals or reports on the well.

**ITEM 4:** Locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local Federal offices for specific instructions.

**ITEM 14:** Needed only when location of well cannot readily be found by road from the land or lease description. A plat, or plats, separate or on the reverse side, showing the roads to, and the surveyed location of, the well, and any other required information, should be furnished when required by Federal agency offices.

**ITEMS 15 AND 18:** If well is to be, or has been directionally drilled, give distances for subsurface location of hole in any present or objective productive zone.

**ITEM 22:** Consult applicable Federal regulations, or appropriate officials, concerning approval of the proposal before operations are started.

**ITEM 24:** If the proposal will involve hydraulic fracturing operations, you must comply with 43 CFR 3162.3-3, including providing information about the protection of usable water. Operators should provide the best available information about all formations containing water and their depths. This information could include data and interpretation of resistivity logs run on nearby wells. Information may also be obtained from state or tribal regulatory agencies and from local BLM offices.

## NOTICES

The Privacy Act of 1974 and regulation in 43 CFR 2.48(d) provide that you be furnished the following information in connection with information required by this application.

**AUTHORITY:** 30 U.S.C. 181 et seq., 25 U.S.C. 396; 43 CFR 3160

**PRINCIPAL PURPOSES:** The information will be used to: (1) process and evaluate your application for a permit to drill a new oil, gas, or service well or to reenter a plugged and abandoned well; and (2) document, for administrative use, information for the management, disposal and use of National Resource Lands and resources including (a) analyzing your proposal to discover and extract the Federal or Indian resources encountered; (b) reviewing procedures and equipment and the projected impact on the land involved; and (c) evaluating the effects of the proposed operation on the surface and subsurface water and other environmental impacts.

**ROUTINE USE:** Information from the record and/or the record will be transferred to appropriate Federal, State, and local or foreign agencies, when relevant to civil, criminal or regulatory investigations or prosecution, in connection with congressional inquiries and for regulatory responsibilities.

**EFFECT OF NOT PROVIDING INFORMATION:** Filing of this application and disclosure of the information is mandatory only if you elect to initiate a drilling or reentry operation on an oil and gas lease.

The Paperwork Reduction Act of 1995 requires us to inform you that:

The BLM connects this information to a new evaluation of the technical, safety, and environmental factors involved with drilling for oil and/or gas on Federal and Indian oil and gas leases. This information will be used to analyze and approve applications. Response to this request is mandatory only if the operator elects to initiate drilling or reentry operations on an oil and gas lease. The BLM would like you to know that you do not have to respond to this or any other Federal agency-sponsored information collection unless it displays a currently valid OMB control number.

**BURDEN HOURS STATEMENT:** Public reporting burden for this form is estimated to average 8 hours per response, including the time for reviewing instructions, gathering and maintaining data, and completing and reviewing the form. Direct comments regarding the burden estimate or any other aspect of this form to U.S. Department of the Interior, Bureau of Land Management (1004-0137), Bureau Information Connection Clearance Officer (WO-630), 1849 C Street, N.W., Mail Stop 401 LS, Washington, D.C. 20240.



APD ID: 10400049821

Submission Date: 08/26/2020

Highlighted data  
reflects the most  
recent changes

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: BELL LAKE UNIT NORTH

Well Number: 229H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - General

APD ID: 10400049821

Tie to previous NOS? N

Submission Date: 08/26/2020

BLM Office: CARLSBAD

User: Melanie Wilson

Title: Regulatory Analyst

Federal/Indian APD: FED

Is the first lease penetrated for production Federal or Indian? FED

Lease number: NMNM0000587

Lease Acres: 634.55

Surface access agreement in place?

Allotted?

Reservation:

Agreement in place? YES

Federal or Indian agreement: FEDERAL

Agreement number: NMNM068292X

Agreement name: BELL LAKE

Keep application confidential? Y

Permitting Agent? YES

APD Operator: KAISER FRANCIS OIL COMPANY

Operator letter of designation:

## Operator Info

Operator Organization Name: KAISER FRANCIS OIL COMPANY

Operator Address: 6733 S. Yale Ave.

Zip: 74121

Operator PO Box: PO Box 21468

Operator City: Tulsa

State: OK

Operator Phone: (918)491-0000

Operator Internet Address:

## Section 2 - Well Information

Well in Master Development Plan? NO

Master Development Plan name:

Well in Master SUPO? NO

Master SUPO name:

Well in Master Drilling Plan? NO

Master Drilling Plan name:

Well Name: BELL LAKE UNIT NORTH

Well Number: 229H

Well API Number:

Field/Pool or Exploratory? Field and Pool

Field Name: OJO CHISO

Pool Name: WOLFCAMP,  
SOUTHWEST

Is the proposed well in an area containing other mineral resources? NATURAL GAS,OIL

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

**Is the proposed well in an area containing other mineral resources?** NATURAL GAS,OIL

**Is the proposed well in a Helium production area?** N

**Use Existing Well Pad?** N

**New surface disturbance?**

**Type of Well Pad:** MULTIPLE WELL

**Multiple Well Pad Name:**  
NORTH BELL LAKE UNIT

**Number:** 11

**Well Class:** HORIZONTAL

**Number of Legs:** 1

**Well Work Type:** Drill

**Well Type:** OIL WELL

**Describe Well Type:**

**Well sub-Type:** EXPLORATORY (WILDCAT)

**Describe sub-type:**

**Distance to town:** 20 Miles

**Distance to nearest well:** 30 FT

**Distance to lease line:** 660 FT

**Reservoir well spacing assigned acres Measurement:** 480 Acres

**Well plat:** BLUN\_229H\_C102\_20191024182134.pdf

**Well work start Date:** 03/01/2020

**Duration:** 40 DAYS

### Section 3 - Well Location Table

**Survey Type:** RECTANGULAR

**Describe Survey Type:**

**Datum:** NAD83

**Vertical Datum:** NAVD88

**Survey number:** 5930

**Reference Datum:** GROUND LEVEL

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
SHL Leg #1	198 0	FSL	775	FEL	23S	34E	6	Aliquot NESE	32.33182 53	- 103.5032 206	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 000124 4A	345 4	0	0	N
KOP Leg #1	198 0	FSL	775	FEL	23S	34E	6	Aliquot NESE	32.33182 53	- 103.5032 206	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 000124 4A	- 606 1	951 5	951 5	N
PPP Leg #1-1	264 0	FNL	131 0	FEL	23S	34E	6	Aliquot SENE	32.33364 7	- 103.5049 53	LEA	NEW MEXI CO	NEW MEXI CO	F	NMNM 000058 7	- 679 3	108 35	102 47	Y

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

Wellbore	NS-Foot	NS Indicator	EW-Foot	EW Indicator	Twsp	Range	Section	Aliquot/Lot/Tract	Latitude	Longitude	County	State	Meridian	Lease Type	Lease Number	Elevation	MD	TVD	Will this well produce from this lease?
PPP Leg #1-2	2600	FNL	1310	FEL	23S	34E	6	Aliquot SWNE	32.3337577	- 103.5049519	LEA	NEW MEXICO	NEW MEXICO	F	NMNM0000587	- 6794	10872	10248	Y
PPP Leg #1-3	0	FSL	1330	FEL	22S	34E	31	Aliquot SWSE	32.340902	- 103.505056	LEA	NEW MEXICO	NEW MEXICO	F	NMLC0070544B	- 6794	13472	10248	Y
PPP Leg #1-4	2640	FNL	1410	FEL	22S	34E	31	Aliquot SWNE	32.345409	- 103.505118	LEA	NEW MEXICO	NEW MEXICO	F	NMLC0070544A	- 6794	15112	10248	Y
EXIT Leg #1	330	FNL	1410	FEL	22S	34E	31	Aliquot NWNE	32.3545121	- 103.5052498	LEA	NEW MEXICO	NEW MEXICO	F	NMLC0070544A	- 6794	18423	10248	Y
BHL Leg #1	330	FNL	1410	FEL	22S	34E	31	Aliquot NWNE	32.3545121	- 103.5052498	LEA	NEW MEXICO	NEW MEXICO	F	NMLC0070544A	- 6794	18423	10248	Y



District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

<sup>1</sup> API Number 30-025-	<sup>2</sup> Pool Code 98259	<sup>3</sup> Pool Name Ojo Chiso:Bone Spring, Southwest
<sup>4</sup> Property Code 316707	<sup>5</sup> Property Name BELL LAKE UNIT NORTH	<sup>6</sup> Well Number 229H
<sup>7</sup> OGRID No. 12361	<sup>8</sup> Operator Name KAISER-FRANCIS OIL COMPANY	<sup>9</sup> Elevation 3454.2

<sup>10</sup> Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	6	23 S	34 E		1980	SOUTH	775	EAST	LEA

<sup>11</sup> Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	31	22 S	34 E		330	NORTH	1410	EAST	LEA

<sup>12</sup> Dedicated Acres 480	<sup>13</sup> Joint or Infill	<sup>14</sup> Consolidation Code	<sup>15</sup> Order No. R-14527A
--------------------------------------	-------------------------------	----------------------------------	-------------------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<p>NW CORNER SEC. 31 LAT. = 32.3554149°N LONG. = 103.5175188°W NMSP EAST (FT) N = 493991.59 E = 793253.54</p> <p>W Q CORNER SEC. 31 LAT. = 32.3481597°N LONG. = 103.5175050°W NMSP EAST (FT) N = 491352.17 E = 793277.92</p> <p>NW CORNER SEC. 6 LAT. = 32.3409003°N LONG. = 103.5175014°W NMSP EAST (FT) N = 488711.17 E = 793299.16</p> <p>W Q CORNER SEC. 6 LAT. = 32.3336453°N LONG. = 103.5175046°W NMSP EAST (FT) N = 486071.76 E = 793318.27</p> <p>SW CORNER SEC. 6 LAT. = 32.3263895°N LONG. = 103.5175066°W NMSP EAST (FT) N = 483432.09 E = 793337.75</p> <p>N 89°32'19"E 2561.05 FT N 89°32'08"E 2638.83 FT 1410' BOTTOM OF HOLE N Q CORNER SEC. 31 LAT. = 32.3699315°N LONG. = 103.5175204°W NMSP EAST (FT) N = 498272.83 E = 795212.79 BOTTOM OF HOLE LAT. = 32.3545121°N LONG. = 103.5052498°W NMSP EAST (FT) N = 493692.24 E = 797044.74 NOTE: LATITUDE AND LONGITUDE COORDINATES ARE SHOWN USING THE NORTH AMERICAN DATUM OF 1983 (NAD83) LISTED NEW MEXICO STATE PLANE EAST COORDINATES ARE GRID (NAD83) BASIS OF BEARING AND DISTANCES USED ARE NEW MEXICO STATE PLANE EAST COORDINATES MODIFIED TO THE SURFACE. VERTICAL DATUM NAVD83. N 01°08'29"W 7552.66 FT N 89°32'55"E 2546.53 FT N 89°32'29"E 2641.19 FT N Q CORNER SEC. 6 LAT. = 32.3409018°N LONG. = 103.5092579°W NMSP EAST (FT) N = 488731.23 E = 795845.16 FIRST TAKE POINT BELL LAKE UNIT NORTH 229H ELEV. = 3454.2' LAT. = 32.3318253°N (NAD83) LONG. = 103.5032206°W NMSP EAST (FT) N = 485443.55 E = 797735.37 N 37°42'15"W 883.47 FT SURFACE LOCATION S Q CORNER SEC. 6 LAT. = 32.3263876°N LONG. = 103.5092598°W NMSP EAST (FT) N = 483450.91 E = 795885.19 S 89°34'36"W 2547.96 FT S 89°36'07"W 2641.15 FT</p>	<p>NE CORNER SEC. 31 LAT. = 32.3554203°N LONG. = 103.5006833°W NMSP EAST (FT) N = 494033.60 E = 798452.33</p> <p>E Q CORNER SEC. 31 LAT. = 32.3481622°N LONG. = 103.5006950°W NMSP EAST (FT) N = 491393.03 E = 798469.27</p> <p>NE CORNER SEC. 6 LAT. = 32.3409038°N LONG. = 103.5007079°W NMSP EAST (FT) N = 488752.37 E = 798485.80</p> <p>FIRST TAKE POINT 2600' FNL, 1310' FEL LAT. = 32.3337577°N LONG. = 103.5049519°W NMSP EAST (FT) N = 797195.15 E = 486142.41</p> <p>E Q CORNER SEC. 6 LAT. = 32.3336332°N LONG. = 103.5007116°W NMSP EAST (FT) N = 486107.27 E = 798505.21</p> <p>SE CORNER SEC. 6 LAT. = 32.3263820°N LONG. = 103.5007113°W NMSP EAST (FT) N = 483469.26 E = 798525.81</p>	<p><b>17 OPERATOR CERTIFICATION</b> I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division. <i>Melanie Wilson</i> 10/18/19 Signature Date Melanie Wilson Printed Name mjp1692@gmail.com E-mail Address</p> <p><b>18 SURVEYOR CERTIFICATION</b> I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. JANUARY 12, 2018 Date of Survey <i>[Signature]</i> Signature and Seal of Professional Surveyor Certificate Number: JILIMON F. JARAMILLO, PLS 12/19/ SURVEY NO. 5930</p>
--	--	--



APD ID: 10400049821

Submission Date: 08/26/2020

Highlighted data  
reflects the most  
recent changes

Operator Name: KAISER FRANCIS OIL COMPANY

Well Name: BELL LAKE UNIT NORTH

Well Number: 229H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
567497	---	3454	0	0	OTHER : Surface	NONE	N
567498	RUSTLER	2107	1347	1347	SANDSTONE	NONE	N
567499	SALADO	1732	1722	1722	SALT	NONE	N
567500	TOP SALT	1432	2022	2022	SALT	NONE	N
567501	BASE OF SALT	-1568	5022	5022	SALT	NONE	N
567502	LAMAR	-1768	5222	5222	SANDSTONE	NATURAL GAS, OIL	N
567503	BELL CANYON	-1843	5297	5297	SANDSTONE	NATURAL GAS, OIL	N
567504	CHERRY CANYON	-2693	6147	6147	SANDSTONE	NATURAL GAS, OIL	N
567505	BRUSHY CANYON	-4118	7572	7572	SANDSTONE	NATURAL GAS, OIL	N
567506	BONE SPRING	-5258	8712	8712	LIMESTONE	NATURAL GAS, OIL	N
567507	AVALON SAND	-5518	8972	8972	SANDSTONE	NATURAL GAS, OIL	N
567508	BONE SPRING 1ST	-6368	9822	9822	SANDSTONE	NATURAL GAS, OIL	N
567515	BONE SPRING 2ND	-6968	10422	10422	SANDSTONE	NATURAL GAS, OIL	Y
571195	BONE SPRING LIME	-7368	10822	10822	LIMESTONE	NATURAL GAS, OIL	N

## Section 2 - Blowout Prevention

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

**Pressure Rating (PSI):** 5M

**Rating Depth:** 13000

**Equipment:** A 5M system will be installed according to Onshore Order #2 consisting of an Annular Preventer, BOP with two rams, a blind ram and safety valves and appropriate handles located on the rig floor. BOP will be equipped with 2 side outlets (choke side shall be a minimum 3 line, and kill side will be a minimum 2 line). Kill line will be installed with (2) valves and a check valve (2 min) of proper pressure rating for the system. Remote kill line (2 min) will be installed and ran to the outer edge of the substructure and be unobstructed. A manual and hydraulic valve (3 min) will be installed on the choke line, 3 chokes will be used with one being remotely controlled. Fill up line will be installed above the uppermost preventer. Pressure gauge of proper pressure rating will be installed on choke manifold. Upper and lower kelly cocks will be utilized with handles readily available in plain sight. A float sub will be available at all times. All connections subject to well pressure will be flanged, welded, or clamped.

**Requesting Variance?** YES

**Variance request:** Flex Hose Variance

**Testing Procedure:** BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all of the components installed will be functional and tested.

**Choke Diagram Attachment:**

BLUN\_229H\_Choke\_Manifold\_20191020171636.pdf

**BOP Diagram Attachment:**

BLUN\_229H\_Flex\_Hose\_20191020171651.pdf

BLUN\_229H\_BOP2\_20200826105325.pdf

BLUN\_229H\_Wellhead\_Diagram\_20200826105326.pdf

### Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.375	NEW	API	N	0	1350	0	1350	3454	2104	1350	J-55	54.5	BUTT	2.1	5	DRY	14.2	DRY	13.3
2	INTERMEDIATE	12.25	9.625	NEW	API	N	0	5200	0	5200		-1746	5200	HCP-110	40	LT&C	1.9	3.5	DRY	6.4	DRY	6.4
3	PRODUCTION	8.75	5.5	NEW	API	N	0	18423	0	10248		-6794	18423	P-110	20	OTHER - GB CD Butt	2.3	2.7	DRY	3.3	DRY	3.1

### Casing Attachments



**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

#### Casing Attachments

---

**Casing ID:** 1      **String Type:** SURFACE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

BLUN\_229H\_Csg\_Assumptions\_20191020171947.pdf

---

**Casing ID:** 2      **String Type:** INTERMEDIATE

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

BLUN\_229H\_Csg\_Assumptions\_20191020171813.pdf

---

**Casing ID:** 3      **String Type:** PRODUCTION

**Inspection Document:**

**Spec Document:**

**Tapered String Spec:**

**Casing Design Assumptions and Worksheet(s):**

BLUN\_229H\_Prod\_Csg\_Specs\_20191020171905.pdf

---

#### Section 4 - Cement

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	1350	730	1.74	13.5	1275	75	HALCEM	4% Bentonite
SURFACE	Tail		0	1350	300	1.3	14.8	400	75	HalCem	0.125 #/sk Poly Flake
INTERMEDIATE	Lead		0	5200	1000	2.08	12.5	2089	75	Econocem	3#/sk KolSeal
INTERMEDIATE	Tail		0	5200	380	1.33	14.8	506	75	Halcem	none
PRODUCTION	Lead		4000	1842 3	425	3.48	10.5	1482	10	NeoCem	2#/sk Kol Seal
PRODUCTION	Tail		4000	1842 3	2425	1.22	14.5	2966	10	Versacem	None

### Section 5 - Circulating Medium

**Mud System Type:** Closed

**Will an air or gas system be Used?** NO

**Description of the equipment for the circulating system in accordance with Onshore Order #2:**

**Diagram of the equipment for the circulating system in accordance with Onshore Order #2:**

**Describe what will be on location to control well or mitigate other conditions:** Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all time.

**Describe the mud monitoring system utilized:** PVT/Pason/Visual Monitoring

### Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
5200	1024 8	OIL-BASED MUD	8.7	8.9							
1350	5200	OIL-BASED MUD	8.7	8.9							
0	1350	OTHER : Fresh Water	8.4	9							

**Operator Name:** KAISER FRANCIS OIL COMPANY

**Well Name:** BELL LAKE UNIT NORTH

**Well Number:** 229H

## Section 6 - Test, Logging, Coring

**List of production tests including testing procedures, equipment and safety measures:**

Top of cement on production casing will be determined by calculation.

**List of open and cased hole logs run in the well:**

DIRECTIONAL SURVEY, GAMMA RAY LOG, MUD LOG/GEOLOGIC LITHOLOGY LOG, MUD LOG/GEOLOGICAL LITHOLOGY LOG,

**Coring operation description for the well:**

None planned

## Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 4437

**Anticipated Surface Pressure:** 2182

**Anticipated Bottom Hole Temperature(F):** 165

**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO

**Describe:**

**Contingency Plans geohazards description:**

**Contingency Plans geohazards attachment:**

**Hydrogen Sulfide drilling operations plan required?** YES

**Hydrogen sulfide drilling operations plan:**

BLUN\_229H\_H2S\_PLAN\_20191020172602.pdf

## Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

BLUN\_229H\_Directional\_Plan\_20191020172615.pdf

**Other proposed operations facets description:**

Gas Capture Plan attached

**Other proposed operations facets attachment:**



BLUN\_Pad\_11\_GCP\_20191020172703.pdf

**Other Variance attachment:**

BLUN\_229H\_Flex\_Hose\_20191020172715.pdf

BLUN\_229H\_MultiBowl\_Wellhead\_20191020172831.pdf

**10M Choke Manifold  
Cactus Rig 171  
Kaiser Francis Oil Company**





# Certificate of Registration

**APIQR® REGISTRATION NUMBER**

**3042**

*This certifies that the quality management system of*

**COPPER STATE RUBBER, INC.  
10485 W. Roosevelt Street  
Avondale, AZ**

*has been assessed by the American Petroleum Institute Quality Registrar (APIQR®) and  
found it to be in conformance with the following standard:*

**ISO 9001:2015**

*The scope of this registration and the approved quality management system applies to the*  
**Design and Manufacture of Oilfield, Marine and Other Industrial Hoses**

*APIQR® approves the organization's justification for excluding:*

**No Exclusions Identified as Applicable**

**Effective Date: APRIL 21, 2019**  
**Expiration Date: APRIL 21, 2022**  
**Registered Since: APRIL 21, 2016**

*Vice President of Global  
Industry Services*

Accredited by Member of  
the International  
Accreditation Forum  
Multilateral Recognition  
Arrangement for Quality  
Management Systems



This certificate is valid for the period specified herein. The registered organization must continually meet all requirements of APIQR's Registration Program and the requirements of the Registration Agreement. Registration is maintained and regularly monitored through annual full system audits. Further clarifications regarding the scope of this certificate and the applicability of ISO 9001 standard requirements may be obtained by consulting the registered organization. This certificate has been issued from APIQR offices located at 200 Massachusetts Avenue, NW Suite 1100, Washington, DC 20001-5571, U.S.A., it is the property of APIQR, and must be returned upon request. To verify the authenticity of this certificate, go to [www.api.org/compositelist](http://www.api.org/compositelist).



2018-152 | 02.19  
Digital



Kaiser-Francis Oil Company  
Bell Lake Unit North 229H  
Casing Assumptions

Interval	Length	Casing Size	Weight (#/ft)	Grade	Thread	Condition	Hole Size	TVD (ft)	Mud Type	Mud Weight Hole Control	Viscosity	Fluid Loss	Anticipated Mud Weight (ppg)	Max Pore Pressure (psi)	Collapse (psi)	Burst (psi)	Body Tensile Strength	Joint Tensile Strength	Collapse Safety Factor (Min 1.1)	Burst Safety Factor (Min 1.0)	Body Tensile Safety Factor (Min 1.8)	Joint Tensile Safety Factor (Min 1.8)
Conductor	120'	20"				New		120														
Surface	1350'	13-3/8"	54.5	J-55	BTC	New	17-1/2"	1177	FW	8.4 - 9.0	32 - 34	NC	9	551	1130	2730	853000	909000	2.1	5.0	13.3	14.2
Intermediate	5200'	9-5/8"	40	HCP-110	LTC	New	12-1/4"	4922	OBM	8.7-8.9	28	NC	8.9	2278	4230	7900	1260000	1266000	1.9	3.5	6.4	6.4
Production	18423	5-1/2"	20	P110	GBCD	New	8-3/4"	10248	OBM	8.7 - 8.9	28-29	NC	8.9	4743	11100	12640	641000	667000	2.3	2.7	3.1	3.3

**KAISER-FRANCIS OIL COMPANY  
HYDROGEN SULFIDE (H<sub>2</sub>S) CONTINGENCY PLAN  
FOR DRILLING/COMPLETION WORKOVER/FACILITY**

**Bell Lake Unit North  
SECTION 1 -T23S-R33E  
SECTION 6 -T23S-R34E  
SECTION 5 -T23S-R34E**

**LEA COUNTY, NM**

This well/facility is not expected to have H<sub>2</sub>S, but due to the sensitive location, the following is submitted as requested.

## TABLE OF CONTENTS

Emergency Response Activation and General Responsibilities	3
Individual Responsibilities During An H <sub>2</sub> S Release	4
Procedure For Igniting An Uncontrollable Condition	5
Emergency Phone Numbers	6
Protection Of The General Public/Roe	7
Characteristics Of H <sub>2</sub> S And SO <sub>2</sub>	8
Training	8
Public Relations	8
Maps	

## **EMERGENCY RESPONSE ACTIVATION AND GENERAL RESPONSIBILITIES**

### **Activation of the Emergency Action Plan**

In the event of any emergency situation, all personnel on location should first ensure that the following items are initiated. After that, they should refer to the appropriate Specific Emergency Guidance sections below for further responsibilities:

1. Notify the senior ranking contract representative on site.
2. Notify Kaiser-Francis representative in charge.
3. Notify civil authorities if the Kaiser-Francis Representative cannot be contacted and the situation dictates.
4. Perform rescue and first aid as required (without jeopardizing additional personnel).

### **General Responsibilities**

In the event of an H<sub>2</sub>S emergency, the following plan will be initiated.

- 1) All personnel will immediately evacuate to an up-wind and if possible up-hill "safe area".
- 2) If for any reason a person must enter the hazardous area, they must wear a SCBA (Self contained breathing apparatus).
- 3) Always use the "buddy system".
- 4) Isolate the well/problem if possible.
- 5) Account for all personnel
- 6) Display the proper colors, warning all unsuspecting personnel of the danger at hand
- 7) Contact the Company personnel as soon as possible if not at the location. (use the enclosed call list as instructed)

At this point the company representative will evaluate the situation and coordinate the necessary duties to bring the situation under control, and if necessary, the notification of emergency response agencies and residents.

## **INDIVIDUAL RESPONSIBILITIES DURING AN H<sub>2</sub>S RELEASE**

The following procedures and responsibilities will be implemented on activation of the H<sub>2</sub>S siren and lights.

### **All Personnel:**

1. On alarm, don escape unit (if available) and report to upwind briefing area.

### **Rig Manager/Tool Pusher:**

1. Check that all personnel are accounted for and their condition.
2. Administer or arrange for first aid treatment, and/or call EMTs as needed.
3. Identify two people best suited to secure well and perform rescue, and instruct them to don SCBA.
4. Notify Contract management and Kaiser-Francis Representative.
5. Remain at the briefing area, assess and monitor personnel and overall situation for hazards or conditions that might warrant a change in the action plan.

### **Two People Responsible for Shut-in and Rescue:**

1. Don SCBA and acquire tools to secure well and perform rescue, i.e., wrenches, retrieval ropes, etc.
2. Utilize the buddy system to secure well and perform rescue(s).
3. Return to the briefing area and stand by for further instructions.

### **All Other Personnel:**

1. Isolate the area and prevent entry by other persons into the 100 ppm ROE. Additionally the first responder(s) must evacuate any public places encompassed by the 100 ppm ROE. First responder(s) must take care not to injure themselves during this operation. Company and/or local officials must be contacted to aid in this operation. Evacuation of the public should be beyond the 100 ppm ROE.

### **Kaiser-Francis Oil Company Representative:**

1. Remain at the briefing area, assess and monitor personnel and overall situation for hazards or conditions that might warrant a change in the action plan.
2. Notify company management or Local Incident Commander, and Police, Fire Department, or other local emergency services as required.



#### **PROCEDURE FOR IGNITING AN UNCONTROLLABLE CONDITION:**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police shall be the Incident Command of any major release.

The decision to ignite a well should be a last resort and one if not both of the following pertain.

- 1) Human life and/or property are in danger.
- 2) There is no hope of bringing the situation under control with the prevailing conditions at the site.

#### **INSTRUCTIONS FOR IGNITION:**

- 1) Two people are required. They must be equipped with positive pressure; self contained breathing apparatus and a "D"-ring style, full body, OSHA approved safety harness. Non-flammable rope will be attached.
- 2) One of the people will be a qualified safety person who will test the atmosphere for H<sub>2</sub>S, Oxygen, & LFL. The other person will be the company supervisor; he is responsible for igniting the well.
- 3) Ignite up-wind from a distance no closer than necessary. Make sure that where you ignite from has the maximum escape avenue available. A 25mm flare gun shall be used, with a +/-500' range to ignite the gas.
- 4) Prior to ignition, make a final check for combustible gases.
- 5) Following ignition, continue with the emergency actions & procedures as before.

#### **CONTACTING AUTHORITIES**

Kaiser-Francis personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. This response plan must be in coordination with the State of New Mexico's 'Hazardous Materials Emergency Response Plan' (HMER).

EMERGENCY CALL LIST: (Start and continue until ONE of these people have been reached)

	<u>OFFICE</u>	<u>MOBILE</u>
Kaiser-Francis Oil Co.	918/494-0000	
Bill Wilkinson	580/668-2335	580/221-4637
David Zerger	918/491-4350	918/557-6708
Charles Lock	918/491-4337	918/671-6510
Stuart Blake	918/491-4347	918/510-4126
Robert Sanford	918/491-4201	918/770-2682
Eric Hansen	918/491-4339	918/527-5260

EMERGENCY RESPONSE NUMBERS: Lea County, New Mexico

State Police – Artesia	575/748-9718
State Police – Hobbs	575/392-5580
State Police – Carlsbad	575/885-3138
Lea County Sheriff - Lovington	575/396-3611
Local Emergency Planning Center – Lea County	575/396-8607
Local Emergency Planning Center – Eddy County	575/885-3581
Fire Fighting, Rescue & Ambulance – Carlsbad	911 or 575/885-3125
Fire Fighting, Rescue & Ambulance – Hobbs	911 or 575/397-9308
Fire Fighting – Jal Volunteer Fire Department	911 or 505/395-2221
New Mexico Oil & Gas Commission – Artesia	575/748-1283
New Mexico Oil & Gas Commission – Hobbs	575/393-6161
Air Medical Transport Services – Hobbs	800/550-1025
Med Flight Air Ambulance – Albuquerque	505/842-4433
Angel MedFlight	844/553-9033
DXP	432/580-3770
BJ Services	575/392-5556
Halliburton	575/392-6531 800/844-8451

## PROTECTION OF THE GENERAL PUBLIC/ROE:

In the event of a release with a concentration greater than 100 ppm H<sub>2</sub>S, the ROE (Radius of Exposure) calculations will be done to determine if the following conditions have been met:

- Does the 100 ppm ROE include any public area (any place not associated with this site)
- Does the 500 ppm ROE include any public road (any road which the general public may travel)
- Is the 100 ppm ROE equal to or greater than 3000 feet

If any one of these conditions have been met then the Contingency Plan will be implemented. The following shows how to calculate the radius of exposure and an example.

### **Calculation for the 100 ppm ROE:**

$$X = [(1.589)(\text{concentration})(Q)]^{(0.6258)}$$

(H<sub>2</sub>S concentrations in decimal form)

10,000 ppm +=1.+

1,000 ppm +=.1+

100 ppm +=.01+

10 ppm +=.001+

### **Calculation for the 500 ppm ROE:**

$$X+[(0.4546)(\text{concentration})(Q)]^{(0.6258)}$$

EXAMPLE: If a well/facility has been determined to have 150 ppm H<sub>2</sub>S in the gas mixture and the well/facility is producing at a gas rate of 200 MCFPD then:

ROE for 100 PPM  $X=[(1.589)(.0150)(200)]^{(0.6258)}$

$$X=2.65'$$

ROE for 500 PPM  $X=[(.4546)(.0150)(200)]^{(0.6258)}$

$$X=1.2'$$

(These calculations will be forwarded to the appropriate District NMOCD office when applicable.)

## PUBLIC EVACUATION PLAN:

(When the supervisor has determined that the General Public will be involved, the following plan will be implemented)

- 1) Notification of the emergency response agencies of the hazardous condition and Implement evacuation procedures.
- 2) A trained person in H<sub>2</sub>S safety, shall monitor with detection equipment the H<sub>2</sub>S Concentration, wind and area of exposure (ROE). This person will determine the outer perimeter of the hazardous area. The extent of the evacuation area will be determined from the data being collected. Monitoring shall continue until the situation has been resolved. **(All monitoring equipment will be UL approved, for use in class I groups A,B,C & D, Division I, hazardous locations. All monitors will have a minimum capability of measuring H<sub>2</sub>S, oxygen, and flammable values.)**
- 3) Law enforcement shall be notified to set up necessary barriers and maintain such for the duration of the situation as well as aid in the evacuation procedure.
- 4) The company supervising personnel shall stay in communication with all agencies through out the duration of the situation and inform such agencies when the situation has been contained and the effected area(s) is safe to enter.

### **CHARACTERISTICS OF H<sub>2</sub>S AND SO<sub>2</sub>**

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H <sub>2</sub> S	1.189 Air = 1	10 ppm	100 ppm	600 ppm
Sulfur Dioxide	SO <sub>2</sub>	2.21 Air = 1	2 ppm	N/A	1000 ppm

### **TRAINING:**

All responders must have training in the detection of H<sub>2</sub>S measures for protection against the gas, equipment used for protection and emergency response. Weekly drills by all crews will be conducted and recorded in the IADC daily log. Additionally, responders must be equipped with H<sub>2</sub>S monitors at all times.

### **PUBLIC RELATIONS**

Kaiser-Francis recognizes that the news media have a legitimate interest in incidents at Kaiser-Francis facilities that could affect the public. It is to the company's benefit to cooperate with the news media when incidents occur because these media are our best liaison with the public.

Our objective is to see that all reports of any emergency are factual and represent the company's position fairly and accurately. Cooperation with news media representatives is the most reliable guarantee that this objective will be met.

All contract and Kaiser-Francis employees are instructed **NOT** to make any statement to the media concerning the emergency incident. If a media representative contacts any employee, they should refer them to the designated Emergency Command Center where they should contact the Incident Commander or his designated relief for any information concerning the incident.



## **Kaiser Francis**

**Bell Lake Unit North 229H**  
**Bell Lake Unit North 229H**  
**Bell Lake Unit North 229H**  
**Bell Lake Unit North 229H**

**Plan: 190913 Bell Lake Unit North 229H**

## **Morcor Standard Plan**

**13 September, 2019**



**Morcor Engineering**  
Morcor Standard Plan

<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

<b>Project</b>	Bell Lake Unit North 229H		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Mean Sea Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		

<b>Site</b>	Bell Lake Unit North 229H		
<b>Site Position:</b>		<b>Northing:</b>	485,443.55 usft
<b>From:</b>	Map	<b>Easting:</b>	797,735.37 usft
<b>Position Uncertainty:</b>	1.0 usft	<b>Slot Radius:</b>	17-1/2 "
		<b>Latitude:</b>	32° 19' 54.571 N
		<b>Longitude:</b>	103° 30' 11.594 W
		<b>Grid Convergence:</b>	0.44 °

<b>Well</b>	Bell Lake Unit North 229H		
<b>Well Position</b>	<b>+N/-S</b>	0.0 usft	<b>Northing:</b>
	<b>+E/-W</b>	0.0 usft	<b>Easting:</b>
<b>Position Uncertainty</b>		1.0 usft	<b>Wellhead Elevation:</b>
			usft
			<b>Latitude:</b>
			32° 19' 54.571 N
			<b>Longitude:</b>
			103° 30' 11.594 W
			<b>Ground Level:</b>
			3,454.2 usft

<b>Wellbore</b>	Bell Lake Unit North 229H				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF2010	9/13/2019	6.54	60.08	47,863

<b>Design</b>	190913 Bell Lake Unit North 229H			
<b>Audit Notes:</b>				
<b>Version:</b>	<b>Phase:</b>	PLAN	<b>Tie On Depth:</b>	0.0
<b>Vertical Section:</b>	<b>Depth From (TVD) (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Direction (°)</b>
	0.0	0.0	0.0	355.21

<b>Survey Tool Program</b>	<b>Date</b>	9/13/2019		
<b>From (usft)</b>	<b>To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Description</b>
0.0	18,423.8	190913 Bell Lake Unit North 229H (Bell La	MWD	MWD - Standard

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
0.0	0.00	0.00	0.0	-3,476.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
100.0	0.00	0.00	100.0	-3,376.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
120.0	0.00	0.00	120.0	-3,356.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>20" Conductor</b>										
200.0	0.00	0.00	200.0	-3,276.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
300.0	0.00	0.00	300.0	-3,176.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
400.0	0.00	0.00	400.0	-3,076.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
500.0	0.00	0.00	500.0	-2,976.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
600.0	0.00	0.00	600.0	-2,876.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
700.0	0.00	0.00	700.0	-2,776.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
800.0	0.00	0.00	800.0	-2,676.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
900.0	0.00	0.00	900.0	-2,576.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,000.0	0.00	0.00	1,000.0	-2,476.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,100.0	0.00	0.00	1,100.0	-2,376.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,152.0	0.00	0.00	1,152.0	-2,324.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>Rustler</b>										
1,177.0	0.00	0.00	1,177.0	-2,299.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>13 3/8" Surface Casing</b>										
1,200.0	0.00	0.00	1,200.0	-2,276.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,300.0	0.00	0.00	1,300.0	-2,176.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,400.0	0.00	0.00	1,400.0	-2,076.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,500.0	0.00	0.00	1,500.0	-1,976.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,522.0	0.00	0.00	1,522.0	-1,954.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>Salado</b>										
1,600.0	0.00	0.00	1,600.0	-1,876.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,700.0	0.00	0.00	1,700.0	-1,776.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
1,722.0	0.00	0.00	1,722.0	-1,754.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>Top of Salt</b>										

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
1,800.0	0.00	0.00	1,800.0	-1,676.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
1,900.0	0.00	0.00	1,900.0	-1,576.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,000.0	0.00	0.00	2,000.0	-1,476.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,100.0	0.00	0.00	2,100.0	-1,376.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,200.0	0.00	0.00	2,200.0	-1,276.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,300.0	0.00	0.00	2,300.0	-1,176.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,400.0	0.00	0.00	2,400.0	-1,076.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,500.0	0.00	0.00	2,500.0	-976.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,600.0	0.00	0.00	2,600.0	-876.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,700.0	0.00	0.00	2,700.0	-776.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,800.0	0.00	0.00	2,800.0	-676.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
2,900.0	0.00	0.00	2,900.0	-576.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,000.0	0.00	0.00	3,000.0	-476.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,100.0	0.00	0.00	3,100.0	-376.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,200.0	0.00	0.00	3,200.0	-276.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,300.0	0.00	0.00	3,300.0	-176.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,400.0	0.00	0.00	3,400.0	-76.2	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,500.0	0.00	0.00	3,500.0	23.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,600.0	0.00	0.00	3,600.0	123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,700.0	0.00	0.00	3,700.0	223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,800.0	0.00	0.00	3,800.0	323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
3,900.0	0.00	0.00	3,900.0	423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,000.0	0.00	0.00	4,000.0	523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,100.0	0.00	0.00	4,100.0	623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,200.0	0.00	0.00	4,200.0	723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,300.0	0.00	0.00	4,300.0	823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,400.0	0.00	0.00	4,400.0	923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
4,500.0	0.00	0.00	4,500.0	1,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,600.0	0.00	0.00	4,600.0	1,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,622.0	0.00	0.00	4,622.0	1,145.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Base of Salt											
4,700.0	0.00	0.00	4,700.0	1,223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,800.0	0.00	0.00	4,800.0	1,323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,872.0	0.00	0.00	4,872.0	1,395.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Lamar											
4,900.0	0.00	0.00	4,900.0	1,423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
4,922.0	0.00	0.00	4,922.0	1,445.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
9 5/8" Intermediate Casing											
5,000.0	0.00	0.00	5,000.0	1,523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,072.0	0.00	0.00	5,072.0	1,595.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Bell Canyon											
5,100.0	0.00	0.00	5,100.0	1,623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,200.0	0.00	0.00	5,200.0	1,723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,300.0	0.00	0.00	5,300.0	1,823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,400.0	0.00	0.00	5,400.0	1,923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,500.0	0.00	0.00	5,500.0	2,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,600.0	0.00	0.00	5,600.0	2,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,700.0	0.00	0.00	5,700.0	2,223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,800.0	0.00	0.00	5,800.0	2,323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,900.0	0.00	0.00	5,900.0	2,423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
5,912.0	0.00	0.00	5,912.0	2,435.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Cherry Canyon											
6,000.0	0.00	0.00	6,000.0	2,523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,100.0	0.00	0.00	6,100.0	2,623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,200.0	0.00	0.00	6,200.0	2,723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
6,300.0	0.00	0.00	6,300.0	2,823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,400.0	0.00	0.00	6,400.0	2,923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,500.0	0.00	0.00	6,500.0	3,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,600.0	0.00	0.00	6,600.0	3,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,700.0	0.00	0.00	6,700.0	3,223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,800.0	0.00	0.00	6,800.0	3,323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
6,900.0	0.00	0.00	6,900.0	3,423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,000.0	0.00	0.00	7,000.0	3,523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,100.0	0.00	0.00	7,100.0	3,623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,200.0	0.00	0.00	7,200.0	3,723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,272.0	0.00	0.00	7,272.0	3,795.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Brushy Canyon											
7,300.0	0.00	0.00	7,300.0	3,823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,400.0	0.00	0.00	7,400.0	3,923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,500.0	0.00	0.00	7,500.0	4,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,600.0	0.00	0.00	7,600.0	4,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,700.0	0.00	0.00	7,700.0	4,223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,800.0	0.00	0.00	7,800.0	4,323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
7,900.0	0.00	0.00	7,900.0	4,423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,000.0	0.00	0.00	8,000.0	4,523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,100.0	0.00	0.00	8,100.0	4,623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,200.0	0.00	0.00	8,200.0	4,723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,300.0	0.00	0.00	8,300.0	4,823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,400.0	0.00	0.00	8,400.0	4,923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,500.0	0.00	0.00	8,500.0	5,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
8,512.0	0.00	0.00	8,512.0	5,035.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00	
Bone Spring											



**Morcor Engineering**  
Morcor Standard Plan

Kaiser-Francis Oil Company

<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

**Planned Survey**

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
8,600.0	0.00	0.00	8,600.0	5,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
8,675.0	0.00	0.00	8,675.0	5,198.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>Avalon</b>										
8,700.0	0.00	0.00	8,700.0	5,223.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
8,800.0	0.00	0.00	8,800.0	5,323.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
8,900.0	0.00	0.00	8,900.0	5,423.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,000.0	0.00	0.00	9,000.0	5,523.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,100.0	0.00	0.00	9,100.0	5,623.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,200.0	0.00	0.00	9,200.0	5,723.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,300.0	0.00	0.00	9,300.0	5,823.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,400.0	0.00	0.00	9,400.0	5,923.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,500.0	0.00	0.00	9,500.0	6,023.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,515.0	0.00	0.00	9,515.0	6,038.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>1st Bone Spring Sand</b>										
9,600.0	0.00	0.00	9,600.0	6,123.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
9,615.0	0.00	0.00	9,615.0	6,138.8	0.0	0.0	797,735.37	485,443.55	0.00	0.00
<b>Start Build 10.00</b>										
9,700.0	8.50	307.59	9,699.7	6,223.5	3.8	-5.0	797,730.38	485,447.39	4.24	10.00
9,800.0	18.50	307.59	9,796.8	6,320.6	18.1	-23.5	797,711.91	485,461.61	19.95	10.00
9,900.0	28.50	307.59	9,888.4	6,412.2	42.3	-55.0	797,680.36	485,485.90	46.79	10.00
10,000.0	38.49	307.59	9,971.7	6,495.5	76.0	-98.7	797,636.69	485,519.52	83.94	10.00
10,100.0	48.49	307.59	10,044.1	6,567.9	117.9	-153.2	797,582.22	485,561.46	130.27	10.00
10,105.9	49.08	307.59	10,048.0	6,571.8	120.6	-156.6	797,578.72	485,564.15	133.25	10.00
<b>2nd Bone Spring Sand</b>										
10,200.0	58.49	307.59	10,103.6	6,627.4	166.9	-216.8	797,518.61	485,610.43	184.38	10.00
10,300.0	68.49	307.59	10,148.1	6,671.9	221.4	-287.6	797,447.79	485,664.95	244.62	10.00
10,339.8	72.47	307.59	10,161.4	6,685.2	244.3	-317.3	797,418.05	485,687.84	269.91	10.00
<b>Start DLS 10.02 TFO 76.42</b>										

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
10,400.0	73.98	313.69	10,178.8	6,702.6	281.8	-361.0	797,374.37	485,725.35	310.94	10.02	
10,500.0	76.85	323.61	10,204.1	6,727.9	354.4	-424.8	797,310.57	485,797.93	388.58	10.02	
10,600.0	80.09	333.29	10,224.1	6,747.9	437.8	-476.0	797,259.42	485,881.33	475.96	10.02	
10,700.0	83.60	342.77	10,238.3	6,762.1	529.5	-512.9	797,222.46	485,973.02	570.42	10.02	
10,800.0	87.28	352.12	10,246.3	6,770.1	626.6	-534.5	797,200.84	486,070.20	669.06	10.02	
10,872.5	90.00	358.86	10,248.0	6,771.8	698.9	-540.2	797,195.15	486,142.41	741.50	10.02	
Start 7551.3 hold at 10872.5 MD											
10,900.0	90.00	358.86	10,248.0	6,771.8	726.3	-540.8	797,194.60	486,169.90	768.94	0.00	
11,000.0	90.00	358.86	10,248.0	6,771.8	826.3	-542.8	797,192.61	486,269.88	868.73	0.00	
11,100.0	90.00	358.86	10,248.0	6,771.8	926.3	-544.8	797,190.62	486,369.86	968.53	0.00	
11,200.0	90.00	358.86	10,248.0	6,771.8	1,026.3	-546.7	797,188.63	486,469.84	1,068.33	0.00	
11,300.0	90.00	358.86	10,248.0	6,771.8	1,126.3	-548.7	797,186.64	486,569.82	1,168.13	0.00	
11,400.0	90.00	358.86	10,248.0	6,771.8	1,226.3	-550.7	797,184.64	486,669.80	1,267.92	0.00	
11,500.0	90.00	358.86	10,248.0	6,771.8	1,326.2	-552.7	797,182.65	486,769.78	1,367.72	0.00	
11,600.0	90.00	358.86	10,248.0	6,771.8	1,426.2	-554.7	797,180.66	486,869.76	1,467.52	0.00	
11,700.0	90.00	358.86	10,248.0	6,771.8	1,526.2	-556.7	797,178.67	486,969.74	1,567.32	0.00	
11,800.0	90.00	358.86	10,248.0	6,771.8	1,626.2	-558.7	797,176.68	487,069.72	1,667.12	0.00	
11,900.0	90.00	358.86	10,248.0	6,771.8	1,726.2	-560.7	797,174.68	487,169.70	1,766.91	0.00	
12,000.0	90.00	358.86	10,248.0	6,771.8	1,826.1	-562.7	797,172.69	487,269.68	1,866.71	0.00	
12,100.0	90.00	358.86	10,248.0	6,771.8	1,926.1	-564.7	797,170.70	487,369.66	1,966.51	0.00	
12,200.0	90.00	358.86	10,248.0	6,771.8	2,026.1	-566.7	797,168.71	487,469.64	2,066.31	0.00	
12,300.0	90.00	358.86	10,248.0	6,771.8	2,126.1	-568.7	797,166.72	487,569.62	2,166.10	0.00	
12,400.0	90.00	358.86	10,248.0	6,771.8	2,226.1	-570.6	797,164.72	487,669.60	2,265.90	0.00	
12,500.0	90.00	358.86	10,248.0	6,771.8	2,326.0	-572.6	797,162.73	487,769.58	2,365.70	0.00	
12,600.0	90.00	358.86	10,248.0	6,771.8	2,426.0	-574.6	797,160.74	487,869.56	2,465.50	0.00	
12,700.0	90.00	358.86	10,248.0	6,771.8	2,526.0	-576.6	797,158.75	487,969.54	2,565.30	0.00	
12,800.0	90.00	358.86	10,248.0	6,771.8	2,626.0	-578.6	797,156.76	488,069.52	2,665.09	0.00	

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
12,900.0	90.00	358.86	10,248.0	6,771.8	2,726.0	-580.6	797,154.77	488,169.50	2,764.89	0.00
13,000.0	90.00	358.86	10,248.0	6,771.8	2,825.9	-582.6	797,152.77	488,269.48	2,864.69	0.00
13,100.0	90.00	358.86	10,248.0	6,771.8	2,925.9	-584.6	797,150.78	488,369.46	2,964.49	0.00
13,200.0	90.00	358.86	10,248.0	6,771.8	3,025.9	-586.6	797,148.79	488,469.44	3,064.28	0.00
13,300.0	90.00	358.86	10,248.0	6,771.8	3,125.9	-588.6	797,146.80	488,569.42	3,164.08	0.00
13,400.0	90.00	358.86	10,248.0	6,771.8	3,225.9	-590.6	797,144.81	488,669.40	3,263.88	0.00
13,500.0	90.00	358.86	10,248.0	6,771.8	3,325.8	-592.6	797,142.81	488,769.38	3,363.68	0.00
13,600.0	90.00	358.86	10,248.0	6,771.8	3,425.8	-594.5	797,140.82	488,869.36	3,463.47	0.00
13,700.0	90.00	358.86	10,248.0	6,771.8	3,525.8	-596.5	797,138.83	488,969.34	3,563.27	0.00
13,800.0	90.00	358.86	10,248.0	6,771.8	3,625.8	-598.5	797,136.84	489,069.32	3,663.07	0.00
13,900.0	90.00	358.86	10,248.0	6,771.8	3,725.8	-600.5	797,134.85	489,169.30	3,762.87	0.00
14,000.0	90.00	358.86	10,248.0	6,771.8	3,825.7	-602.5	797,132.86	489,269.28	3,862.67	0.00
14,100.0	90.00	358.86	10,248.0	6,771.8	3,925.7	-604.5	797,130.86	489,369.26	3,962.46	0.00
14,200.0	90.00	358.86	10,248.0	6,771.8	4,025.7	-606.5	797,128.87	489,469.25	4,062.26	0.00
14,300.0	90.00	358.86	10,248.0	6,771.8	4,125.7	-608.5	797,126.88	489,569.23	4,162.06	0.00
14,400.0	90.00	358.86	10,248.0	6,771.8	4,225.7	-610.5	797,124.89	489,669.21	4,261.86	0.00
14,500.0	90.00	358.86	10,248.0	6,771.8	4,325.6	-612.5	797,122.90	489,769.19	4,361.65	0.00
14,600.0	90.00	358.86	10,248.0	6,771.8	4,425.6	-614.5	797,120.90	489,869.17	4,461.45	0.00
14,700.0	90.00	358.86	10,248.0	6,771.8	4,525.6	-616.5	797,118.91	489,969.15	4,561.25	0.00
14,800.0	90.00	358.86	10,248.0	6,771.8	4,625.6	-618.4	797,116.92	490,069.13	4,661.05	0.00
14,900.0	90.00	358.86	10,248.0	6,771.8	4,725.6	-620.4	797,114.93	490,169.11	4,760.85	0.00
15,000.0	90.00	358.86	10,248.0	6,771.8	4,825.5	-622.4	797,112.94	490,269.09	4,860.64	0.00
15,100.0	90.00	358.86	10,248.0	6,771.8	4,925.5	-624.4	797,110.95	490,369.07	4,960.44	0.00
15,200.0	90.00	358.86	10,248.0	6,771.8	5,025.5	-626.4	797,108.95	490,469.05	5,060.24	0.00
15,300.0	90.00	358.86	10,248.0	6,771.8	5,125.5	-628.4	797,106.96	490,569.03	5,160.04	0.00
15,400.0	90.00	358.86	10,248.0	6,771.8	5,225.5	-630.4	797,104.97	490,669.01	5,259.83	0.00
15,500.0	90.00	358.86	10,248.0	6,771.8	5,325.4	-632.4	797,102.98	490,768.99	5,359.63	0.00

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey											
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)	
15,600.0	90.00	358.86	10,248.0	6,771.8	5,425.4	-634.4	797,100.99	490,868.97	5,459.43	0.00	
15,700.0	90.00	358.86	10,248.0	6,771.8	5,525.4	-636.4	797,098.99	490,968.95	5,559.23	0.00	
15,800.0	90.00	358.86	10,248.0	6,771.8	5,625.4	-638.4	797,097.00	491,068.93	5,659.03	0.00	
15,900.0	90.00	358.86	10,248.0	6,771.8	5,725.4	-640.4	797,095.01	491,168.91	5,758.82	0.00	
16,000.0	90.00	358.86	10,248.0	6,771.8	5,825.3	-642.4	797,093.02	491,268.89	5,858.62	0.00	
16,100.0	90.00	358.86	10,248.0	6,771.8	5,925.3	-644.3	797,091.03	491,368.87	5,958.42	0.00	
16,200.0	90.00	358.86	10,248.0	6,771.8	6,025.3	-646.3	797,089.04	491,468.85	6,058.22	0.00	
16,300.0	90.00	358.86	10,248.0	6,771.8	6,125.3	-648.3	797,087.04	491,568.83	6,158.01	0.00	
16,400.0	90.00	358.86	10,248.0	6,771.8	6,225.3	-650.3	797,085.05	491,668.81	6,257.81	0.00	
16,500.0	90.00	358.86	10,248.0	6,771.8	6,325.2	-652.3	797,083.06	491,768.79	6,357.61	0.00	
16,600.0	90.00	358.86	10,248.0	6,771.8	6,425.2	-654.3	797,081.07	491,868.77	6,457.41	0.00	
16,700.0	90.00	358.86	10,248.0	6,771.8	6,525.2	-656.3	797,079.08	491,968.75	6,557.20	0.00	
16,800.0	90.00	358.86	10,248.0	6,771.8	6,625.2	-658.3	797,077.08	492,068.73	6,657.00	0.00	
16,900.0	90.00	358.86	10,248.0	6,771.8	6,725.2	-660.3	797,075.09	492,168.71	6,756.80	0.00	
17,000.0	90.00	358.86	10,248.0	6,771.8	6,825.1	-662.3	797,073.10	492,268.69	6,856.60	0.00	
17,100.0	90.00	358.86	10,248.0	6,771.8	6,925.1	-664.3	797,071.11	492,368.67	6,956.40	0.00	
17,200.0	90.00	358.86	10,248.0	6,771.8	7,025.1	-666.3	797,069.12	492,468.65	7,056.19	0.00	
17,300.0	90.00	358.86	10,248.0	6,771.8	7,125.1	-668.2	797,067.12	492,568.63	7,155.99	0.00	
17,400.0	90.00	358.86	10,248.0	6,771.8	7,225.1	-670.2	797,065.13	492,668.61	7,255.79	0.00	
17,500.0	90.00	358.86	10,248.0	6,771.8	7,325.0	-672.2	797,063.14	492,768.59	7,355.59	0.00	
17,600.0	90.00	358.86	10,248.0	6,771.8	7,425.0	-674.2	797,061.15	492,868.57	7,455.38	0.00	
17,700.0	90.00	358.86	10,248.0	6,771.8	7,525.0	-676.2	797,059.16	492,968.55	7,555.18	0.00	
17,800.0	90.00	358.86	10,248.0	6,771.8	7,625.0	-678.2	797,057.17	493,068.53	7,654.98	0.00	
17,900.0	90.00	358.86	10,248.0	6,771.8	7,725.0	-680.2	797,055.17	493,168.51	7,754.78	0.00	
18,000.0	90.00	358.86	10,248.0	6,771.8	7,824.9	-682.2	797,053.18	493,268.49	7,854.58	0.00	
18,100.0	90.00	358.86	10,248.0	6,771.8	7,924.9	-684.2	797,051.19	493,368.47	7,954.37	0.00	
18,200.0	90.00	358.86	10,248.0	6,771.8	8,024.9	-686.2	797,049.20	493,468.45	8,054.17	0.00	

**Morcor Engineering**  
Morcor Standard Plan



<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	TVDSS (usft)	N/S (usft)	E/W (usft)	Easting (usft)	Northing (usft)	V. Sec (usft)	DLeg (°/100usft)
18,300.0	90.00	358.86	10,248.0	6,771.8	8,124.9	-688.2	797,047.21	493,568.43	8,153.97	0.00
18,400.0	90.00	358.86	10,248.0	6,771.8	8,224.9	-690.2	797,045.21	493,668.41	8,253.77	0.00
18,423.8	90.00	358.86	10,248.0	6,771.8	8,248.7	-690.6	797,044.74	493,692.21	8,277.52	0.00
TD at 18423.8 - 5 1/2" Production Casing										

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")	
120.0	120.0	20" Conductor	20	26	
1,177.0	1,177.0	13 3/8" Surface Casing	13-3/8	17-1/2	
4,922.0	4,922.0	9 5/8" Intermediate Casing	9-5/8	12-1/4	
18,423.8	10,248.0	5 1/2" Production Casing	5-1/2	8-3/4	

Formations					
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
8,675.0	8,675.0	Avalon		0.00	
1,152.0	1,152.0	Rustler		0.00	
9,515.0	9,515.0	1st Bone Spring Sand		0.00	
4,872.0	4,872.0	Lamar		0.00	
8,512.0	8,512.0	Bone Spring		0.00	
1,722.0	1,722.0	Top of Salt		0.00	
10,105.9	10,048.0	2nd Bone Spring Sand		0.00	
7,272.0	7,272.0	Brushy Canyon		0.00	
5,912.0	5,912.0	Cherry Canyon		0.00	
5,072.0	5,072.0	Bell Canyon		0.00	
4,622.0	4,622.0	Base of Salt		0.00	
1,522.0	1,522.0	Salado		0.00	



**Morcor Engineering**  
Morcor Standard Plan

<b>Company:</b>	Kaiser Francis	<b>Local Co-ordinate Reference:</b>	Well Bell Lake Unit North 229H
<b>Project:</b>	Bell Lake Unit North 229H	<b>TVD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Site:</b>	Bell Lake Unit North 229H	<b>MD Reference:</b>	WELL @ 3476.2usft (Original Well Elev)
<b>Well:</b>	Bell Lake Unit North 229H	<b>North Reference:</b>	Grid
<b>Wellbore:</b>	Bell Lake Unit North 229H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Design:</b>	190913 Bell Lake Unit North 229H	<b>Database:</b>	EDM 5000.1 Single User Db

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
9,615.0	9,615.0	0.0	0.0	Start Build 10.00
10,339.8	10,161.4	244.3	-317.3	Start DLS 10.02 TFO 76.42
10,872.5	10,248.0	698.9	-540.2	Start 7551.3 hold at 10872.5 MD
18,423.8	10,248.0	8,248.7	-690.6	TD at 18423.8

Checked By:	_____	Approved By:	_____	Date:	_____
-------------	-------	--------------	-------	-------	-------

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 S. First St., Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Submit Original  
to Appropriate  
District Office

## GAS CAPTURE PLAN

Date: **01/26/2018**

☒ Original

Operator & OGRID No.: Kaiser-Francis Oil Company, 12361

☐ Amended - Reason for Amendment: \_\_\_\_\_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

*Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).*

### Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Bell Lake Unit North 229H		6-23S-34E		2000	0	
Bell Lake Unit North 230H		6-23S-34E		2000	0	
Bell Lake Unit North 329H		6-23S-34E		2000	0	
Bell Lake Unit North 330H		6-23S-34E		2000	0	
Bell Lake Unit North 429H		6-23S-34E		2000	0	
Bell Lake Unit North 430H		6-23S-34E		2000	0	

### Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Targa and will be connected to Targa low/high pressure gathering system located in Lea County, New Mexico. It will require 11,000' of pipeline to connect the facility to low/high pressure gathering system. Kaiser-Francis Oil Company provides (periodically) to Targa a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Kaiser-Francis Oil Company and Targa have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Targa Processing Plant located in Sec. 36, Twn. 19S, Rng. 36E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Targa system at that time. Based on current information, it is Kaiser-Francis Oil Company's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines