

**OCD – HOBBS**  
**11/24/2020**  
**RECEIVED**

FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM126974
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator TITUS OIL AND GAS PRODUCTION LLC <b>[373986]</b>		8. Lease Name and Well No. EL CAMPEON FED COM <b>[328509]</b> 204H
3a. Address 420 Throckmorton St., Suite 1150, Fort Worth, TX 76102	3b. Phone No. (include area code) (817) 852-6358	9. API Well No. <b>30-025-48111</b>
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface TR P / 332 FSL / 620 FEL / LAT 32.0224207 / LONG -103.3829102 At proposed prod. zone LOT 1 / 10 FSL / 330 FEL / LAT 32.0003223 / LONG -103.3819546		10. Field and Pool, or Exploratory <b>[96672]</b> WC-025 G-08 S263412K/BONE SPRING
14. Distance in miles and direction from nearest town or post office* 13 miles		11. Sec., T. R. M. or Blk. and Survey or Area SEC 20/T26S/R35E/NMP
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 332 feet		12. County or Parish LEA
16. No of acres in lease 320		13. State NM
17. Spacing Unit dedicated to this well 240.0		
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 30 feet		20. BLM/BIA Bond No. in file FED: NMB001532
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3172 feet		22. Approximate date work will start* 06/01/2020
		23. Estimated duration 45 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- |  |   |
|--|---|
| 1. Well plat certified by a registered surveyor.   | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan.  | 5. Operator certification.  |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM.            |

25. Signature (Electronic Submission)	Name (Printed/Typed) RYAN DELONG / Ph: (817) 852-6358	Date 01/29/2020
Title Regulatory Manager		
Approved by (Signature) (Electronic Submission)	Name (Printed/Typed) Cody Layton / Ph: (575) 234-5959	Date 09/29/2020
Title Assistant Field Manager Lands & Minerals Carlsbad Field Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.  
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GCP Rec 11/24/2020

SL

(Continued on page 2)



KZ  
12/07/2020

\*(Instructions on page 2)

## Additional Operator Remarks

### Location of Well

0. SHL: TR P / 332 FSL / 620 FEL / TWSP: 26S / RANGE: 35E / SECTION: 20 / LAT: 32.0224207 / LONG: -103.3829102 ( TVD: 0 feet, MD: 0 feet )

PPP: TR A / 0 FNL / 329 FEL / TWSP: 26S / RANGE: 35E / SECTION: 32 / LAT: 32.006977 / LONG: -103.381959 ( TVD: 10970 feet, MD: 16871 feet )

PPP: TR A / 0 FNL / 176 FEL / TWSP: 26S / RANGE: 35E / SECTION: 29 / LAT: 32.021505 / LONG: -103.381477 ( TVD: 10949 feet, MD: 11479 feet )

BHL: LOT 1 / 10 FSL / 330 FEL / TWSP: 26S / RANGE: 35E / SECTION: 32 / LAT: 32.0003223 / LONG: -103.3819546 ( TVD: 10980 feet, MD: 19202 feet )

### BLM Point of Contact

Name: TYLER HILL

Title: LIE

Phone: (575) 234-5972

Email: tjhill@blm.gov

CONFIDENTIAL



**Titus Oil & Gas, LLC**  
**County: LEA**  
**EL CAMP PROJECT**  
**El Campeon Fed Com 204H**  
**El Campeon Fed Com 204H**

**Standard Planning Report**  
27 January 2020

<b>Operator</b>	Titus Oil & Gas, LLC	<b>Local co-ord ref</b>	Well Centered
<b>Field</b>	County: LEA	<b>TVD Reference</b>	Default
<b>Facility</b>	EL CAMP PROJECT	<b>North Reference</b>	GRID
<b>Well</b>	EI Campeon Fed Com 204H	<b>Survey Calc Method</b>	Minimum Curvature
<b>Wellbore</b>	EI Campeon Fed Com 204H		

<b>Field</b>	County: LEA
--------------	-------------

<b>CRS</b>	NAD83 / New Mexico East (ftUS)	<b>Scale Factor</b>	0.99991
<b>Apply Scale Factor</b>	NO	<b>Depth Datum-&gt;MSL</b>	0.00 Ft
<b>System Datum</b>	Ground Level		

<b>Facility</b>	EL CAMP PROJECT
-----------------	-----------------

<b>Map Northing</b>	388675.48 US survey foot	<b>Map Easting</b>	831074.42 US survey foot
<b>Latitude</b>	32° 3' 54.350" N	<b>Longitude</b>	103° 23' 52.868" W
<b>Vertical Uncertainty</b>	0.00 Ft	<b>Horizontal Uncertainty</b>	0.00 Ft
<b>Grid Convergence</b>	0.497		

<b>Well</b>	EI Campeon Fed Com 204H
-------------	-------------------------

<b>Local North</b>	-15484.52 Ft	<b>Local East</b>	4817.15 Ft
<b>Map Northing</b>	373190.99 US survey foot	<b>Map Easting</b>	835891.56 US survey foot
<b>Latitude</b>	32° 1' 20.715" N	<b>Longitude</b>	103° 22' 58.477" W
<b>Depth Datum</b>	Default	<b>Datum Elevation</b>	0.00 Ft
<b>GL Elevation</b>	0.00 Ft		
<b>Grid Convergence</b>	0.504		

## Survey Report

MD	Inc	Azi	TVD	NS	EW	VS	DLS	BR	TR	TF	CL	TVD SS	Map Northing	Map Easting	Latitude	Longitude
Ft	°	°	Ft	Ft	Ft	Ft	(*/100 Ft)	(*/100 Ft)	(*/100 Ft)	°	Ft	Ft	US survey foot	US survey foot		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	-3254.00	373190.99	835891.56	32° 1' 20.715" N	103° 22' 58.477" W
1500.00	0.00	0.00	1500.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1500.00	-1754.00	373190.99	835891.56	32° 1' 20.715" N	103° 22' 58.477" W
1600.00	0.00	47.69	1600.00	0.00	0.00	0.00	0.00	0.00	47.69	47.69	100.00	-1654.00	373190.99	835891.56	32° 1' 20.715" N	103° 22' 58.477" W
1881.50	5.63	47.69	1881.05	9.30	10.22	-8.83	2.00	2.00	0.00	47.69	281.50	-1372.95	373200.29	835901.78	32° 1' 20.806" N	103° 22' 58.357" W
8000.54	5.63	47.69	7970.57	413.39	454.15	-392.20	0.00	0.00	0.00	0.00	6119.04	4716.57	373604.38	836345.71	32° 1' 24.766" N	103° 22' 53.160" W
8375.87	0.00	47.69	8345.30	425.79	467.78	-403.97	1.50	-1.50	0.00	180.00	375.33	5091.30	373616.78	836359.34	32° 1' 24.887" N	103° 22' 53.000" W
10375.87	0.00	179.45	10345.30	425.79	467.78	-403.97	0.00	0.00	6.59	179.45	2000.00	7091.30	373616.78	836359.34	32° 1' 24.887" N	103° 22' 53.000" W
11320.82	89.77	179.45	10948.41	-174.87	473.54	196.34	9.50	9.50	0.00	179.45	944.95	7694.41	373016.12	836365.11	32° 1' 18.943" N	103° 22' 52.995" W
11833.32	89.77	199.95	10950.49	-677.35	387.65	694.36	4.00	0.00	4.00	90.04	512.50	7696.49	372513.64	836279.21	32° 1' 13.979" N	103° 22' 54.044" W
12345.82	89.77	179.45	10952.57	-1179.83	301.76	1192.39	4.00	0.00	-4.00	-90.04	512.50	7698.57	372011.16	836193.32	32° 1' 9.014" N	103° 22' 55.093" W
19202.62	89.77	179.45	10980.09	-8036.26	367.58	8044.66	0.00	0.00	0.00	0.00	6856.80	7726.09	365154.75	836259.14	32° 0' 1.164" N	103° 22' 55.029" W

# **TITUS**

**Oil & Gas** LLC

## **TITUS Oil & Gas Production, LLC**

**100 Throckmorton Street**

**Suite 1630**

**Fort Worth, TX 76102**

## **Hydrogen Sulfide (H<sub>2</sub>S) Contingency Plan**

**For**

### **El Campeon Fed Com 204H**

**Sec-20 T-26S R-35E**

**332 FSL & 620' FEL**



**LAT. = 32.02242074' N (NAD83)**

**LONG = 103.38291023' W**

**Lea County NM**

## El Campeon Fed Com 204H

This is an open drilling site. H<sub>2</sub>S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H<sub>2</sub>S, including warning signs, wind indicators and H<sub>2</sub>S monitor.



Assumed 100 ppm **ROE = 3000'** (**Radius of Exposure**)  
100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

**Assumed 100 ppm ROE = 3000'**

## 100 ppm H<sub>2</sub>S concentration shall trigger activation of this plan.

### Emergency Procedures

In the event of a release of gas containing H<sub>2</sub>S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H<sub>2</sub>S monitors and air packs in order to control the release.
- Use the “buddy system” to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- Have received training in the
  - Detection of H<sub>2</sub>S, and
  - Measures for protection against the gas,
  - Equipment used for protection and emergency response.

### **Ignition of Gas Source**

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO<sub>2</sub>). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

### **Characteristics of H<sub>2</sub>S and SO<sub>2</sub>**

<b>Common Name</b>	<b>Chemical Formula</b>	<b>Specific Gravity</b>	<b>Threshold Limit</b>	<b>Hazardous Limit</b>	<b>Lethal Concentration</b>
<b>Hydrogen Sulfide</b>	H <sub>2</sub> S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
<b>Sulfur Dioxide</b>	SO <sub>2</sub>	2.21 Air = 1	2 ppm	N/A	1000 ppm

### **Contacting Authorities**

Titus Oil & Gas personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Titus Oil & Gas Company response must be in coordination with the State of New Mexico’s ‘Hazardous Materials Emergency Response Plan’ (HMER)

# Hydrogen Sulfide Drilling Operation Plan

## I. HYDROGEN SULFIDE (H<sub>2</sub>S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H<sub>2</sub>S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500 feet) and weekly H<sub>2</sub>S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan.

## II. HYDROGEN SULFIDE TRAINING

Note: All H<sub>2</sub>S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S.

## 1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

## 2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

## 3. H<sub>2</sub>S detection and monitoring equipment:

Portable H<sub>2</sub>S monitors positioned on location for best coverage and response. These units have warning lights which activate when H<sub>2</sub>S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- **Bell nipple**
- **Poosum Belly/Shale shaker**
- **Rig floor**
- **Choke manifold**
- **Cellar**

### **Visual warning systems:**

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

#### **4. Mud program:**

The mud program has been designed to minimize the volume of H<sub>2</sub>S circulated to surface. Proper mud weight, safe drilling practices and the use of H<sub>2</sub>S scavengers will minimize hazards when penetrating H<sub>2</sub>S bearing zones.

#### **5. Metallurgy:**

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H<sub>2</sub>S trim.
- B. All elastomers used for packing and seals shall be H<sub>2</sub>S trim.

#### **6. Communication:**


- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

#### **7. Well testing:**

- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H<sub>2</sub>S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.



Well Name El Campeon Fed Com 204H  
 Latitude 32° 1' 20.715" N  
 Longitude 103° 22' 58.477" W  
 CRS NAD83 / New Mexico East (ftUS)






North Reference  
 Magnetic Declination  
 Grid Convergence  
 Dip angle  
 Magnetic Model  
 Total Field (nT)  
 Date  
 TRUE to GRID:  
 MAG to GRID:

GRID  
 6.566  
 0.50  
 59.872  
 IGRF12.COF  
 47573.444  
 27/1/2020  
 Add -0.50  
 Add 6.07

Well Name El Campeon Fed Com 204H  
 RTE Elevation 0.00 Ft above Ground Level  
 GL Elevation 0.00 Ft above Ground Level  
 Calculation Method Minimum Curvature  
 Local Co-Ordinate Ref Well Centered  
 Grid East 835891.56 US survey foot  
 Grid North 373190.99 US survey foot  
 Local North -15484.52 Ft  
 Local East 4817.15 Ft  
 Latitude 32° 1' 20.715" N  
 Longitude 103° 22' 58.477" W  
 CRS NAD83 / New Mexico East (ftUS)  
 VS Origin Well  
 North Ref GRID  
 Depth Datum Default  
 Grid Convergence 0.504

Plan Sections	MD(ft)	INC(°)	AZI(°)	TVD(ft)	NS(ft)	EW(ft)	VS(ft)	DLS(°/100ft)	Tool face	Method
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	HOLD_CL
	1500.00	0.00	0.00	1500.00	0.00	0.00	0.00	0.00	0.00	ADJ_CL
	1600.00	0.00	47.69	1600.00	0.00	0.00	0.00	0.00	47.69	BT_INC
	1881.50	5.63	47.69	1881.05	9.30	10.22	-8.83	2.00	47.69	BT_INC
	8000.54	5.63	47.69	7970.57	413.39	454.15	-392.20	0.00	0.00	HOLD_CL
	8375.87	0.00	47.69	8345.30	425.79	467.78	-403.97	1.50	180.00	BT_INC
	10375.87	0.00	179.45	10345.30	425.79	467.78	-403.97	0.00	179.45	ADJ_CL
	11320.82	89.77	179.45	10948.41	-174.87	473.54	196.33	9.50	179.45	BT_INC
	11833.32	89.77	199.95	10950.49	-677.35	387.65	694.36	4.00	90.04	BT_INC
	12345.82	89.77	179.45	10952.57	-1179.83	301.76	1192.39	4.00	-90.04	BT_AZI
	19202.62	89.77	179.45	10980.09	-8036.26	367.58	8044.66	0.00	0.00	HOLD_CL



# Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H

## 1. Geologic Formations

TVD of target	10,980' EOL	Pilot hole depth	NA
MD at TD:	19,202'	Deepest expected fresh water:	250'

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	1080	Water	
Top of Salt	1542	Salt	
Base of Salt	5034	Salt	
Lamar	5339	Salt Water	
Bell Canyon	5374	Oil/Gas	
Cherry Canyon	6429	Oil/Gas	
Brushy Canyon	7801	Oil/Gas	
Bone Spring Lime	9225	Oil/Gas	
Leonard	9274	Oil/Gas	
1st Bone Spring Sand	10418	Oil/Gas	
2nd Bone Spring Sand	10997	Target Oil/Gas	
3rd Bone Spring Sand	12117	Not Penetrated	
Wolfcamp	12466	Not Penetrated	
X	X	Not Penetrated	

## 2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	1105	13.375"	54.5	J55	STC	2.23	1.19	8.54
12.25"	0	5365	9.625"	40	J55	LTC	1.13	0.93	2.42
8.75"	0	19,202	5.5"	17	P110	LTC	1.39	2.49	2.38
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

Intermediate casing will be kept at least 1/3 full while running casing to mitigate collapse. Intermediate burst based on 0.7 frac gradient at the shoe with Gas Gradient 0.1 psi/ft to surface.

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

**Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H**

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
<b>Is well located within Capitan Reef?</b>	
If yes, does production casing cement tie back a minimum of 50' above the Reef?	N
Is well within the designated 4 string boundary?	
<b>Is well located in SOPA but not in R-111-P?</b>	
If yes, are the first 2 strings cemented to surface and 3 <sup>rd</sup> string cement tied back 500' into previous casing?	N
<b>Is well located in R-111-P and SOPA?</b>	
If yes, are the first three strings cemented to surface?	N
Is 2 <sup>nd</sup> string set 100' to 600' below the base of salt?	
<b>Is well located in high Cave/Karst?</b>	
If yes, are there two strings cemented to surface?	N
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
<b>Is well located in critical Cave/Karst?</b>	
If yes, are there three strings cemented to surface?	N

**Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H**

**3. Cementing Program**

Casing	# Sks	Wt. lb/ gal	Yld ft3/ sack	H <sub>2</sub> O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	470	13.5	1.75	9	12	Lead: Class C + 4% Gel + 1% CaCl <sub>2</sub>
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl <sub>2</sub>
Inter.	1040	12.7	2.0	9.6	16	Lead: 35:65:6 C Blend
	250	14.8	1.34	6.34	8	Tail: Class C + 2% CaCl
5.5 Prod	780	11.9	2.5	19	72	Lead: 50:50:10 H Blend
	2220	14.4	1.24	5.7	19	Tail: 50:50:2 Class H Blend

Volumes Subject to Observed Hole Conditions and/or Fluid Caliper Results

Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Casing String	TOC	% Excess
Surface	0'	50%
1 <sup>st</sup> Intermediate	0'	50%
Production	4,865'	25% OH in Lateral (KOP to EOL) – 40% OH in Vertical

**Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H**

**4. Pressure Control Equipment**

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	x	Tested to:
12-1/4"	13-5/8"	2M	Annular	x	2000 psi
			Blind Ram		2M
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	13-5/8"	3M	Annular	x	50% testing pressure
			Blind Ram	x	3M
			Pipe Ram	x	
			Double Ram		
			Other*		

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
N	Are anchors required by manufacturer?
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

**Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H**

**5. Mud Program**

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. Shoe	FW Gel	8.6 - 8.8	28-34	N/C
Surf csg	9-5/8" Int shoe	Saturated Brine	10 - 10.2	28-34	N/C
9-5/8" Int shoe	Lateral TD	Cut Brine	8.6 - 9.4	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

**6. Logging and Testing Procedures**

Logging, Coring and Testing.	
Y	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
Y	No Logs are planned based on well control or offset log information.
N	Drill stem test? If yes, explain.
N	Coring? If yes, explain.

Additional logs planned		Interval
N	Resistivity	Pilot Hole TD to ICP
N	Density	Pilot Hole TD to ICP
Y	CBL	Production casing (If cement not circulated to surface)
Y	Mud log	Intermediate shoe to TD
N	PEX	

**Titus Oil & Gas Production, LLC - El Campeon Fed Com 204H**

**7. Drilling Conditions**

<b>Condition</b>	<b>Specify what type and where?</b>
BH Pressure at deepest TVD	5370 psi at 10980' TVD
Abnormal Temperature	NO 165 Deg. F.

No abnormal pressure or temperature conditions are anticipated. Sufficient mud materials to maintain mud properties and weight increase requirements will be kept on location at all times.

Sufficient supplies of Paper/LCM for periodic sweeps to control seepage and losses will be maintained on location.

Hydrogen Sulfide (H <sub>2</sub> S) monitors will be installed prior to drilling out the surface shoe. If H <sub>2</sub> S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.	
N	H <sub>2</sub> S is present
Y	H <sub>2</sub> S Plan attached

**8. Other Facets of Operation**

Y	Is it a walking operation?
N	Is casing pre-set?


x	H <sub>2</sub> S Plan.
x	BOP & Choke Schematics.
x	Directional Plan

<b><u>Titus Oil &amp; Gas Company Call List</u></b>		
Drilling Supervisor –		
Ryan DeLong - <b>Office</b> (817) 852-6370 <b>Mobile</b> (405) 664-5188		
<b><u>Agency Call List</u></b>		
<b><u>Lea County (575)</u></b>	<b>Hobbs</b>	
	Lea County Communication Authority	393-3981
	State Police	392-5588
	City Police	397-9265
	Sheriff's Office	393-2515
	<b>Ambulance</b>	<b>911</b>
	Fire Department	397-9308
	LEPC (Local Emergency Planning Committee)	393-2870
	NMOCD	393-6161
	US Bureau of Land Management	393-3612
	<b><u>Eddy County (575)</u></b>	<b>Carlsbad</b>
State Police		885-3137
City Police		885-2111
Sheriff's Office		887-7551
<b>Ambulance</b>		<b>911</b>
Fire Department		885-3125
LEPC (Local Emergency Planning Committee)		887-3798
US Bureau of Land Management		887-6544
NM Emergency Response Commission (Santa Fe)		(505) 476-9600
24 HR		(505) 827-9126
National Emergency Response Center		(800) 424-8802
National Pollution Control Center: Direct		(703) 872-6000
For Oil Spills		(800) 280-7118
<b>Emergency Services</b>		
Wild Well Control		(281) 784-4700
Cudd Pressure Control		915-699-0139 (915) 563-3356
Halliburton		(575) 746-2757
B. J. Services	(575) 746-3569	
<b><u>Give GPS position:</u></b>	Native Air – Emergency Helicopter – Hobbs	(575) 392-6429
	Flight For Life - Lubbock, TX	(806) 743-9911
	Aerocare - Lubbock, TX	(806) 747-8923
	Med Flight Air Amb - Albuquerque, NM	(575) 842-4433
	Lifeguard Air Med Svc. Albuquerque, NM	(800) 222-1222
	Poison Control (24/7)	(575) 272-3115
	Oil & Gas Pipeline 24 Hour Service	(800) 364-4366
	NOAA – Website - <a href="http://www.nhc.noaa.gov">www.nhc.noaa.gov</a>	

# TITUS Oil & Gas Production - Well Pad

## Rig Location Layout

### Safety Equipment Location



## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	<b>Titus Oil and Gas Production LLC</b>
<b>LEASE NO.:</b>	<b>NMNM126974</b>
<b>WELL NAME &amp; NO.:</b>	<b>El Campeon Federal Com 204H</b>
<b>SURFACE HOLE FOOTAGE:</b>	<b>332'/S &amp; 620'/E</b>
<b>BOTTOM HOLE FOOTAGE:</b>	<b>10'/S &amp; 330'/E</b>
<b>LOCATION:</b>	<b>Section 20, T.26 S., R.35 E., NMPM</b>
<b>COUNTY:</b>	<b>Lea County, New Mexico</b>

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input checked="" type="radio"/> Low	<input type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input checked="" type="radio"/> Conventional	<input type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

### A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

### B. CASING

1. The **13-3/8 inch** surface casing shall be set at approximately **1,105 feet** (a minimum of **25 feet (Lea County)**) into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.

- b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

**Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.**

2. The minimum required fill of cement behind the **9-5/8 inch** intermediate casing and shall be set at approximately **5,300 feet** is:
  - Cement to surface. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
3. The minimum required fill of cement behind the **5-1/2 inch** production casing with a tie-back into the previous casing of approximately **4,865 feet** is:
  - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

**C. PRESSURE CONTROL**

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M) psi**.
3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **3000 (3M) psi**.

## **D. SPECIAL REQUIREMENT (S)**

### **Communitization Agreement**

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575) 393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

## B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
  - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including

lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

**YJ (09/11/2020)**

District I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
District II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office  
**OCB - HOBBS**  
**11/24/2020**  
**RECEIVED**  AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

1 API Number <b>30-025-48111</b>		2 Pool Code <b>96672</b>		3 Pool Name <b>WC-025 G-08 S263412K; Bone Spring</b>	
4 Property Code <b>328509</b>		5 Property Name <b>EL CAMPEON FED COM</b>			6 Well Number <b>204H</b>
7 OGRID No. <b>373986</b>		8 Operator Name <b>TITUS OIL &amp; GAS PRODUCTION LLC</b>			9 Elevation <b>3172'</b>

10 Surface Location


UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
P	20	26-S	35-E		332'	SOUTH	620'	EAST	LEA

11 Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
1	32	26-S	35-E		10'	SOUTH	330'	EAST	LEA

12 Dedicated Acres <b>233.64</b> <del>240</del>	13 Joint or Infill <b>Y</b>	14 Consolidation Code	15 Order No.
---	--------------------------------	-----------------------	--------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.



17 OPERATOR CERTIFICATION  
I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

*Ryan DeLong* 1/22/2020  
Signature Date

Ryan DeLong - Regulatory Manager  
Printed Name

rdelong@titusoil.com  
E-mail Address

18 SURVEYOR CERTIFICATION  
I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Date of Survey  
Signature and Seal of Professional Surveyor

**GARRETT J SMELKER**  
NEW MEXICO  
PROFESSIONAL SURVEYOR  
25036  
01/15/2020

Certificate Number

Intent  As Drilled

API #  
30-025-48111

Operator Name: Titus Oil & Gas Production, LLC	Property Name: El Campeon Fed Com	Well Number 204H
---	--------------------------------------	---------------------

Kick Off Point (KOP)

UL	Section 20	Township 26S	Range 35E	Lot	Feet 755	From N/S South	Feet 148	From E/W East	County Lea
Latitude 32.023580					Longitude -103.381389				NAD 83

First Take Point (FTP)

UL	Section 29	Township 26S	Range 35E	Lot	Feet 100	From N/S North	Feet 330	From E/W East	County Lea
Latitude 32.02123139					Longitude -103.38197323				NAD 83

Last Take Point (LTP)

UL	Section 32	Township 26S	Range 35E	Lot	Feet 100	From N/S South	Feet 330	From E/W East	County Lea
Latitude 32.00056978					Longitude -103.38195495				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?  N

Is this well an infill well?  N

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #

Operator Name:	Property Name:	Well Number
----------------	----------------	-------------

District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 S. First St., Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department

Submit Original  
to Appropriate  
District Office

Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

**OCD - HOBBS**  
**11/24/2020**  
**RECEIVED**

**GAS CAPTURE PLAN**

Date: 1/17/2020

Original Operator & OGRID No.: 373986  
 Amended - Reason for Amendment: \_\_\_\_\_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

*Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).*

**Well(s)/Production Facility – El Campeon CTB 20**

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
El Campeon South Fed Com 111H		Sec 29, T26S, R35E	1828' FNL & 632' FWL			El Campeon CTB 20 will be utilized
El Campeon South Fed Com 201H		Sec 29, T26S, R35E	1828' FNL & 707' FEL			El Campeon CTB 20 will be utilized
El Campeon South Fed Com 321H		Sec 29, T26S, R35E	1828' FNL & 657' FWL			El Campeon CTB 20 will be utilized
El Campeon South Fed Com 431H		Sec 29, T26S, R35E	1828' FNL & 682' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 032H		Sec 20, T26S, R35E	353' FSL & 2077' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 112H		Sec 20, T26S, R35E	353' FSL & 2107' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 122H		Sec 20, T26S, R35E	353' FSL & 2137' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 322H		Sec 20, T26S, R35E	579' FSL & 2077' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 432H		Sec 20, T26S, R35E	579' FSL & 2137' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 512H		Sec 20, T26S, R35E	579' FSL & 2107' FWL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 123H		Sec 20, T26S, R35E	355' FSL & 1927' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 203H		Sec 20, T26S, R35E	355' FSL & 1957' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 323H		Sec 20, T26S, R35E	581' FSL & 1912' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 403H		Sec 20, T26S, R35E	581' FSL & 1972' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 513H		Sec 20, T26S, R35E	581' FSL & 1942' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 034H		Sec 20, T26S, R35E	332' FSL & 590' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 114H		Sec 20, T26S, R35E	332' FSL & 650' FEL			El Campeon CTB 20 will be utilized
El Campeon Fed Com 204H	30-025-48111	Sec 20, T26S, R35E	332' FSL & 620' FEL			El Campeon CTB 20 will be utilized

El Campeon South 404H		Sec 20, T26S, R35E	558' FSL & 590' FEL			El Campeon CTB 20 will be utilized
El Campeon South 514H		Sec 20, T26S, R35E	558' FSL & 620' FEL			El Campeon CTB 20 will be utilized

**Gathering System and Pipeline Notification**

Well(s) will be connected to a production facility after flowback operations are complete, where a gas transporter system is in place. The gas produced from production facility is dedicated to Lucid and is connected to a Lucid low pressure gathering system located in Lea County, New Mexico. Titus provides (periodically) to Lucid a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Titus and Lucid have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at a Lucid’s Red Hills Plant located in Sec 13, T24S, R33E near Jal, NM. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

**Flowback Strategy**

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the well(s) start flowing through the production facilities, unless there are operational issues on Lucid’s system at that time. Based on current information, it is Titus’s belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be flared rather than sold on a temporary basis.

**Alternatives to Reduce Flaring**

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines