Form 3160-5 (June 2019)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2021

5. Lease Serial No. NMLC063798 6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

abandoned well.	Use Form 3160-3 (A	(PD) for such proposals.		
SUBMIT IN TRIPLICATE - Other instructions on page 2			7. If Unit of CA/Agreement, Name and/or No.	
1. Type of Well Oil Well Gas V	lament d		8. Well Name and No. BROADSIDE 13 FED COM W 1H	
2. Name of Operator BC OPERATING, INC.			9. API Well No. 30-025-46517	
3a. Address PO BOX 50820 3b. Phone		3b. Phone No. (include area code) (432) 684-9696	10. Field and Pool or Exploratory Area WC-025 G-09 S243310P UPPER WOLFCAMP	
4. Location of Well (Footage, Sec., T.,I N, 350' FSL & 2330' FWL, SEC 12)	11. Country or Parish, State LEA, NEW MEXICO	
12. CHE	CK THE APPROPRIATE B	OX(ES) TO INDICATE NATURE OF 1	NOTICE, REPORT OR OTHER DATA	
TYPE OF SUBMISSION		TYPE O	FACTION	
Notice of Intent	Acidize Alter Casing	Deepen Hydraulic Fracturing	Production (Start/Resume) Water Shut-Off Reclamation Well Integrity	
Subsequent Report Final Abandonment Notice	Casing Repair Change Plans Convert to Injection	✓ New Construction ☐ Plug and Abandon ☐ Plug Back ☐	Recomplete Other Temporarily Abandon Water Disposal	
completion of the involved operation completed. Final Abandonment Notice is ready for final inspection.) Please see attached summary ACCEPTED F BUREAU OF LAN CARLSBAD F	ons. If the operation results in tices must be filed only after of completed operations. OR RECORD D. MANAGEMENT IELD OFFICE	n a multiple completion or recompletion all requirements, including reclamation	uired subsequent reports must be filed within 30 days following a in a new interval, a Form 3160-4 must be filed once testing has been, have been completed and the operator has detennined that the site	
14. I hereby certify that the foregoing is JASON WACKER	true and correct. Name (Pri		EERING & OPERATIONS	
Signature Jush Waln		Date	Date 09/08/2020	
0	THE SPACE	FOR FEDERAL OR STATE	OFICE USE	
Approved by		Title PE	Date 12/21/2020	
Conditions of approval, if any are attack certify that the applicant holds legal or e which would entitle the applicant to con	equitable title to those rights		CFO	
Title 18 U.S.C Section 1001 and Title 4 any false, fictitious or fraudulent statem			d willfully to make to any department or agency of the United States	

Drilling Sundry Broadside 13 Fed COM W #1H; 30-025-46517

Spud Date: 12/06/2019 Rig Release Date: 1/14/2020

12,213'/17,426' TVD/MD as drilled. TD reached 1/12/2020 PBTD 17,397'

12/06/2019 - Well spud. Hole Size 17-1/2".

12/08/2019 - Called BLM (Paul Flowers) @ 12:00 PM with intent to run 13-3/8" csg and cmt.

12/09/2019 – TIH 34 jnts of 13-3/8", J-55, 54.0 lb casing to 1370'. Cement casing with 710 sx 13.4 ppg, 1.78 yield, water 9.4 gal/sx Lead Class C cement and 540 sx 14.8 ppg, Yield 1.34, water 6.3 gal/sx Tail Class C cement, displaced with 210 bbl water, bump plug @ 5:50 AM 12/10/2019 with 500 psi, final pressure 1050 psi. Floats held, gave back 1 bbl. Circulated 505 sx (160 bbl) cement back to surface.

12/10/2019 – WOC 5 hrs. Pressure test casing to 500 psig for 30 mins. Good test.

12/12/2019 - Drill ahead. Hole Size 12-1/4".

12/13/2019 - Called BLM (Trish Badbear) with intent to run 10-3/4" csg and cmt.

12/14/2019 – Set 131 jnts of 10-3/4", 45.5 lb, J-55 BTC casing @ 5236'. Cement 10-3/4" casing with 780 sx, 11.9 ppg 2.36 Yield Lead cement and 300 sx, 14.8 ppg, 1.34 Yield Tail cement, 1400 psig before landing plug, bump plug @ 02:15, land plug with 1840 psig, float held, gave 3.5 bbl back (circulated 326 sx (137 bbl) cement to surface), RD cementers.

12/16/2019 - WOC 33 hours. Pressure test casing to 1500 psig for 30 mins. Good test. Drill ahead. Hole Size 9-7/8".

12/24/2019 – Set 345 jnts 7-5/8", 29.70#, HCP-110 BTC casing @ 12,343'. Cement 7-5/8" casing with 1635 sx, 2.27 Yield, 11.8 ppg Lead cement and 300 sx, 1.34 Yield, 14.2 ppg Tail cement. Did not land plug. With 210 bbl displaced, lost returns. With 280 bbl displaced, pressured up to 4700 psig. Floats held, got 7 bbl back.

12/25/2019 - Called BLM (Mandela Kamau) for remedial cementing procedure on 7-5/8" casing.

12/27/2019 – Ran CBL. TOC behind 7-5/8" casing is 6100'. Set CIBP @ 6100'. Perforated squeeze holes in 7-5/8" casing @ 6080'.

12/30/2019 - Set cement retainer @ 5894'.

12/31/2019 – Squeezed holes in casing to tie cement back to prior 10-3/4" casing string @ 5236'. Cement job consisted of 20 bbl freshwater spacer and 330 sx, 1.33 Yield, 14.8 lb/gal, water 6.3 gal/sx, Tail Class C cement. Displaced with 84 BBL freshwater. TOC @ 4500'. Stung out of retainer and circ clean. WOC 18 hrs. Drill cement retainer and cement to 6094'.

1/02/2020 – Drill bridge plug @ 6100' and CO to 12,300'. Pressure test 7-5/8" casing to 1500 psig for 30 mins. Good test. CO to 12,341'.

1/04/2020 - Hole Size 6-3/4".

1/12/2020 - TD well @ 17,426'.

1/14/2020 – Set 383 jnts 5-1/2", 20.0#, P-110- EYHC casing @ 17,426'. RU cementers test lines, pump 80 sx, 35.9 bbl, 11.5 ppg, 2.52 Yield Lead cement and 540 sx, 128.8 bbl, 13.8 ppg, 1.34 Yield Tail cement, bumped plug w/3650 psig. Pressure test casing to 4000 psig for 30 mins. Good test. Floats held 3.5 bbl back. Rig Released.

1/22/2020 - Ran GR/CBL/CCL inside 5-1/2" casing from 17150'-5950'. TOC @ 6250'