

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87400
District IV - (505) 476-3460
1220 S St Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

HOBBS OCD

OIL CONSERVATION DIVISION

AUG 29 2011

1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

WELL API NO. 30-025-26492
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. 3680
7. Lease Name or Unit Agreement Name State HL
8. Well Number 1
9. OGRID Number 217955
10. Pool name or Wildcat Brinninstool Bone Springs

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
OGX Resources LLC

3. Address of Operator
P. O. Box 2064 Midland, Texas 79702

4 Well Location

Unit Letter L : 1980 feet from the South line and 660 feet from the West line
Section 2 Township 23S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/18/11-8/23/11 MIRUPU. With end of tubing at 5005', circ hole w/10# brine & gel. Then spot 25 sxs Cl C (14.8 ppg, 1.32 yield) w/1% CaCl at 5005'. Tag plug at 4867'. Perf 7 5/8" casing at 3372'. Spot 50 sxs Cl C w/1% CaCl. Squeeze 25 sxs into perfs. Tag plug at 3295'. Perf 7 5/8" casing at 1870'. Circ thru perfs & out 10 3/4" casing. Spot 50 sxs Cl C w/1% CaCl at 1870'. Squeeze 25 sxs into perfs. Did not tag the cmt, so spot another 50 sxs Cl C w/1% CaCl at 1870'. Tag plug at 1775'. Perf 7 5/8" csg at 940'. Spot 50 sxs Cl C w/1% CaCl. Squeeze 25 sxs into perfs. Tag plug at 790'. Perf 7 5/8" csg to 300'. Pump 115 sxs Cl C w/1% CaCl. Circ cmt to surface. Cut off wellhead below ground level & install dry hole marker. Maintained contact w/Mark Whitikar w/NMOCD during plugging operation.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.emnrd.state.nm.us/oed.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Steve Douglas TITLE Engineer DATE 8/25/11

Type or print name Steve Douglas E-mail address: steve@ogxresources.com PHONE: 432/685-1287

For State Use Only

APPROVED BY [Signature] TITLE State Engineer DATE 8-30-2011
Conditions of Approval (if any):

AUG 30 2011