

Submit 3 Copies To Appropriate District
Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88201
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103

May 27, 2004

SEP 07 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

WELL API NO. 30-025-05810
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name North Monument Grayburg/SA Unit Blk 17
8. Well Number 15
9. OGRID Number 873
10. Pool name or Wildcat Eunice Monument;G/SA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3568' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ N/A _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
OTHER: drill out & add Plugs ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/23/11 MIRU plugging equipment.

8/24/11 Tag existing 7" CIBP @ 3787'. Circ. Hole w/mlf. Cap w/80 sxs cmt woc.

8/25/11 Tag cmt plug @ 3356'. Perf 6 holes @ 2535'. Started flowing water - 200bbls/hr. Shut in @ 1000 psi.

8/26/11 Set 7" CICR @ 2435'. Sqz 150 sxs cmt.

8/29/11 Sting into CICR & pressure test to 1500psi. Cap CICR w/25 sxs cmt (150'). Perf @ 1450'. 7" pkr @ 1009'. Sqz 80 sxs cmt. woc

8/30/11 Tag cmt plug @ 1200'. Perf @ 300'. Sqz 80 sxs cmt. Woc tag @ 130'. Perf @ 125'. Circ 35 sxs cmt 7" x 9 5/8" To surface. Sqz 25 sxs 9 5/8" x 12 1/2" woc.

8/31/11 Tag cmt plug @ 15'. Install dry hole marker. MO plugging equipment. **Cut off anchors & w.h. Clean location.**

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmrnd.state.nm.us/oecd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE  TITLE P & A Technician (Basic Energy Services) DATE 9/6/11

Type or print name: **Greg Bryant**

E-mail address:

Telephone No. 432-563-3355

For State Use Only

APPROVED BY  TITLE STAFF DATE 9-8-2011

Conditions of Approval (if any):

SEP 08 2011