

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

HOBBS OCD
SEP 08 2011
RECEIVED

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-25927
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: J.W. COOPER
8. Well Number 007
9. OGRID Number 162683
10. Pool name or Wildcat JALMAT TAN-YATES-7 RVRs ON-GRBURG.

Pit or Below-grade Tank Application ☐ or Closure ☒
Pit type STEEL Depth to Groundwater _____ Distance from nearest fresh water well * _____ Distance from nearest surface water * _____
Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material * NONE WITHIN 1,000'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:
Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
CIMAREX ENERGY CO. OF COLORADO ATTN: ZENO FARRIS

3. Address of Operator
600 N. MARIENFELD, SUITE 600, MIDLAND, TEXAS 79701

4. Well Location
Unit Letter J : 1650 feet from the SOUTH line and 2310 feet from the EAST line
Section 14 Township 24S Range 36E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,338' - GR

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all per of starting any proposed work). SEE RULE 1103. For Multiple or recompletion.

PROPOSED PLUG AND ABANDONMENT PROCEDURE:

- 1) SET 5-1/2" CIBP @ 3,100'; PRES. TEST 5-1/2" CSG. TO 500#; CIRC. WELL W/ PXA MUD.
- 2) MIX X PUMP A 55 SX. CMT. PLUG @ 3,100'-2,690' (T/YATES, DV TOOL, B/SALT); WOC X TAG CMT. PLUG.
- 3) MIX X PUMP A 30 SX. CMT. PLUG @ 1,400'-1,170' (T/SALT, 8-5/8" CSG. SHOE, T/ANHY.); WOC X TAG CMT. PLUG.
- 4) MIX X CIRC. TO TO SURF. A 10 SX. CMT. PLUG @ 63'-3'.
- 5) DIG OUT X CUT OFF WELLHEAD 3' B.G.L.; WELD ON STEEL PLATE TO CASINGS X INSTALL DRY HOLE MARKER.

The Oil Conservation Division Must be notified
24 hours prior to the beginning of plugging operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE David A. Eyer TITLE AGENT DATE 09/03/11
E-mail address: deyer@milagro-res.com
Type or print name DAVID A. EYER Telephone No. (432) 687-3033

For State Use Only

APPROVED BY [Signature] TITLE Staff member DATE 9-12-2011
Conditions of Approval, if any:

SEP 13 2011

CIMAREX

KB: 3351' (12')

GL: 3338'

Cimarex Energy Co. of Colorado

JW Cooper #7

1650' FSL & 2310' FEL

14-24S-36E

Lea County, NM

API: 30-025-25927

LDL 2/24/10

8 5/8" 24# K55 STC @ 1226'

Cmt'd w/800 sx, circ 100 sx

DV Tool 2811'

Tubing & Rod Detail: from 8/7/09 report

Quantity	Description	Length	Setting Depth
	KB	0.00	0.00
2	2 7/8" ' 10' sub	20.45	20.45
100	2 7/8" EUE 8rd J55 tbg	3125.68	3146.13
1	3 1/2" x 10' sub	10.30	3156.43
	Stator	30.60	3187.03
1	3 1/2" x 1' nipple w/2 7/8" X/O	2.00	3189.03
	(X/O has tag plate)		3189.03
	2 7/8" SN	1.10	3190.13
	2 7/8" x 5 1/2" TAC left rise	2.80	3192.93
	EOT		3192.93
	1 1/4" x 16' PR w/2' liner	16.00	
	1" rod	25.00	
	1" x 6', 4', 1' pony rod	11.00	
125	1" rods	3125.00	
	1" x 1' lift sub	1.00	
	Rotor	31.50	
	Total Rod String Length	3209.50	

RUSTLER 1224'

T/SALT 1342'

B/SALT 2742'

YATES 2893'

7-R 3110'

7 Rivers / Yates Perfs:

3131'-3137' w/1 SPF (7 holes)

3153'-3161' w/1 SPF (9 holes)

3164'-3172' w/1 SPF (9 holes)

3177'-3183' w/1 SPF (7 holes)

CIBP 3240' w/1 sx cmt cap

3257'-3265' w/1 SPF (9 holes)

Stator

PBSD: 3240'; Original 3280' (SLM)

TD: 3300'

5 1/2" 14# K55 STC @ 3300'

Cmt'd w/925 sx, circ 150 sx

CIMAREX

KB: 3351' (12')

GL: 3338'

Cimarex Energy Co. of Colorado

JW Cooper #7

1650' FSL & 2310' FEL

14-24S-36E

Lea County, NM

API: 30-025-25927

LDL 2/24/10

8 5/8" 24# K55 STC @ 1226'

Cmt'd w/800 sx, circ 100 sx

105xs. cmt.

@ 68'-3'

305xs. cmt.

@ 1,400' - 1,170'

DV Tool 2811'

55 xs. cmt.

@ 3,100' - 2,690'

5 1/2" CIBP @
3,100'**7 Rivers / Yates Perfs:**

3131'-3137' w/1 SPF (7 holes)

3153'-3161' w/1 SPF (9 holes)

3164'-3172' w/1 SPF (9 holes)

3177'-3183' w/1 SPF (7 holes)

CIBP 3240' w/1 sx cmt cap

3257'-3265' w/1 SPF (9 holes)

5 1/2" 14# K55 STC @ 3300'

Cmt'd w/925 sx, circ 150 sx

Stator

PBTD: 3240'; Original 3280' (SLM)

TD: 3300'

RUSTLER 1224'
T/SALT 1342'
B/SALT 2742'
YATES 2895'
7-R 3110'

09/12/11 DAE