

HOBBS OCD

## OIL CONSERVATION DIVISION

SEP 16 2011

1220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: ☒ Well ☐ Gas Well ☐ Other2. Name of Operator  
APACHE CORPORATION3. Address of Operator  
303 VETERANS AIRPARK LANE, STE 3000; MIDLAND, TX 79705

## 4. Well Location

Unit Letter K : 1680 feet from the S line and 2310 feet from the WEST line  
Section 8 Township 20S Range 37E NMPM County LEA11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3547' GRWELL API NO.  
30-025-401455. Indicate Type of Lease  
STATE ☐ FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name  
T ANDERSON

8. Well Number 006

9. OGRID Number  
87310. Pool name or Wildcat  
Monument;Abo,Southeast

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐OTHER: ☐OTHER: ADD TUBB AND DRINKARD ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7-20-2011: RIH WITH 3 1/8" SLICK GUNS AND PERF ABO @

6958-6962,6966-6970,6976-6980,7021-7023,7032-7034,7042-7046,7048-7050,7058-7062,7084-7087,7094-7100,7106-7

110,7116-7120,7125-7127,7130-7133,7160-7164,7200-7203,7221-7224,7234-7237,7246-7250,7264-7268,7271-7274,73

02-7304,7356-7364. 2 SPF. 120 DEG PHASE. 210 HOLES. ACIDIZE ABO PERFS WITH 6000 GALS 15% NEFE HCL ACID.

7-26-2011: FRAC ABO: PUMP 30000 GALS BFRAC 20, PUMP 32000 GALS GEL ACID, PUMP 28000 GALS 20% ACID, PUMP 20000 GALS TREATED WTR; PMP 238 BBLs FLUSH.

8-16-2011: RIH WITH 2 7/8" SN, 1-2 7/8" BLAST JT, 17 JTS 2 7/8" TBG, 5 1/2" X 2 7/8" TAC AND 221 JTS 2 7/8" TBG. SN @ 7424'. TAC @ 6867'. ND BOP. NU WELLHEAD.

8-19-2011: RIH WITH PUMP AND RODS. SPACE OUT PUMP. LOAD TBG AND CHECK PUMP ACTION TO 500#. RD PU AND CLEAN LOCATION. SET PUMPING UNIT. RUN ELECT SERVICE. WELL PUMPING

Spud Date: 06/18/2011

Rig Release Date: 07/09/2011

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE SR. STAFF ENGR TECH

DATE 09/13/2011

Type or print name BEV HATFIELD

E-mail address: beverly.hatfield@apachecorp.com

PHONE: 432-818-1906

## For State Use Only

APPROVED BY:

TITLE

PETROLEUM ENGINEER

DATE

SEP 19 2011

Conditions of Approval (if any):

SEP 19 2011