Form 3160-5 (August 2007)

UNITED STATES

HOBI	BS O	CD
CEP	22	5011

FORM APPROVED

OMB N	O. 1004-013;
Expires:	July 31, 201
ease Serial No	

	UREAU OF LAND MANA	GEMENT CEP	22 2011	Expires	: July 31, 2010
SUNDRY	NOTICES AND REPO	RTS ON WELLS		NMNM17807	
abandoned we	II. Use form 3160-3 (AP	D) for such proposals.	RECEIVED	6 If Indian, Allottee	or Tribe Name
SUBMIT IN TRI	PLICATE - Other instruc	ctions on reverse side.	·	7. If Unit or CA/Agre NMNM91005X	eement, Name and/or No
Type of Well Oil Well	-			8. Well Name and No QPQAS UNIT 17	
2 Name of Operator Contact: JACKIE LATHAN MEWBOURNE OIL COMPANY E-Mail: jlathan@mewbourne.com			9. API Well No. 30-025-24455-0	00-S1 /	
3a Address	Address 3b. Phone No. (include area code) Ph: 575-393-5905		:)	10. Field and Pool, or Exploratory QUERCHO PLAINS AS	
HOBBS, NM 88240		7 n. 373-393-3903		QUENCHO FE	ains Qn As
4 Location of Well (Footage, Sec., T., R, M., or Survey Description)				11. County or Parish, and State	
Sec 23 T18S R32E SESW 660FSL 1980FWL			LEA COUNTY, NM		
•					
12. CHECK APPL	ROPRIATE BOX(ES) TO	O INDICATE NATURE OF	NOTICE, RI	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
□ Notice of Intent	☐ Acidize	□ Deepen	Producti	ion (Start/Resume)	☐ Water Shut-Off
	☐ Alter Casing	☐ Fracture Treat	Reclamation Recomplete		■ Well Integrity
Subsequent Report	□ Casing Repair	■ New Construction			□ Other
☐ Final Abandonment Notice	Change Plans	Plug and Abandon	☐ Temporarily Abandon		
,	Convert to Injection	□ Plug Back	☐ Water Disposal		
13. Describe Proposed or Completed Oplif the proposal is to deepen directional Attach the Bond under which the work following completion of the involved testing has been completed. Final Attach the site is ready for final that the site is ready for final Attach the site is ready for final Attach that the site is ready for final Attach that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide operations. If the operation resondonment Notices shall be filtinal inspection.)	give subsurface locations and measi the Bond No. on file with BLM/BIA sults in a multiple completion or rec	red and true ve A Required sub ompletion in a r ding reclamation	ntical depths of all pertii bsequent reports shall be new interval, a Form 316 n, have been completed,	nent markers and zones e filed within 30 days 50-4 shall be filed once
In veil goes off produc					

30 days notify BLM by Sundry within 5 business days

14 Thereby certify that the foregoing is true and correct Electronic Submission #115940 verifie For MEWBOURNE OIL CO Committed to AFMSS for processing by KU	/IPANY, sent to the Hobbs				
Name(Printed/Typed) ROBIN TERRELL	Title SR PRODUCTION ENGINEER				
Signature (Electronic Submission)	Date 08/24/2011				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved By REJECTED	DUNCAN WHITLOCK TitleLEAD PET	Date 09/20/2011			
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those nights in the subject lease which would entitle the applicant to conduct prestions thereon.	Office Hobbs				
Fitle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any punishers any false, fictitious or fraudulent statements or representations as to any matter w	erson knowingly and willfully to make to any department of thin its jurisdiction	or agency of the United			

Conditions of Approval: Wells with Packers*

Mewbourne Oil Company QPQASU 17 API 3002524455

September 14, 2011

- Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within. 30 days.
 - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
 - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
 - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a. Approved injection pressure compliance is required.
 - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
 - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
 - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
 - b. **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of this approval.
 - The operator shall keep monthly records documenting that the casing annulus is fluid filled.
 A suggested format for these records is available from the BLM Carlsbad Field Office.
 Copies of those records shall be furnished at the request of a BLM authorized officer.
 - d. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - a. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
 - e. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
 - f. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.

^{*}COA's prepared by Paul R Swartz