Submit I Copy To Appropriate District Office	State of New Mexico	Form C-103
District I - (575) 393-6161	Energy, Minerals and Natural Resources	October 13, 2009
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> - (575) 748-1283		WELL API NO.
811 S. First St., Artesia, NM 88210	RECOMPERVATION DIVISION	30-025-00662
District III - (505) 334-6178	1220 South St. Francis Dr.	5. Indicate Type of Lease STATE FEE FED
1000 Rio Brazos Rd., Aztec, NM 87410 <u>District IV</u> - (505) 476-3460	SEP 2920 Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	2Ek 585011	306907
87505	HORRSOCD OVER 1	
1	TISES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
	PLICATION FOR PERMIT" (FORM C-101) FOR SUCH	CAPROCK MALJAMAR UNIT
PROPOSALS.)	· · · · · ·	8. Well Number: 49
1. Type of Well: Oil Well	Gas Well Other INJECTION	
2. Name of Operator LINN OPERATING, INC.		9. OGRID Number 269324
3. Address of Operator		10. Pool name or Wildcat
600 TRAVIS, SUITE 5100, HO	USTON TEXAS 77002	MALJAMAR; GRAYBURG-SAN
300 1101113, 30112 3100, 110	001011, 127110 77002	ANDRES
4. Well Location		111,2122
Unit Letter H;	1980 feet from the N line and	660 feet from the E line
Section 24	Township 17S Range	32E NMPM LEA County
	11. Elevation (Show whether DR, RKB, RT, GR, 4.183' GR	eic.)
	4,163 OK	
12 Charl	. Ammonista Day to Indicate Nature of Nati	Daniert or Other Date
12. Check	Appropriate Box to Indicate Nature of Notice	ce, Report or Other Data
NOTICE OF	INTENTION TO: SI	JBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK		
TEMPORARILY ABANDON [DRILLING OPNS. P AND A
PULL OR ALTER CASING	☐ MULTIPLE COMPL ☐ CASING/CEM	
		
OTHER:	OTHER:	
13. Describe proposed or cor	mpleted operations. (Clearly state all pertinent details	and give pertinent dates, including estimated date
13. Describe proposed or cor of starting any proposed	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
13. Describe proposed or cor	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
 Describe proposed or cor of starting any proposed proposed completion or r 	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
13. Describe proposed or cor of starting any proposed	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple	and give pertinent dates, including estimated date Completions: Attach wellbore diagram of
Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion.	Completions: Attach wellbore diagram of
 13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI 	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3	Completions: Attach wellbore diagram of
 13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI 	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion.	Completions: Attach wellbore diagram of
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL,	Completions: Attach wellbore diagram of 83'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg.	Completions: Attach wellbore diagram of 83'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot	Completions: Attach wellbore diagram of 83'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2.025'-2.420'.
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 3	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tagget work work in case.	Ragged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'.
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'. 1	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer	Ragged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'.
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 3	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer	Ragged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'.
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'. 1	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer	Completions: Attach wellbore diagram of 83'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. tagged plug @ 2,250'. POH LD tbg to 1,375'. tt from 980-1,375'. POH w/ 900' of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'. 1	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer	Completions: Attach wellbore diagram of 83'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. tagged plug @ 2,250'. POH LD tbg to 1,375'. tt from 980-1,375'. POH w/ 900' of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'. 1	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., target RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location.	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. It from 980-1,375'. POH w/ 900' of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'.] @ 34'. Displaced cmt to 1,225'.	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. It from 980-1,375'. POH w/ 900' of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or n 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5 Stood back 300'. Perf @ 1,325'.] @ 34'. Displaced cmt to 1,225'.	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., target RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location.	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. It from 980-1,375'. POH w/ 900' of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @: Stood back 300'. Perf @ 1,325'.] @ 34'. Displaced cmt to 1,225'. Spud Date:	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420' of tbg. LD the remainder. g, couldn't get past 240'. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420'. Spot 34'. Displ cmt to 2,250'. WOC 4 hrs. RIH w/ tbg., tagili RIH w/ tbg to 1,375'. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date:	Ranged plug @ 2,370°. POH. RIH w/ WL, perf @ POH, RIH w/ 3000° of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025°-2,420°. agged plug @ 2,250°. POH LD tbg to 1,375°. It from 980-1,375°. POH w/ 900° of tbg. Set pkr
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ . Stood back 300'. Perf @ 1,325'	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date:	Ragged plug @ 2,370°. POH. RIH w/ WL, perf @ POH, RIH w/ 3000° of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025°-2,420°. agged plug @ 2,250°. POH LD tbg to 1,375°. at from 980-1,375°. POH w/ 900° of tbg. Set pkr Accepted for Record Only Accepted for Record Only COL Holds:
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ . Stood back 300'. Perf @ 1,325'	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date:	Ragged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. at from 980-1,375'. POH w/ 900' of tbg. Set pkr Recepted for Record Only Accepted for Record Only COL Holds:
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ . Stood back 300'. Perf @ 1,325'	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date:	Ragged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. at from 980-1,375'. POH w/ 900' of tbg. Set pkr Recepted for Record Only Accepted for Record Only COL Holds:
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ . Stood back 300'. Perf @ 1,325'	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., ta RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date: TITLE: REGULATORY SP	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. at from 980-1,375'. POH w/ 900' of tbg. Set pkr Accepted for Record Only Accepted for Record Only EGG 9-29-20, edge and belief.
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5tood back 300'. Perf @ 1,325'. I @ 34'. Displaced cmt to 1,225'. Spud Date: I hereby certify that the information of the property of the prope	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,2 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., tare RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date:	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. at from 980-1,375'. POH w/ 900' of tbg. Set pkr Accepted for Record Only Accepted for Record Only EGG 9-29-20, edge and belief.
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BO! "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ . Stood back 300'. Perf @ 1,325'	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., ta RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date: TITLE: REGULATORY SP	R3'. Circ hole w/ salt gel. Spotted 24 sxs Class tagged plug @ 2,370'. POH. RIH w/ WL, perf @ POH, RIH w/ 3000' of tail pipe & packer. Tried ted 40 sxs Class "C" cmt from 2,025'-2,420'. agged plug @ 2,250'. POH LD tbg to 1,375'. at from 980-1,375'. POH w/ 900' of tbg. Set pkr Accepted for Record Only Accepted for Record Only EGG 9-29-20, edge and belief.
13. Describe proposed or cor of starting any proposed proposed completion or r 9/7/11 – MI PU 9/8/11 – RUPU ND WH, NU BOI "C" neat cmt from 3,136-3,383'. 9/9/11 – RIH w/ 5-1/2" gauge ring 2,370'. POH, RIH w/ muleshoe e to work pkr downhole. POH, slip POH w/ 1800' of tbg. Set pkr @ 5tood back 300'. Perf @ 1,325'. I @ 34'. Displaced cmt to 1,225'. Spud Date: I hereby certify that the information of the property of the prope	mpleted operations. (Clearly state all pertinent details work). SEE RULE 19.15.7.14 NMAC. For Multiple recompletion. P. PU & RIH w/ tbg open ended & tagged plug @ 3,3 POH standing back 2,420° of tbg. LD the remainder. g, couldn't get past 240°. POH LD GR. RIH w/ WL, and 5-1/2" pkr. Tried to work pkr thru bad spot in csg. was broken on pkr. RIH open ended to 2,420°. Spot 34°. Displ cmt to 2,250°. WOC 4 hrs. RIH w/ tbg., ta RIH w/ tbg to 1,375°. Spotted 40 sxs class "C" cemer RD PU, cleaned location. Rig Release Date: TITLE: REGULATORY SP	Racepted for Record Only Accepted for Record Only Accepted for Record Only CCIALIST III DATE SEPTEMBER 29,2011 Mar 183'. Circ hole w/ salt gel. Spotted 24 sxs Class Ray Class