the second of th		
	ate of New Mexico	Form C-103
Office District I Energy, Minerals and Natural Resources		WELL API NO. June 19, 2008
1625 N French Dr., Hobbs, NM 88246BBS OCD  District II. 1301 W. Grand Ave. Artesia, NM 8821 0 OIL CONSERVATION DIVISION		30-025-36988  5. Indicate Type of Lease
District III 1220	1 2011 1220 South St. Francis Dr.	
I 000 Rio Brazos Rd., Aztec, NM 87401 1 2011  District IV.	Rio Brazos Rd., Aztec, NM 87401 L L Zorr Santa Fe, NM 87505	
1220 S. St. Francis Dr, Santa Fe, NM 87505		V-5860
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		T-Rex State
1. Type of Well: Oil Well Gas Well Other		8. Well Number 1
2. Name of Operator  Mack Energy Corporation		9. OGRID Number 013837
3. Address of Operator		10. Pool Name or Wildcat mayanar
P.O. Box 960 Artesia, NM 8	38210	West Kemnitz-Wolfcamp-Graybry, 517
4. Well Location Unit Letter H 1980 feet fr	om the North line and	660 feet from the East line
Unit Letter H 1980 feet fr Section 31 Town	169 225	NMPM County Lea
20	(Show whether DR, RKB, RT, GR etc.,	
4239'		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF INTENTION TO		SEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND AB	<del></del>	
TEMPORARILY ABANDON		· · · · · · · · · · · · · · · · · · ·
	mais Wis	
OTHER:	OTHER:	100 m
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		
10/3/2011 MIRU. Set CIBP @ 4750'.		
10/4/2011 Circulate hole with salt gel. Set 35sx Class C neat cement plug @ 4750'-4390'. Set 25sx Class C cement with 3%		
Calcium plug @ 4100'-3850'. Set 25sx Class C cement with 3% calcium plug @ 2662'-2412'. WOC tag @ 2405'. Set 30sx Class C cement with 4% calcium plug @ 1565'-1315' WOC tag @ 1257'. Circulate cement from 390' to surface. Install Dry hole Marker.		
		on 500 to surface. Instant Dry note Warker.
Approved for plugging of well bore only.		
	of C-103	Subsequence B. (Subsequence B.
	Forms, w	tay be found at OCD Web Page under to www.cmird.state.nm.us/ocd.
		and the state of t
	i iid ad	
Spud Date: 9/8/2009	Rig Release Date:	0/09/2009
30.203		
I hereby certify that the information above is true slid	complete to the best of my knowledge	ve and belief
Thereby certify that the information above is the site complete to the cost of my knowledge and content		
SIGNATURE Jany W. Shevell	TITLE Production Clerk	DATE 10/7/11
Type or print name Jerry W. Sherrell	E-mail address: jerrys@mec.com	m PHONE: (575)748-1288
For State Use Only		
APPROVED BY TITLE STAFF MATE 10-12-2011		
Conditions of Approval (if any):		
		/