Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR OCT 13 2011 BUREAU OF LAND MANAGEMENT 1

 	_	 Expires: July 31, 2010
		OMB No. 1004-0137
		FORM APPROVED

5. Lease Serial No.
NMLD029405B

SUNDRY			NMLD029405B
abandoned well.	form for proposals to	ORTS ON WELLS ENTER o drill or to re enter an PD) for such proposal	
CIIDM	IT IN TRIPLICATE - Other	instructions on page 2	7. If Unit of CA/Agreement, Name and/or No.
1. Type of Well	- Culer	matractions on page 2.	/
X Oil Well Gas	Weld Other		8. Well Name and No. Ruby Federal 3
2. Name of Operator	7		9. API Well No. 30-025-40222
ConocoPhillips Company 3a. Address	· · · · · · · · · · · · · · · · · · ·	3b. Phone No. (include area co	
		(432)688-9174	Maljamar, Yeso, West
3300 N "A" St Midland TX 4 Location of Well (Footage, Sec., T.	R. M. or Survey Description)	(432)000-8114	11. Country or Parish, State
4. Location of Well (Footage, Sec., T. UL: N, 330' FSL & 2310' F	WL, Sec 17, T17S, R	32E /	LEA NM
12. CHE	CK THE APPROPRIATE BO	X(ES) TO INDICATE NATUR	E OF NOTICE, REPORT OR OTHER DATA
TYPE OF SUBMISSION		TY	PE OF ACTION
District Class	Acidize	Deepen	Production (Start/Resume) Water Shut-Off
Notice of Intent	Alter Casing	Fracture Treat	Reclamation Well Integrity
	Casing Repair	New Construction	Recomplete X Other Spud
X Subsequent Report	Change Plans	Plug and Abandon	Temporarily Abandon
Final Abandonment Notice	Convert to Injection	Plug Back	Water Disposal
determined that the site is ready for		,	n or recompletion in a new interval, a Form 3160-4 must be filed once s, including reclamation, have been completed and the operator has
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (94. & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8	94. & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (94. & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716	#. Circ 50 bbls to surf. WOC
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (9/28/11 PT surf csg to 100	94. 2 & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls 00#/30 mins - test goo	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716 d.	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC ACCEPTED FOR RECORD OCT 8 2073
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (9/28/11 PT surf csg to 100	94. 2 & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls 00#/30 mins - test goo	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716 d.	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC ACCEPTED FOR RECORD OCT 8 2073
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (9/28/11 PT surf csg to 100	94. 2 & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls 00#/30 mins - test goo	D. RIH w/17 jts, 8 5/8", : FW. Bump plug to 716 d.	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC ACCEPTED FOR RECORD OCT 8 200' BURE/U OF LAND MANAGEMENT CARLSBAD FIELD OFFICE egulatory Technician
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (9/28/11 PT surf csg to 100) 14 I hereby certify that the foregoing is Rhonda Rogers	94. 2 & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls 00#/30 mins - test good true and correct. Name (Printed	D. RIH w/17 jts, 8 5/8", FW. Bump plug to 716 d. Title Staff R	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC ACCEPTED FOR RECORD OCT 8 2089 BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE egulatory Technician
9/26/11 MIRU Precision 1 9/27/11 Spud 12 1/4" hole spacer. Lead of 280 sx (8 & 200 sx (48 bbls) Class (9/28/11 PT surf csg to 100) 14 I hereby certify that the foregoing is Rhonda Rogers	94. 2 & drill to 812' spud TE 35 bbls) Class C cmt C cmt. Disp w/48 bbls 00#/30 mins - test good true and correct. Name (Printed	D. RIH w/17 jts, 8 5/8", FW. Bump plug to 716 d. #/Typed) Title Staff R	s, including reclamation, have been completed and the operator has 24#, J-55 csg & set @ 798'. Pump 20 bbls FW #. Circ 50 bbls to surf. WOC ACCEPTED FOR RECORD OCT 8 2089 BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE egulatory Technician

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,

(Instructions on page 2)

entitle the applicant to conduct operations thereon.

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.