This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

NEW MEXICO OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

ETEST

API # 30-0 300392541000

Page 1 Revised June 10, 2003

Well

Or	erator	Williams	Exploration	and Production	ì
VΙ	Jorator	VV 1111411110	.Corp. Coracion		_

Location Of Well: Unit Letter <u>L</u> Sec <u>31</u> Twp <u>31N</u> Rge <u>05W</u>

Lease Name Rosa Unit

No. <u>137</u>

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)	
Upper Completion	PC	Gas	Flow	TBG !	
Lower Completion	MV	Gos	Flow	7 B.G	

Pre-Flow Shut-In Pressure Data Stabilized? (Yes or No) SI Press. Psig Length of Time Shut-In Hour, Date, Shut-In Upper 226 0230 Length of Time Shut-In 1030 Completion Stabilized? (Yes or No) SI Press. Psig Hour, Date, Shut-In Lower T 186 1050 Completion

			Flow T			
Commenced a	t (hour, date)*	730 3.	7-05	Zone	producing (Up	per or Lower): 400EC
Time (Hour, Date)	Lapsed Time Since*		essure Lower Com	pl.	Prod. Zone Temp.	Remarks
1030 3-8	1 DAG	T /34	T 193	<i>></i>	36_	PC PROBUCED @ ROTE
1030 3-9	2 Days	T 101	T 190	e	20	10 P ITO MEFO COR
1630 B-10	3 DAYS	T 101	T 200	2	24	24 HPS than LOGGED
11E 0E0	4 DAys	C 103	T 203	·	28	OFF GR DUNGTION
	1					1 of 485T
						1829 30 3N 7 3
Production rate	during test	<u></u>		1		Map

Gas:17	MCFPD; Test th	ru (Orifice or Meter): WETE		Ding DIV. of
		Mid-Test Shut-In Pressure D		Solding Sports on No.
Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized 2 (Yes or No)
Completion			<u> </u>	G. 1'1' 10 (W N-)
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion				

Oil: ______BOPD based on _____Bbls. In _____ Hrs. ____ Grav.

(Continue on reverse side)

Flow Test No. 2

. /1 1		Flow Test I		
at (hour, date)**	,			
1			1	Remarks
				and the state of the state of
			,	
		· .	:	
			,	422
·				
BOPD based MCFPI	on D; Test thru (Orif	Bbls. In ice or Meter):	Hrs	Grav. GOR
	. , ,			The state of the s
	• •			and the second of the second o
that the informati	on herein contain	ed is true and com	plete to the best of	
		ed is true and com		of my knowledge.
that the information MAR 3 1	2005		Operator <u></u>	of my knowledge. Prop. Exp.
MAR 3 1	2005		Operator By	of my knowledge.
MAR 3 1	2005 ivision		Operator By Title	of my knowledge. Prop. Exp.
	Lapsed Time Since**	Lapsed Time Since** Upper Compl.	Lapsed Time Since** Upper Compl. Lower Compl.	Lapsed Time Since** Upper Compl. Lower Compl. Temp.

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).