This form is <u>not</u> to be used for reporting packer leakage tests in Southeast New Mexico

Completion

NEW MEXICO OIL CONSERVATION DIVISIONS

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

API # 30-0 300392659900

Revised June

Page 1

Location Of Well: Unit Letter J Sec 12 Twp 31N Rge 06W

DATIOTA

Operator Williams Exploration and Production Lease Name Rosa Unit

Well No. 149B

				•
	Name of Reservoir or Pool	Type of Prod.	Method of Prod.	Prod. Medium
		(Oil or Gas)	(Flow or Art. Lift)	(Tbg. Or Csg.)
Upper]	
Completion	Mesa weade	GAS	Flow	Tha
Lower				

Pre-Flow Shut-In Pressure Data Hour, Date, Shut-In Length of Time Shut-In SI Press. Psig Stabilized? (Yes or No) Upper Completion 9:00 3-4-05 96 bas Length of Time Shut-In Stabilized? (Yes or No) SI Press. Psig Lower Hour, Date, Shut-In Completion 3-41-05 96 has 01:00

Flow Test No. 1 Commenced at (hour, date)* Zone producing (Upper or Lower): 0900 3-8-05 Time Lapsed Time Prod. Zone Remarks Pressure Since* (Hour, Date) Upper Compl. Lower Compl. Temp. 0900 3-405 24 hor 0900 7-1001 48 /11 670 roduction rate during test

Dil: _____BOPD based on ____Bbls. In ____Hrs. ___Grav. ___GOR _____

Bas: _____MCFPD; Test thru (Orifice or Meter): _____Meter

 Mid-Test Shut-In Pressure Data

 Upper Completion
 Hour, Date, Shut-In
 Length of Time Shut-In
 SI Press. Psig
 Stabilized? (Yes or No)

 Lower Lower Completion
 Hour, Date, Shut-In
 Length of Time Shut-In
 SI Press. Psig
 Stabilized? (Yes or No)

 Completion
 Completion
 SI Press. Psig
 Stabilized? (Yes or No)

(Continue on reverse side)

Flow Test No. 2

			Flow Test N			
Commenced a	at (hour, date)**	1	$\mathbf{z} \leftarrow \mathbf{z} \cdot \mathbf{z}$	ne producing (U		
Time (Hour, Date)	Lapsed Time Since**		essure Lower Compl.	Prod. Zone Temp.		
						1. "
					1,0	
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		- All the second			
					*	
						1. 2
			and the second second			
roduction rate of	during testBOPD based		Bbls. Inice or Meter):	Hrs	Grav.	GOR
emarks:	<u> </u>); rest intu (Om	ice or Meter):			<u>.</u>
			ed is true and comp	lete to the best o	f my knowledge.	
pproved	MAR 3 1 2 Conservation Di	005 vision				duction
- Chal	7	1 1 4			of Text	
,	RVISOR DISTRIC		**	E-mail Addres		
}-			in a second of the second of t	Date	10.06	

- Northwest New Mexico Packer Leakage Test Instructions
- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).