This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## NEW MEXICO OIL CONSERVATION DIVISION

Page 1

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST

Revised June 10, 2003

Operator Williams Exploration and Production Lease Name Rosa Unit

No. 165C]

Location Of Well: Unit Letter G Sec 25 Twp 31N Rge 06W

API # 30-0 300392696100

	Name of Reservoir or Pool	Type of Prod. (Oil or Gas)	Method of Prod. (Flow or Art. Lift)	Prod. Medium (Tbg. Or Csg.)
Upper Completion	mv	Gaz	Flow	TRG
Lower Completion	24	<u> </u>	FLOW	TBG

**Pre-Flow Shut-In Pressure Data** 

		110	11011 0444 444 444		
Upper	Hour, Date, Shut-In		Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion		3-05	4 200	T1920194_	
Lower	Hour, Date, Shut-In		Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)
Completion	1140	3-3-05	470	T SIO	
Compidation	11-10				

Flow Test No. I								
Commend	ed at (hour, date)*	140 3	-7-05	Zone	producing (Up	oper or Lower):		
Time			essure		Prod. Zone	Remarks		
(Hour, Da	te) Since*	Upper Compl.	Lower Com	pl.	Temp.			
1140 3	-8 1 DAG	T 194 C 197	T 100		70			
	-9 2 Days	7 201	7 108	3	72	78793031V72		
1140 3-		T 204 C 207	7 135	2	74	MAR 2005		
1(40 3		7 209 C 213	T 110		75	E or other I		
				;				
						COUSINI SIZILI		

Production rate during test

Dil:BOPD based on	Bbls. In	Hrs	Grav	GOR
-------------------	----------	-----	------	-----

Mid-Test Shut-In Pressure Data

IMM-168t Dillit-in 1 1688 at 2 at 2							
Upper	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)			
Completion				G. 1111 10 (37 N.)			
Lower	Hour, Date, Shut-In	Length of Time Shut-In	SI Press. Psig	Stabilized? (Yes or No)			
Completion							

(Continue on reverse side)

			Flow 1est	······			
	at (hour, date)**		Z	one producing (U	pper or Lower)	<u> </u>	i.
Time (Hour, Date)	Lapsed Time Since**		essure Lower Compl	Prod. Zone	Remarks	r s s in the	: , ,
(Flour, Dute)	Since	Оррег сопрт.	Lower compi.	1 Cilip.	1 1 1 1 2		
- <del></del>		1" (,,) 4	11 (1174)		2( <u>2</u> j.	<u> </u>	<u>. ,                                   </u>
				<u> </u>			
		, , , , , , , , , , , , , , , , , , ,	, (				
F							*
	,	,	<u>.</u>				:
	,	, -					
)il: Jas:	BOPD based MCFPI	onOrif	Bbls. In	Hrs	Grav	GOR'	1.04
Remarks:		ــــــــــــــــــــــــــــــــــــــ		4·		f	-
					_		
hereby certify	that the informati	on herein contair	ed is true and con	nplete to the best	of my knowled	ge.(abb. ami - o	
Approved	MAR 3 1	2005	20	Operator 🔱	Mans 8	9x2 8 000	
lew Mexico Oi	l Conservation D	ivision		7'			Types ()
y Chah	J				BEEVERS		-
y Man	OUDERWOOD			Title <u>So</u>	PROD TECH	· · · · · · · · · · · · · · · · · · ·	
itle	SUPERVISOR D	DISTRICT #3		E-mail Addre	ع <u>ع ما ألو ون</u>	ses @ Williams	Com
	- y -			Date 3	-11-05		•
	•	Northwest	New Mexico Packer Le				

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.' 9 12 .

11 - 12 Sign & C

- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in case of a gas well and 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.

- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same. as for Flow Test No. 1 except that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hour tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

,24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges. the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 11-16-98, with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).