Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

HOBBS OCD

OCD-Hobbs FORM APPROVED OMB NO 1004-0135 Expires July 31, 2010

5	Lease Serial No
	NMLC059576

NMLC059576	

SUNDRY Do not use thi abandoned wel	NMLC059576 6. If Indian, Allottee or Tribe Name					
SURMIT IN TRI	PLICATE - Other instruc	tions on reve	RECEN	<u>/ED</u>	7 If Unit or CA/Agree	ment, Name and/or No.
·						
I Type of Well ☐ Oil Well ☐ Gas Well ☑ Oth			8 Well Name and No. MALJAMAR GB U	N 12		
2 Name of Operator	Contact	LAHAN		9 API Well No.	0.64	
SANDRIDGE EXPL & PROD	LLC E-Mail: tcallahan@		(include area coo	10)	30-025-00445-0	<u> </u>
3a. Address 123 ROBERT S KERR AVENI OKLAHOMA CITY, OK 73102	Ph: 281-840			10 Field and Pool, or Exploratory MALJAMAR Grayburg SA		
4 Location of Well (Footage, Sec., T	1	1)			11 County or Parish, a	
Sec 3 T17S R32E SWSE 660	FSL 1905FEL				LEA COUNTY, I	VM /
(<u> </u>	
12. CHECK APPI	ROPRIATE BOX(ES) TO) INDICATE	NATURE OF	NOTICE, R	EPORT, OR OTHE	R DATA
TYPE OF SUBMISSION		TYPE	OF ACTION			
Notice of Intent	Acidize	□ Deep	en	□ Produc	ction (Start/Resume)	☐ Water Shut-Off
Notice of Intent	☐ Alter Casing	□ Fract	ure Treat	□ Reclan	nation	□ Well Integrity
Subsequent Report	☐ Casing Repair	_	Construction	□ Recom	=	Other
☐ Final Abandonment Notice	Change Plans	_	and Abandon	_	orarily Abandon	
13 Describe Proposed or Completed Op	Convert to Injection	□ Plug		□ Water		
Attach the Bond under which the wo following completion of the involved testing has been completed. Final Aldetermined that the site is ready for f	l operations If the operation re bandonment Notices shall be file	sults in a multiple led only after all r RE (e completion or re	rion A	a new interval, a Form 316	and the operator has ng of the well bore. s retained until
9/13/11 - RU. DRLG OUT CE UNIT. CIRC HOLE W/ SALT OF TBG. SWINFN.	ELLAR, ND WH, NO TUB GEL. SPOTTED 25 SXS	ING, NU BOP CLASS "C" N	. RIH, TAGED IEAT CEMEN	CIBP @ 3,9 T FR 3659'-3	37' RU CEMENT 3937' POH W/ 2,000	ŗ
9/14/11 - RIH, TAGGED PLU 3,249' - 3,490'. POH, STOOE 2,300'. WOC. SQZD 60 SXS) BÁCK 2,703' OF TBG, l	∟D REST. PE	RF @ 2,703'.	RIH W/ 5-1/	2" PKR TO	M
9/15/11 - RIH W/ WL, TAGGE	ED PLUG @ 2,553'. POF	I. WO ORDEI	RS FROM BLI	M. PRESS L	JP ON PLUG; HELD (600
14. Thereby certify that the foregoing is	Electronic Submission #	GE EXPL & PR	OD LLC, sent	to the Hobbs		
Name (Printed/Typed) TERRY B	CALLAHAN		Title REGU	JLATORY SI	PECIALIST III	
Signature (Electronic	Submission)		Date 09/22	/2011		
Signature (Electronic)	THIS SPACE FO	OR FEDERA			ISF	
	0 ((((((((((((((((((((((((((((((((((((· .	
Approved By ACCEP I	TitleSUPER	A AMOS VISOR EPS		Date 10/15/201		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	untable table to those rights in the	e subject lease	Office Hobbs			
Title 18 U S C Section 1001 and Title 43 States any false, fictitious or fraudulent					make to any department of	r agency of the United

Additional data for EC transaction #118246 that would not fit on the form

32. Additional remarks, continued

PSI. PERF @ 2,547' TRIED TO EST INJECTION RATE, PRESSURED UP 1500 PSI. PERF @ 2,523' TRIED TO EST INJECTION RATE, PRESS UP TO 1500 PSI. WOO FROM BLM. POOH, LD PKR. RIH OPEN ENDED TO 2,553'. SPOTTED 25 SXS CLASS "C" NEAT CEMENT FR 2312' TO 2553' POOH STOOD BACK 1100' TBG, LD THE REST. RIH W/ 5-1/2: PKR TO 1100'. WOC. RIH W/ WL, TAGGED PLUG @ 2280'. PERF @ 1,465'. SQZD 80 SXS CLASS "C" NEAT CEMENT, DISPL CMT TO 1,294'. SIWFN.

9/16/11 - SAFETY MTG. RIH W/ WL, TAGGED PLUG @ 1,261'. POH. LD TBG. ND BOP. PERF @ 150'. FLANGED UP WH. SQZD 65 SXS CLASS "C" NEAT CEMENT TO SURFACE. RD AND CLEANED LOCATION. SHUT DOWN.