Submit 3 Copies To Appropriate Pulling SOCD)  State of New Mexico	Form C-103
Office District I Energy, Minerals and Natural Resources	June 19, 2008
1625 N French Dr., Hobbs, NM 88240	WELL API NO. 30-25-29780
District II OIL CONSERVATION DEVISION 1301 W. Grand Ave, Artesia, NM 88210	5. Indicate Type of Lease
District III 1 000 Rto Brazos Rd., Aztec, NM 8741.0 District IV 1220 South St. Francis Dr. Santa Fe, NM 87505	STATE STATE FEE
	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505	VO-5232
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH	Cherry State
PROPOSALS.)	8. Well Number 1
1. Type of Well: Oil Well Gas Well Other	9. OGRID Number
Mack Energy Corporation	013837
3. Address of Operator	10. Pool Name or Wildcat
P.O. Box 960 Artesia, NM 88210	Anderson Ranch; Wolfcamp, West
4. Well Location	662 feet from the West line
Unit Letter E 1982 feet from the North line and Section 9 Township 16S Range 32E	<del></del>
Section 9 Township 16S Range 32E  11. Elevation (Show whether DR, RKB, RT, GR etc.)	11111111
4345' GR	, v
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: 10 MINISTER   SUBSEQUENT REPORT OF:	
NOTICE OF INTENTION TO: SUB-PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR	
TEMPORARILY ABANDON - CHANGE PLANS RV/ 105 COMMENCE DRI	
PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEMEN	T JOB
DOWNHOLE COMMINGLE .	The same of the sa
OTHER:	п
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion	
or recompletion.	and the second s
10/19/2011 Set CIBP @ 8850'. 10/20/2011 Pump 15sx cement plug on top CIBP. Circulate hole w/salt gel. Set 25sx Class H cement plug @-7680'-7382'. Set 25sx	
Class H cement plug @ 5705'-5448'. Perforate @ 4450'. Tried pumping into perfs, wouldn't pump into. RIH open ended w/tbg.	
Set 45sx Class C w/3% CaCl cement plug @ 4500'-4090'. WOC and tagged @ 4049'. Set 30sx Class C Cement w/2% CaCl @	
2515'-2258'. Pull up the hole & SD.	
10/21/2011 RIH & tagged cement @ 2215'. Set 50sx Class C w/3% CaCl @ 1420'-90	
w/3% CaCl @ 575'-318'. WOC & tagged @ 315'. Circulate hole w/cement @ 60' to s	
Approved for plugging of well bore onl Liability under road is retained pendir	
of C-103 (Subsequent Act) Web Page which may be found at OCD Web Page Forms, www.cmnrd.state.nm.us/ocd.	
Forms, www.	
Snud Date: Rig Release Date:	
12/7/2010 Rig Release Bate.	1/7/2011
I hereby certify that the information above is true slid complete to the best of my knowledge and belief.	
SIGNATURE Very W. Sherrell TITLE Production Clerk	DATE 10/26/11
and the state of t	
Type or print name Jerry W. Sherrell E-mail address: jerrys@mec.com	PHONE: (575)748-1288
For State Use Only	
APPROVED BY: DATE/0-27-2011	
Conditions of Approval (if any):	/