Office	Copies To Appropriate District	State of New Mex		Form C-103
District I		Energy, Minerals and Natur	al Resources	May 27/2004
1625 N. Er.	ench Dr., Hobbs, NM 88240		V	WELL API NO.
District II	HOBBS OCH	OIL CONSERVATION	DIVISION	30-025-27400
District III	irand Ave , Artesia, NW 88210	1220 South St. France	1	5. Indicate Type of Lease
1000 Rio B	Brazos Rd , Aztec, NM 87410 2011		-	STATE FEE
District IV	11/1 0 -	Santa Fe, NM 87	505	6. State Oil & Gas Lease No.
	Francis Dr., Santa Fe, NM			
87505	CLUIDDWACEWED	AND DEDODITE ON WELLS		7 Langa Nama an Unit Agramant Nama
(DO NOT)	SUNDR <b>PRODUCTION</b>	S AND REPORTS ON WELLS S TO DRILL OR TO DEEPEN OR PLU	C DACK TO A	7. Lease Name or Unit Agreement Name
		ON FOR PERMIT" (FORM C-101) FOR	S STICES	Lea St.
PROPOSA		ion for Elam (Forme 101) for	. soon	8. Well Number
1. Type	of Well: Oil Well Gas	s Well 🗌 Other 🛛 SWI		001
	e of Operator			O. OGRID Number
	asic Energy Services			246368
	ess of Operator	1.00.00	1	10. Pool name or Wildcat
	O. Box 10460 Midland, TX	79702		San Andres SWD
				- Committee of the comm
4. Well				
	Unit Letter <u>B</u> : <u>660</u>	feet from the North lin	e and <u>1650</u> fee	et from the <u>East</u> line
	Section 17 Township	23-S Range 37-	E NMPM	County Lea
		1. Elevation (Show whether DR,		
				The second second second second second second
Dit or Polos	w-grade Tank Application 🔲 or Cl			
Pit or Belov				
Pit type	Depth to Groundwater_	Distance from nearest fresh wat	er well Distance fr	om nearest surface waterN/A
Pit Liner T	hickness: mil Be	elow-Grade Tank: Volume	bbls; Construct	ion Material
L			CNT	0.1 D
-	12. Check App	propriate Box to Indicate Na	iture of Notice, R	eport or Other Data
	NOTICE OF INT	ENTION TO:	OUD	OF OUT DEPORT OF
	NOTICE OF INTE			SEQUENT REPORT OF:
PERFOR	RM REMEDIAL WORK 📗 🧗 F	PLUG AND ABANDON 📙	REMEDIAL WORK	ALTERING CASING
TEMPOR	RARILY ABANDON 🔲 🤇	CHANGE PLANS 🗀	COMMENCE DRIL	.LING OPNS.□ P AND A 🖊 🛛
PULL OF	RALTER CASING	MULTIPLE COMPL	CASING/CEMENT	JOB 🗆 _ , _ , _ // _ ::_
			OTHER:	, , , , , , , , , , , , , , , , , , ,
OTUED"			I (IIHER'	
	drill out & add Plugs			
13. L	Describe proposed or complete	d operations. (Clearly state all p	ertinent details, and g	give pertinent dates, including estimated date
13. E	Describe proposed or complete of starting any proposed work)	d operations. (Clearly state all p	ertinent details, and g	give pertinent dates; including estimated date ch wellbore diagram of proposed completion
13. E	Describe proposed or complete	d operations. (Clearly state all p	ertinent details, and g	
13. E	Describe proposed or complete of starting any proposed work)	d operations. (Clearly state all p	ertinent details, and g	
13. E	Describe proposed or complete of starting any proposed work)	d operations. (Clearly state all p	ertinent details, and g	
13. E	Describe proposed or complete of starting any proposed work) or recompletion.	d operations. (Clearly state all p	ertinent details, and g	ch wellbore diagram of proposed completion
13. E o o 10/6/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU	d operations. (Clearly state all p. SEE RULE 1103. For Multiple	ertinent details, and g	Approved for plugging of well bore only.
13. E	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077'	ertinent details, and g	Approved for plugging of well bore only. Liability under bond is retained pending receipt
13. E o o 10/6/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077'	ertinent details, and g	Approved for plugging of well bore only.  Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging)
13. E o o 10/6/11 10/7/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt
13. E o o 10/6/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E o o 10/6/11 10/7/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E o o 10/6/11 10/7/11 10/10/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  ) – Re-spot 25sx cmt w/ 3% Caecmt	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E o o 10/6/11 10/7/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/ 3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E o o 10/6/11 10/7/11 10/10/11	Describe-proposed or complete of starting any proposed work). or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag), PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to @ 1,788' – Spot 80sx cmt –	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/ 3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061'	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E o o 10/6/11 10/7/11 10/10/11	Describe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to	d operations. (Clearly state all p. SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/ 3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061'	ertinent details, and ge Completions: Attac	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11	Pescribe-proposed or complete of starting any proposed work). or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH t @ 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cm	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  - Re-spot 25sx cmt w/3% Caecmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061' nt	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900°	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
13. E o o 10/6/11 10/7/11 10/10/11	Pescribe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cm	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  - Re-spot 25sx cmt w/3% Caecmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061' nt	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900°	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11	Pescribe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cm	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  - Re-spot 25sx cmt w/3% Caecmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061' nt	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900°	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state/min.us/ocd.
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11	Pescribe-proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cm	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  - Re-spot 25sx cmt w/3% Caecmt  o 2,500' - Spot 70sx cmt - Tag - Tag @ 1,061' nt	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900°	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp  RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH t @ 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cm  Tag @ 60'. Spot 6sx cmt to	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  O Re-spot 25sx cmt w/3% Caccmt  O 2,500' - Spot 70sx cmt - Tag  Tag @ 1,061'  nt  o surface. RDMO. Clean location	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900'  @ 1,788'	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E o o 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11	Pescribe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the starting of the starting o	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  O Re-spot 25sx cmt w/3% Caccmt  O 2,500' - Spot 70sx cmt - Tag  Tag @ 1,061'  nt  o surface. RDMO. Clean location of the surface of the beside of the surface.	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900'  @ 1,788'  on. Cut off wellhead st of my knowledge a	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E o o 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11	Pescribe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the starting of the starting o	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  O Re-spot 25sx cmt w/3% Caccmt  O 2,500' - Spot 70sx cmt - Tag  Tag @ 1,061'  nt  o surface. RDMO. Clean location of the surface of the beside of the surface.	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900'  @ 1,788'  on. Cut off wellhead st of my knowledge a	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E o o 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11	Pescribe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the starting of the starting o	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  O Re-spot 25sx cmt w/3% Caccmt  O 2,500' - Spot 70sx cmt - Tag  Tag @ 1,061'  nt  o surface. RDMO. Clean location of the surface of the beside of the surface.	ertinent details, and ge Completions: Attace Completions: Attace CI – Tag @ 3,900'  @ 1,788'  on. Cut off wellhead st of my knowledge a	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E o o 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag, PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the specific or closs.	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  Description = Re-spot 25sx cmt w/3% Calculated to 2,500' - Spot 70sx cmt - Tag	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI - Tag @ 3,900'  @ 1,788'  on. Cut off wellhead st of my knowledge a general permit  or	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/12/11 I hereby c grade tank i	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag, PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the specific or closs.	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  Description = Re-spot 25sx cmt w/3% Calculated to 2,500' - Spot 70sx cmt - Tag	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI - Tag @ 3,900'  @ 1,788'  on. Cut off wellhead st of my knowledge a general permit  or	Approved for plugging of well bore only.  Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emhrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank I	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag, PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the specific property of the specific property of the specific property of the specific property of the starting and specific property of the starting a	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  — Re-spot 25sx cmt w/3% Cae cmt  o 2,500' — Spot 70sx cmt — Tag Tag @ 1,061' nt o surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-ran (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby of grade tank I SIGNATU Type or pi	Pescribe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH t @ 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the specific property of the specific property of the specific property of the specific property of the starting of the starting of the specific property of the starting	d operations. (Clearly state all p. SEE RULE 1103. For Multiple of the down @ 3,077' of 25sx cmt  Description = Re-spot 25sx cmt w/3% Calculated to 2,500' - Spot 70sx cmt - Tag	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only.  Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emhrd.state.nm.us/oed.  and anchors. Install P&A marker.
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby of grade tank I SIGNATU Type or pi	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag, PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400'. Spot 6sx cmt to ertify that the information about the specific property of the specific property of the specific property of the specific property of the starting and specific property of the starting a	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  — Re-spot 25sx cmt w/3% Cae cmt  o 2,500' — Spot 70sx cmt — Tag Tag @ 1,061' nt o surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-ran (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank t SIGNATU Type or pr For State	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400' – Spot 6sx cmt to ertify that the information about the bean will be constructed or closs  JRE  Tint name: Greg Bryant  Use Only	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag Tag @ 1,061' nt surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines   TITLE P&A Telegraphics  E-mail address:	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emard.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-an (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11  Telephone No. 432-563-3355
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank t SIGNATU Type or pr For State APPROVI	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400' – Spot 6sx cmt to ertify that the information about the seen/will be constructed or closed JRE  Tint name: Greg Bryant  Use Only  ED BY	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  — Re-spot 25sx cmt w/3% Cae cmt  o 2,500' — Spot 70sx cmt — Tag Tag @ 1,061' nt o surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-ran (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank t SIGNATU Type or pr For State APPROVI	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400' – Spot 6sx cmt to ertify that the information about the bean will be constructed or closs  JRE  Tint name: Greg Bryant  Use Only	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag Tag @ 1,061' nt surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines   TITLE P&A Telegraphics  E-mail address:	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emard.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-an (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11  Telephone No. 432-563-3355
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank t SIGNATU Type or pr For State APPROVI	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400' – Spot 6sx cmt to ertify that the information about the seen/will be constructed or closed JRE  Tint name: Greg Bryant  Use Only  ED BY	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag Tag @ 1,061' nt surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines   TITLE P&A Telegraphics  E-mail address:	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emard.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-an (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11  Telephone No. 432-563-3355
13. E 0 0 10/6/11 10/7/11 10/10/11 10/11/11 10/11/11 I hereby c grade tank t SIGNATU Type or pr For State APPROVI	Describe proposed or complete of starting any proposed work) or recompletion.  MIRU  RIH WL w/ gauge ring – se RIH o.e. Tbg to 4,124' – Sp RIH Tbg to 4,124' (no Tag) PUH to 3,600' – Spot 60sx  Tag TOC @ 3,058'. PUH to 1,788' – Spot 80sx cmt – PUH to 400' – Spot 40sx cmt – PUH to 400' – Spot 6sx cmt to ertify that the information about the seen/will be constructed or closed JRE  Tint name: Greg Bryant  Use Only  ED BY	d operations. (Clearly state all p SEE RULE 1103. For Multiple t down @ 3,077' ot 25sx cmt  - Re-spot 25sx cmt w/3% Cae cmt  o 2,500' - Spot 70sx cmt - Tag Tag @ 1,061' nt surface. RDMO. Clean location ve is true and complete to the beed according to NMOCD guidelines   TITLE P&A Telegraphics  E-mail address:	ertinent details, and ge Completions: Attace Completions: Attace Completions: Attace CI – Tag @ 3,900°  @ 1,788°  on. Cut off wellhead complete com	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emard.state.nm.us/oed.  and anchors. Install P&A marker.  and belief. I further certify that any pit or below-an (attached) alternative OCD-approved plan :  ic Energy Services) DATE 10-18-11  Telephone No. 432-563-3355