

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTNew Mexico Oil Conservation Division, District I
1625 N. French Drive
Hobbs, NM 88240
SUBMIT IN DUPLICATE
(See other instructions on reverse side)FORM APPROVED
OMB NO. 1004-0137
Expires: February 28, 1995
5. LEASE DESIGNATION AND SERIAL NO.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:		OIL WELL ☒	GAS WELL ☐	DRY ☐	Other ☐		
b. TYPE OF COMPLETION:		NEW WELL ☐	WORK OVER ☐	DEEP-EN ☐	PLUG BACK ☒	DIFF. RESVR. ☐	Other ☐
2. NAME OF OPERATOR MARBOB ENERGY CORPORATION						6. IF INDIAN, ALLOTTEE OR TRIBE NAME NMNM17435A	
3. ADDRESS AND TELEPHONE NO. PO BOX 227, ARTESIA, NM 88211-0227 (505) 748-3303						7. UNIT AGREEMENT NAME NMNM107682	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements) At surface 860 FNL 660 FEL, UNIT A						8. FARM OR LEASE NAME, WELL NO. EGL FEDERAL COM #1	
At top prod. interval reported below SAME						9. API WELL NO. 30-025-35690	
At total depth SAME						10. FIELD AND POOL, OR WILDCAT LUSK; WOLFCAMP, NORTH	
14. PERMIT NO.						12. COUNTY OR PARISH	
DATE ISSUED						13. STATE LEA NM	
15. DATE SPURRED		16. DATE T.D. REACHED		17. DATE COMPL. (Ready to prod.)		18. ELEVATIONS (DF, RKB, RT, GE, ETC.)*	
10/1/01		11/9/01		2/23/05		3697' GL	
20. TOTAL DEPTH, MD & TVD		21. PLUG, BACK T.D., MD & TVD		22. IF MULTIPLE COMPL., HOW MANY*		23. INTERVALS DRILLED BY	
12825'		11350'				ROTARY TOOLS 0 - 12825'	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* 10279' - 10482' WOLFCAMP						25. WAS DIRECTIONAL SURVEY MADE NO	
26. TYPE ELECTRIC AND OTHER LOGS RUN NONE						27. WAS WELL CORED NO	
28. EXISTING CASING RECORD (Report all strings set in well)							
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED		
13 3/8" H40	48#	1110'	17 1/2"	950 SX, CIRC	NONE		
8 5/8" J55	32#	4500'	12 1/4"	1990 SX, CIRC	NONE		
5 1/2" P110	17#	12820'	7 7/8"	1760 SX, CIRC	NONE		
29. LINER RECORD						30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 7/8"	10546'	
31. PERFORATION RECORD (Interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
11392' - 11618' (19 SHOTS) CIBP @ 11350				DEPTH INTERVAL (MD)			
10279' - 10482' (10 SHOTS)				11392'-11618'			
				10279'-10482'			
				AMOUNT AND KIND OF MATERIAL USED			
				ACDZ W/ 3000 GAL 15% NEFE HCL			
				ACDZ W/ 3000 GAL 15% NEFE HCL			
33. PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump)				WELL STATUS (Producing or shut-in)	
2/27/05		PUMPING				PROD	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL--BBL.	GAS--MCF.	WATER--BBL.	GAS-OIL RATIO
3/2/05	24					40	
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL--BBL.	GAS--MCF.	WATER--BBL.	OIL GRAVITY-API (CORR.)	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)						TEST WITNESSED BY	
SOLD						LENDELL HAWKINS	
35. LIST OF ATTACHMENTS NONE							
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records							
SIGNED		TITLE				DATE	
[Signature]		PRODUCTION ANALYST				3/8/05	

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

37. SUMMARY OF POROUS ZONES: (State all important zones of porosity and contents thereof; cored intervals; and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
-----------	-----	--------	-----------------------------

38. GEOLOGICAL MARKERS			
NAME	TOP		TRUE VERT. DEPTH
	MEAS. DEPTH		
YATES	3006'		
QUEEN	3704'		
GRAYBURG	4174'		
DELAWARE	4514'		
BONE SPRINGS	6840'		
WOLFCAMP	10480' 10140		
STRAWN	11266'		
ATOKA	11708'		
MORROW	12343'		
LOWER MORROW	12577'		

38. GEOLOGICAL MARKERS			
NAME	TOP		TRUE VERT. DEPTH
	MEAS. DEPTH		