UNITED STATES August 2007) DEPARTMENT OF THE INTERIOR OCD-HOBBS				FORM APPROVED OMB NO. 1004-0137 Expires July 31, 2010 5. Lease Serial No.	
(August 2007) DEPARTMENT OF THE INTERIOR OCD-HOBBS BUREAU OF LAND MANAGEMENT					
A CONSUNDRY NOTICES AND REPORTS ON WELLS			NM 61605		
NOV Do not use this form for pl abandoned well. Use Form				6. If Indian, A	Allottee or Tribe Name
SUBMIT IN TRIPLICATE - Other instructions on page 2 Type of Well Gas Well Gas Well Gas Well Softer Water Injection 2. Name of Operator EOG Resources Inc.				7. If Unit or CA/Agreement, Name and/or NMM91067X 8. Well Name and No. East Corbin 6	
				3a. Address	3b. Phone No. (include a
P.O. Box 2267 Midland, Texas 79702		432-686-3684	432-686-3684		736 I Pool, or Exploratory Area
4. Location of Well (Footage, Sec, T., R., M., or Survey Description)				West Corbin Delaware	
779' FNL & 1943' FWL, U/L C,				11. County or Parish, State	
Sec 21, T18S, R33E					
	DOV(ES) TO DU	NCATE NATURE OF	NOTICE DEDO		
12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPO				UKI, UKUIH	
TYPE OF SUBMISSION TYPE OF ACTION					
Notice of Intent	Acidize	Deepen	Production	n (Start/Resume)	Water Shut-Off
	Alter Casing	Fracture Treat	Reclamati	on	Well Integrity
X Subsequent Report	Casing Repair	New Construction	Recomple	te	X Other
	Change Plans	Plug and Abandon		ly Abandon	Repair
Final Abandonment Notice	Convert to Injectio		Water Dis		Repair
10/07/11 MIRU to lower packer per POOH w/ 2-3/8" IPC tubin 10/12/11 Sent packer in for redru 10/13/11 RIH w/ 2-3/8" IPC tubing	ng and arrowset ess.			r set at 50)83 ' .
Circulate packer fluid.	6	_			
10/21/11 Ran MIT test to 540 psi Returned to injection.	IOT 30 minutes	. Test good. BI	M witnessed.	•	
			A	CCEPTE	D FOR RECO
SEE A	D FOR			/)	
CON	DITIONS C	F APPROVAL		NOV /s/ J[2 2011 D Whitlock Jr
14 Therefore and 6 de actor Company in the		1			LAND MANAGEMENT
 I hereby certify that the foregoing is true and correct Name (Printed/Typed) 		Ti41.	CARLSBAD FIELD OFFICE		
Stan Wagner	· · · · ·	Title Regula	atory Analys	t ,	
Signature theme way		Date 10/27/1	1	<u></u>	
	SPACE FOR FED	ERAL OR STATE OF	FICE USE		
Approved by		Title		Ľ	Date
Conditions of approval, if any, are attached. Approval of this notice the applicant holds legal or equitable file to those rights in the subje entitle the applicant to conduct overalities thereon.		fy that Office			
Title 18 U S C Section 1001, and Title 43 U.S C Section 1212, mal ficturious or fraudulent statements or representations as to any matter	kes it a crime for any per-	son knowingly and willfully to	make to any departm	nent or agency of t	he United States any false,



Conditions of Approval

EOG Resources East Corbin Delaware Unit #6 API 3002530736 November 02, 2011

- Prior BLM approval of a notice of intent (BLM Form 3160-5) is required for fracture treatment of injection wells. The operator will be required to tag fracture material with a tracer and run a tracer survey to verify that the fracture material is not placed out of zone. Results of the tracer to be reported on the workover subsequent sundry Form 3160-5.
- 2. One year after fracture stimulation an injection profile tracer survey is to be run. Submit the survey report to this office in a subsequent sundry Form 3160-5.

General Conditions of Approval: Wells with Packers

- Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
 - a) The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b) Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c) Notify the BLM's Hobbs Field Office in Lea County phone 575-393-3612 at least 24 hours before the test.
 - d) Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e) Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore workover.
 - f) Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2) Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a) Approved injection pressure compliance is required.

•

- b) If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
- c) When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i) Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.

- 3) Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.
- 4) The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
- 5) The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
- 6) **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of beginning injection.
- 7) The operator shall keep monthly records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.
- 8) Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
 - a) Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's Hobbs Field Office in Lea County phone 575-393-3612.
- 9) Also submit to BLM Carlsbad Field Office a (Sundry Form 3160-5) Notice of Intent (NOI) for planned well work involving a formation change, casing repair/replacement, and injection well fracture treatment for approval by BLM and NMOCD. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days. Packer and tubing repair (normal maintance procedures) do not require a NOI, but a subsequent sundry needs to be filed.
- 10) Submit a (Sundry Form 3160-5) subsequent report (daily reports) describing all wellbore activity and Mechanical Integrity Test as per item 1) above. Include the date(s) of the well work, and the setting depths of required equipment: tubing, on/off tool, profile nipple, and packer.

PRS 110211