Office District I	State of New Mexico	Form C-103
Advantage data at the back	Energy, Minerals and Natural Resource	
1625 N Ltench Dr., Hobbs, NM 88240	och/en	WELL API NO 30-025-20460
1301 W. Grand Ave., Artesia, NM 8821	CEINED VATION DIVISION	N 5. Indicate Type of Lease
District III	1220 South St. Francis Dr.	STATE \boxtimes FEE
1000 Rio Brazos Rd Azice NM 87410 District IV	1 4 20 ppta Fe, NM 87505	6 State Oil & Gas Lease No
1220 S. St. Francis Dr., Santa Fe, NM		
87505		
SUNDRY NOUL	SEDEDEDS ON WELLS	7. Lease Name or Unit Agreement Name
 (DO NOT USE THIS FORM FOR PROPOSAL INFERENCE DECEMBER OF ADDITION 	LS TO DRHLL OR TO DEEPEN OR PLUG BACK TO A FION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS)	HOR FOR FERMIN (FORM C-107) FOR 10CH	Humble A O State
	as Well 🔲 Other	8 Well Number 2
2 Name of Operator		9 OGRID Number
Pride Energy Company		151323
3 Address of Operator		10 Pool name or Wildcat
PO Box 701950, Tulsa, OK 74170		Monument, Abo, North
4 Well Location		
Unit Letter N : 660 feet fr	rom the <u>South</u> line and <u>1,920</u> feet fr	om the West line
Section 11	Township 19 S Range 36E	NMPM Lea County
The second s	11 Elevation (Show whether DR, RKB, RT, G	R, etc)
	3,748' GR	
Pit or Below-grade Tank Application] or C	a second a s	
Pit typiDepth to Groundwater	Distance from nearest fresh water well	Distance from nearest surface water
Pit Liner Thickness. mil		
12. Check Ap	propriate Box to Indicate Nature of No	slice, Report or Other Data
NOTICE OF INTE		SUBSEQUENT REPORT OF
	PLUG AND ABANDON 🛛 REMEDIAL	
—	= 1	
PULL OR ALTER CASING		
OTHER		Drilling
	ed operations (Clearly state all pertinent deta	als and give pertinent dates, including estimated date
of starting any proposed work	 SEE RULE 1103 For Multiple Completion 	ns Attach wellbore diagram of proposed completion
of starting any proposed work or recompletion) SEE RULE 1103 For Multiple Completio	ns Attach wellbore diagram of proposed completion
of starting any proposed work or recompletion		ns Attach wellbore diagram of proposed completion
of starting any proposed work		ns Attach wellbore diagram of proposed completion
of starting any proposed work or recompletion) Provide 24-hour notice to NMC	CD	
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drill out or	CD ment plug at surface and proceeding down hole to	next cement plug, encountered junk in the hole which
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out co prevented any further progress. D	CD ement plug at surface and proceeding down hole to becided to abundon re-entry attempt. Had gotten do	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out co prevented any further progress. D 3. Fill the 8 %" casing (Approxim	DCD ement plug at surface and proceeding down hole to becided to abundon re-entry attempt. Had gotten do ately 225' deep) with generic to a few does surf	next cement plug, encountered junk in the hole which
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out co prevented any further progress. D	DCD ement plug at surface and proceeding down hole to becided to abundon re-entry attempt. Had gotten do ately 225' deep) with generic to a few does surf	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drill out or prevented any further progress D 3 Fill the 8 %" casing (Approxim- finish filling hole with cement to	CD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with gravel of the surface	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drill out or prevented any further progress D 3 Fill the 8 %" casing (Approxim- finish filling hole with cement to	CD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with gravel of the surface	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drill out or prevented any further progress D 3 Fill the 8 %" casing (Approxim- finish filling hole with cement to	CD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with gravel of the surface	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then
 of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out co prevented any further progress. D 3. Fill the 8 %" casing (Approximationsh filling hole with cement to 4. Cut off casing & conductor hele 	CD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with gravel of the surface	next cement plug, encountered junk in the hole which wn to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %" casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with gravel of the surface surface low ground level and weld dry hole marker (with n	next cement plug, encountered junk in the hole which white 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then acker information welded onto it) on conductor pipe
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %" casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab-	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with construction to surface low ground level and weld dry hole marker (with n	next cement plug, encountered junk in the hole which white 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then intker information welded onto it) on conductor pipe oveledge and belief. I further certify that any pit or below-
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %," casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab- grade tank has been/will be constructed or glo	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with complete to the best of my know surface low ground level and weld dry hole marker (with n ove is true and complete to the best of my know sed according to NMOCD guidelines [], a general pe	next cement plug, encountered junk in the hole which white 225' from surface. Propose to P & A wellbore ace. (which is above the top of the water table), and then marker information welded onto it) on conductor pipe oveledge and belief. I further certify that any pit or below- rmit \Box or an (attached) alternative OCD-approved plan \Box .
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %," casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab- grade tank has been/will be constructed or glo	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with complete to the best of my know surface low ground level and weld dry hole marker (with n ove is true and complete to the best of my know sed according to NMOCD guidelines [], a general pe	next cement plug, encountered junk in the hole which white 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe owledge and belief. I further certify that any pit or below- rint [] or an (attached) alternative OCD-approved plan [], ride Oil & Gas Co. Inc.
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %," casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab- grade tank has been/will be constructed or glo	DCD ement plug at surface and proceeding down hole to beerded to abundon re-entry attempt. Had gotten do ately 225' deep) with gravel of the transfer of the surface low ground level and weld dry hole marker (with n over is true and complete to the best of my kno seed according to NMOCD guidelines [], a general pe president of Pr	next cement plug, encountered junk in the hole which white 225' from surface. Propose to P & A wellbore ace. (which is above the top of the water table), and then marker information welded onto it) on conductor pipe oveledge and belief. I further certify that any pit or below- rmit \Box or an (attached) alternative OCD-approved plan \Box .
of starting any proposed work or recompletion 1) Provide 24-hour notice to NMC 2. White attempting to driff out or prevented any further progress. D 3: Fill the 8 %" casing (Approxim- finish filling hole with cement to 4: Cut off casing & conductor bel 5: Restore location Thereby certify that the information ab- grade tank has been/will be constructed or clo SIGNATURE.	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n over is true and complete to the best of my king sed according to NMOCD guidelines [], a general pe President of Pr <u>itul</u>	next cement plug, encountered junk in the hole which with to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then intker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rint \Box or an (attached) alternative OCD-approved plan \Box , ide Oil & Gas Co. Inc., ner of Pride Energy Company DATE_11/1011
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %" casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab- grade tank has beeu/will be constructed or do SIGNATURE	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with complete to the part from the surface low ground level and weld dry hole marker (with n over is true and complete to the best of my kno sed according to NMOCD guidelines [], a general pe	next cement plug, encountered junk in the hole which with to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then intker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rint \Box or an (attached) alternative OCD-approved plan \Box , ide Oil & Gas Co. Inc., ner of Pride Energy Company DATE_11/1011
of starting any proposed work or recompletion 1) Provide 24-hour notice to NMC 2. White attempting to driff out or prevented any further progress. D 3: Fill the 8 %" casing (Approxim- finish filling hole with cement to 4: Cut off casing & conductor bel 5: Restore location Thereby certify that the information ab- grade tank has been/will be constructed or clo SIGNATURE.	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rimit [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company DATE_11/1011 gy com Telephone No. (918) 524-9200
of starting any proposed work or recompletion 1. Provide 24-hour notice to NMC 2. White attempting to drill out or prevented any further progress. D 3. Fill the 8 %" casing (Approxim- finish filling hole with cement to 4. Cut off casing & conductor bel 5. Restore location Thereby certify that the information ab- grade tank has beeu/will be constructed or do SIGNATURE	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which with to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then intker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rint \Box or an (attached) alternative OCD-approved plan \Box , ide Oil & Gas Co. Inc., ner of Pride Energy Company DATE_11/1011
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drill out or prevented any further progress D 3 Fill the 8 %" casing (Approxim- finish filling hole with cement to 4 Cut off casing & conductor bel 5 Restore location 1 hereby certify that the information ab- grade tank has been/will be constructed or ele SIGNATURE	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rimit [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company DATE_11/1011 gy com Telephone No. (918) 524-9200
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drift out compresented any further progress. D 3 Fill the 8 %" casing (Approximationsh filling hole with cement to 4 Cut off casing & conductor hele 5 Restore location 1 hereby certify that the information abgrade tank has been/will be constructed or glo SIGNATURE John W. Pride For State Use Only John W. Pride	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rimit [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company DATE_11/1011 gy com Telephone No. (918) 524-9200
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drift out compresented any further progress. D 3 Fill the 8 %" casing (Approximationsh filling hole with cement to 4 Cut off casing & conductor hele 5 Restore location 1 hereby certify that the information abgrade tank has been/will be constructed or glo SIGNATURE John W. Pride For State Use Only John W. Pride	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rimit [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company DATE_11/1011 gy com Telephone No. (918) 524-9200
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drift out compresented any further progress. D 3 Fill the 8 %" casing (Approximationsh filling hole with cement to 4 Cut off casing & conductor hele 5 Restore location 1 hereby certify that the information abgrade tank has been/will be constructed or glo SIGNATURE John W. Pride For State Use Only John W. Pride	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weledge and belief. I further certify that any pit or below- rimit [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company DATE_11/1011 gy com Telephone No. (918) 524-9200
of starting any proposed work or recompletion 1 Provide 24-hour notice to NMC 2 White attempting to drift out compresented any further progress. D 3 Fill the 8 %" casing (Approximationsh filling hole with cement to 4 Cut off casing & conductor hele 5 Restore location 1 hereby certify that the information abgrade tank has been/will be constructed or glo SIGNATURE John W. Pride For State Use Only John W. Pride	DCD ement plug at surface and proceeding down hole to becided to abandon re-entry attempt. Had gotten do ately 225' deep) with graveling to Surface low ground level and weld dry hole marker (with n prove is true and complete to the best of my kind presid according to NMOCD guidelines [], a general per <u>resid according to NMOCD guidelines [], a general per till</u>	next cement plug, encountered junk in the hole which win to 225' from surface. Propose to P & A wellbore ace, (which is above the top of the water table), and then marker information welded onto it) on conductor pipe weldge and belief. I further certify that any pit or below- rint [] or an (attached) alternative OCD-approved plan [], ide Oil & Gas Co., Inc., ner of Pride Energy Company. DATE_11/1011 gy com

•

.

•

,