Form 3160-5 (August 2007)		UNITED DEPARTMENT O	(1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	BS BED	FORM APPROVED OMB No 1004-0137			
	BUREAU OF LAND MANAGEMENOV 1 4 201		1 4 2011	Expires July 31, 2010 5. Lease Serial No.				
	รเ	JNDRY NOTICES AND	REPORTS ON WELL	_S	NMLC-0031741A6. If Indian, Allottee of	or Tribe Name		
		se this form for proposed well. Use Form 316				·		
	SUBMIT IN 1	TRIPLICATE – Other instru	uctions on page 2.		WBDU NM 1200422			
1. Type of Well Gas Well Other					8. Well Name and No. WEST BLINEBRY DRINKARD UNIT 104			
2. Name of Ope	erator	ORPORATION <873>	/		9. API Well No. 30-025-40272			
3. Address 3b. Phone No. (include area Code)					10. Field and Pool or Exploratory Area			
303 VETERANS AIRPARK LN, #3000 MIDLAND, TX 79705 432-818-1117 / 432-818-1198					EUNICE; BLI-TUBB-DRI, NORTH <22900>			
4. Location of Well (Footage, Sec., T., R., M, or Survey Description)					11. County or Parish, State			
1331' FNL & 1330' FEL SEC 8, T21S, R37E, NMPM								
		THE APPROPRIATE BOX(E				R DATA		
TYPE OF SU	BMISSION		T	YPE OF ACTI	ON	Water Shut-Off		
Nótice of Intent		Acidize	Deepen	Product	tion (Start/Resume)	Well Integrity		
Subsequent Re		Alter Casing	Facture Treat	Reclam		DRILLING OPS:		
Final Abandonment Notice		Change Plans	Plug and Abandon	Tempor	arily Abandon	CASING & CEMENT REPORT		
		Convert to Injection	Plug Back		Disposal			
following com testing has been	pletion of the invol n completed Fina t the site is ready fi	he work will be performed or pro lved operations If the operation i Abandonment Notices must be to or final inspection	results in a multiple completion	on or recompleti	on in a new interval, a Form 3	3160-4 must be filed once		
10/6/2011-	SPUD							
10/7/2011	8-5/8" Surfa	ce: Run & set 8-5/8" 2	24# J-55 STC csg @ 13	<u>98'. Cemer</u>	<u>it with:</u>			
Hole	Lead: 450 sx Class C w/2% CaCl, 0.25% CF, 3#/sx LCM-1, 0.005 gps FP-6L, 4% Bentonite (13.5 ppg, 1.75 yld) Comp Strengths: 12 hr - 402 psi 24 hr - 608 psi 72 hr - 1340 psi EPTED FOR RECORD							
5.2l ?	Tail: 300 sx Class C w/1% CaCl, 0.13 #/sx CF, 0.005 gps FP-6L (14.8 ppg, 1.33 yld) Compressive Strengths: 12 hr - 859 psi 24 hr - 1427 psi CIRC 131 sks cement to surface. NOV 5 2011							
10/13/2011 -	- Drl F/6595' - T/7293' TD Rig up Weatherford Loggers							
10/14/2011	- <u>5-1/2"</u> Pro	duction: Run 5-1/2" 17#		<u>7293'.</u>	BUREAU OF	LAND MANAGEMENT		
10/15/2011			s C w/5% NaCL 0 13 #/s	x (F 3 #/sv I				
Hole Size	Lead: 870 sx (50:50) Poz (Fly ash): Class C w/5% NaCl, 0.13 #/sx CF, 3 #/sx LCM-1; 0.5% FL-52, 0.005 gps FP-6L, 10% Bentonite, 0.2% Sodium Metasilicate (11.8 ppg, 2.45 yld) Compressive Strengths: 12 hr - 259 psi 24 hr - 798 psi 72 hr - 1405 psi							
Size			-					
?	6L, 2% Ben	50:50) Poz (Fly ash): Class (tonite, 0.1% Sodium Meta I.3 yld) <i>Compressive Stre</i>	silicate	CF, 0.2% CD-3 24 psi – 1		6 FL-52, 0.005 gps FP-		
· · · · · · · · · · · · · · · · · · ·		nt was circulated to surfac	e. Toc?			0011		
10/15/2011	- RR		·		NO,	1 5 2011		
						1 of 2 10/31/2011 3:01 PM		

14. I hereby certify that the foregoing is true and correct.							
Name (Printed/Typed)							
VICKI BROWN	ìtle	DRILLING TECH	·				
Signature Wilki Broun	Date	10/31/2011					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved by							
	Title		Date				
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conflue operations the confluence operations the conflu	Offic	e					
Title 18 U>S C Section 1001 and Title 43 U S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction							

(Instructions on page 2)

.

6

2 of 2 10/31/2011 1:54 PM

١