

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

HOBBS OCD

NOV 14 2011

FORM APPROVED  
OMB No. 1004-0137  
Expires: July 31, 2010SUDDRY NOTICES AND REPORTS ON WELLS  
Do not use this form proposals to drill or to re-enter an  
abandoned well. Use Form 3160-3 (APD) for such proposals.

RECEIVED

5. Lease Serial No.  
NMNM121475

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No.  
Road Runner Fed Com #19. API Well No.  
30-005-29164

10. Field and Pool or Exploratory Area

Wildcat; Wolfcamp

11. Country or Parish, State

Chaves, NM

1. Type of Well

☐ Oil Well☒ Gas Well☐ Other

2. Name of Operator

Mack Energy Corporation

3a. Address

P.O. Box 960 Artesia, NM 88210-0960

3b. Phone No. (Include area code)

(575) 748-1288

4. Location of Well (Footage, Sec., T,R,M, or Survey Description)

2285 FNL. &amp; 330 FEL, Sec 24 T15S R30E

## 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recomplate in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Mack Energy proposes to P&amp;A as follows.

- 1) Set 135sx plug from 9000-8730' cover from TD to to Wolfcamp @ 8788'. WOC & tag.
- 2) Set 55sx plug from 7330-7230' cover top of Abo @ 7280'. WOC & tag.
- 3) Set 45sx plug from 5400-5300' cover top of Glorieta @ 5350'. WOC & tag.
- 4) Set 180sx plug from 3837-3410' cover San Andres and Grayburg @ 3787' and 3460'. WOC & tag.
- 5) Set 45sx plug from 2310-2210' cover Base of Salt @ 2260'. WOC & tag.
- 6) Set 45sx plug from 1422-1322' cover Top of Salt. WOC & tag.
- 7) Set 200sx plug from 490-0' cover 9 5/8 casing shoe @ 445'. To Surface W/ Monument Per Stipulation No. 6 Attached

Note: Circ. well with salt gel mud consisting of at least 9.5# Brine with 25 pounds of gel per barrel after the bottom plug is set.

RECEIVED

MAY 20 2011

APPROVED FOR 1 MONTH PERIOD  
ENDING JUN 20 2011

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Jerry W. Sherrill

Title Production Clerk

Signature

*Jerry W. Sherrill*

Date 5/20/11

VERBAL

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

*David P. Glass*

Title PETROLEUM ENGINEER

Date MAY 20 2011

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for my person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

SCANNED

NOV 17 2011

Mack Energy Corporation  
Road Runner Fed Com #1 30-006-29164


Before



9 5/8 casing @ 445'  
cmt w/470sx, TOC @  
75' ready mix to surf

TO 9000'

After



9 5/8 casing @ 445'  
cmt w/470sx, TOC @  
75' ready mix to surf

TO 9000'

SCANNED

## Road Runner #1 P&A

1. TD – 8730' (covering TD and wolfcamp)  
135sx 16.4ppg 1.05yield class H ~~Tag~~
2. 7330' – 7230' (covering ABO)  
55sx 16.4ppg 1.05yield class H Tag
3. 5400' – 5300' (covering Glorietta)  
45sx 14.8ppg 1.34yield class C Tag
4. 3837' – 3410' (covering San Andres and Grayburg)  
180sx 14.8ppg 1.34yield class C Tag
5. 2310' – 2210' (covering Base Salt)  
45sx 14.8ppg 1.34yield class C TAG-PLUG
6. 1422' – 1322' (covering top salt)  
45sx 14.8ppg 1.34yield class C TAG PLUG
7. 495' – surface (Covering casing shoe and surface plug)  
200sx 14.8ppg 1.34yield Circulate CMT

All plugs figured w/ 35% excess.

SCANNED

## BUREAU OF LAND MANAGEMENT

Roswell Field Office  
2909 West Second Street  
Roswell, New Mexico 88201  
(575) 627-0272

### Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon. **If you are unable to plug the well by the 90<sup>th</sup> day provide the BLM Roswell Field Office, prior to the 90<sup>th</sup> day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action.**

2. Notification: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours call (575) 627-0205 or after office hours call (575) 420-2832. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

6. Monument: Upon abandonment of the well, all casing shall be cut-off at the base of the cellar or 3-feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.

SCANNED