Submit 3 Copies To Appropriate District State of New Mexico	
Occ.	Form C-103
Office District I Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 ARS OCD	WELL API NO.
District II 1301 W Grand Ave , Artesia, NM 88210 OIL CONSERVATION DIVISION	30-025-21351 /
District III 2001 1220 South St. Francis Dr	5. Indicate Type of Lease STATE FEE FEE
1000 RIO Brazos Rd., Aztec, NIVI 8/4110 V 1 Santa Ea NIM 87505	STATE FEE 6. State Oil & Gas Lease No.
District IV 1220 S St Francis Dr, Santa Fe, NM	o. State Oil & Gas Lease No.
87505 DECEIVED	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR	Northeast Drinkard Unit (NEDU)
PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well 🛛 Gas Well 🔲 Other	920
2. Name of Operator	9. OGRID Number
Apache Corporation	873
3. Address of Operator	10. Pool name or Wildcat
303 Veterans Airpark Lane, Ste. 3000, Midland, TX 79705	Eunice, Blinebry-Tubb-Dr, N. (22900)
4. Well Location	
Unit Letter J: 2310 feet from the S line and 1980 feet	from the E line
Section 23 Township 21S Range 37E NMPM	County Lea
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
3368' GR	
Pit or Below-grade Tank Application □ or Closure □	
Pit typeDepth to GroundwaterDistance from nearest fresh water well Distance	from nearest surface waterN/A
Pit Liner Thickness: mil Below-Grade Tank: Volumebbls; Constru	ection Material
12. Check Appropriate Box to Indicate Nature of Notice,	Panart or Other Date
12. Check Appropriate, box to indicate Nature of Notice,	Report of Other Data
NOTICE OF INTENTION TO:	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WOR	
	RILLING OPNS. P AND A
PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMEN	<u> </u>
OTHER: drill out & add Plugs	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and of starting any proposed work). SEE RULE 1103. For Multiple Completions: Att	
of starting any proposed work). SEE ROLE 1103. For Multiple Completions. At	
	ach wellbore diagram of proposed completion
or recompletion.	ach wellbore diagram of proposed completion
	ach wellbore diagram of proposed completion
or recompletion.	ach wellbore diagram of proposed completion
or recompletion.	
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097'	good.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762'	good. Approved for plugging of well bore only.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097'	Approved for plugging of well bore only. Liability under bond is retained pending receipt
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995'	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451'	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451'	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface, RDMO - C + + + + + + + + + + + + + + + + + +	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface, RDMO - C + + + + + + + + + + + + + + + + + +	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface, RDMO - C + + + + + + + + + + + + + + + + + +	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451'	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/oed.
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Io 2 oli Perf @ 200' - Circ 140sx cmt to surface. RDMO. Caf off works continuous con	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. H, anchors, clean
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off works and the complete to the best of my knowledge. I hereby certify that the information above is true and complete to the best of my knowledge.	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. H, anchors, clean
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Io 2 oli Perf @ 200' - Circ 140sx cmt to surface. RDMO. Caf off works continuous con	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. H, anchors, clean
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off we have a complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/oed. H, anchors, clean e and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off we have a complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. H, anchors, clean
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off we have a complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines ☒, a general permit ☐	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/oed. H, anchors, clean e and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan .
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx,cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' /o 2 oli Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off we have a complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines \(\Delta \), a general permit \(\Delta \) SIGNATURE \(\Delta \) TITLE \(\Delta \) & Technician \(\Delta \)	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/ocd. H, anchors, clean e and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan asic Energy Services) DATE 11-2-11
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/MLF. Test csg to 500# - Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 332' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut of work O Cation Install dry hole marker I hereby certify that the information above is true and complete to the best of my knowledge grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit SIGNATURE TITLE P&A Technician (B: Type or print name: Greg Bryant E-mail address: For State Use Only	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.emnrd.state.nm.us/ocd. H, anchors, clean e and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan asic Energy Services) DATE 11-2-11 Telephone No. 432-563-3355
or recompletion. 10/14/11MIRU 10/18/11Tag cmt on existing CIBP @ 6,040' - Circ hole w/ MLF. Test csg to 500#- Spot 55sx cmt @ 5,640' (combine plugs) - disp to 5,097' Spot 25sx cmt @ 4,009' - disp to 3,762' Spot 60sx cmt @ 3,423' - Tag @ 2,995' 10/19/11Spot 110sx cmt @ 2,857' - disp to 2,451' Spot 30sx cmt @ 1,425' - disp to 1,315' Spot 40sx cmt @ 432' - Tag @ 287' Perf @ 200' - Circ 140sx cmt to surface. RDMO. Cut off we have been found to the constructed or closed according to NMOCD guidelines \(\text{M} \), a general permit \(\text{SIGNATURE} \) Title \(\text{P&A Technician} \) E-mail address:	Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd. H, anchors, clean e and belief. I further certify that any pit or belower an (attached) alternative OCD-approved plan asic Energy Services) DATE 11-2-11