

District I - (575) 393-6161  
1625 N French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87424  
District IV - (505) 476-3460  
1220 S St Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.  
Santa Fe, NM 87505

HOBBS OGD  
NOV 17 2011  
RECEIVED

WELL API NO. 30-025-40039
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VB-864
7. Lease Name or Unit Agreement Name Mamba BQN State Com
8. Well Number 1H
9. OGRID Number 025575
10. Pool name or Wildcat Wildcat; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Yates Petroleum Corporation

3. Address of Operator  
105 South Fourth Street, Artesia, NM 88210

4. Well Location  
Unit Letter N : 330 feet from the South line and 1980 feet from the West line  
Unit Letter C : 330 feet from the North line and 1980 feet from the West line  
Section 30 Township 24S Range 33E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3553' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Surface and Intermediate casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/8/11 - Resumed drilling at 12:00 AM. TD 17-1/2" hole to 540' at 10:00 AM. Set 13-3/8" 48# J-55 ST&C casing at 540'. Cemented with 590 sx Class "C" + 0.125#/sx D130 + 94#/sx D903 + 0.2% D46 + 3#/sx D42 + 0.1% D201 + 0.1% D65 (yld 1.36, wt 14.8). Circulated 140 sx to pit. Tested casing to 600 psi for 30 min, Ok. Reduced hole to 12-1/4" and resumed drilling.  
11/13/11 - TD 12-1/4" hole to 4870'. Set 9-5/8" 36#, 40# HCK-55 K-55 J-55 LT&C casing at 4870'. Cemented with 1260 sx Class "C" + 0.125#/sx D130 + 4% D20 + 94#/sx D903 + 0.2% D46 + 3#/sx D42 + 0.2% D201 (yld 1.97, wt 12.9). Tailed in with 360 sx Class "C" + 94#/sx D903 (yld 1.35, wt 14.8). Circulated 185 sx to pit. Tested casing to 1200 psi for 30 min. Reduced hole to 8-3/4" and resumed drilling.

Spud Date:

3/1/11

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE November 16, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: Mark Whitaker TITLE Compliance Officer DATE 11-18-2011

Conditions of Approval (if any):