Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Hobbs HOBBS OCD

FORM APPROVED OMB NO 1004-0135 Expires: July 31, 2010

## Lease Serial No. NMLC059576

SUNDRY NOTICES AND REPORTS ON WELLS

abandoned wel	6. If Indian, Allottee of	6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRI	7 If Unit or CA/Agre	ement, Name and/or No.			
1 Type of Well			8 Well Name and No		
Oil Well Gas Well Oth  Name of Operator LINN OPERATING, INC.		B CALLAHAN	9 API Well No. 30-025-32087	/	
3a Address 600 TRAVIS STREET SUITE HOUSTON, TX 77002	1 3b. Phe	one No (include area code 81-840-4272	e) 10 Field and Pool, or	10 Field and Pool, or Exploratory mali and GRAYBURG SAN ANDRES	
4 Location of Well (Footage, Sec., T	R., M., or Survey Description)		11. County or Parish,	11. County or Parish, and State	
Sec 3 T17S R32E Mer NMP 2 32.861920 N Lat, 103.750650			LEA COUNTY,	NM /	
12. CHECK APPR	ROPRIATE BOX(ES) TO INDIC	CATE NATURE OF 1	NOTICE, REPORT, OR OTHEI	R DATĄ	
TYPE OF SUBMISSION	TYPE OF ACTION				
☐ Notice of Intent	☐ Acidize ☐	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off	
_	☐ Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity	
■ Subsequent Report	☐ Casing Repair	New Construction	Recomplete	Other	
· 🗖 Final Abandonment Notice	☐ Change Plans	Plug and Abandon	Temporarily Abandon	Workover Operation	
	Convert to Injection	Plug Back	☐ Water Disposal		
well to fail a Mechanical Integr replace the equipment as nece pressure loss, LINN will isolate LINN will verbally notify the Re casing remediation work.  SEE ATTACHED  CONDITIONS OI	onto location to identify the source ity Test (MIT). LINN will inspect essary. If the tubing, packer, and the casing leak with a RBP/Pace gulatory Agencies and secure approximately the test of the t	the wellhead, tubing, wellhead are not the ker. Once the leak is	packer and source of isolated.	d had	
14 Thereby certify that the foregoing is	Electronic Submission #118067 v For LINN OPERAT	erified by the BLM We ING, NC., sent to the	II Information System ` Hobbs		
Name (Printed/Typed) TERRY B CALLAHAN		Title REGUL	REGULATORY SPECIALIST III		
Signature (Electronic S	ubmission)	Date 09/21/2	011	-	
	THIS SPACE FOR FED	ERAL OR STATE	OFFICE USE		
Approved By		Title	ACCEPTED FOR	RECORD	
Conditions of approval, if any, are attached Approval of this notice does not warrant or ertify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.		ease Office	NOV 1.1	2011	
Itle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent s	U.S C Section 1212, make it a crime for tatements or representations as to any m	any person knowingly and atter within its jurisdiction	d willfully to make to any department of	agency of the United	

MW/OCD 11-18-2011 CARLSBAD FIELD OFFICE

## **Conditions of Approval: Wells with Packers\***

## Linn Operating, INC Maljamar Grayburg Unit 150 API 3002532087

October 05, 2011

- 1. Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
  - a. The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
  - b. Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
  - c. Notify Paul R. Swartz at 575-234-5985 and/or 575-200-7902 at least 24 hours before the test. If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
  - d. Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
  - e. Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore work.
  - f. Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2. Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
  - a. Approved injection pressure compliance is required.
  - b. If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
  - c. When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
  - i. Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
  - e. Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.

- 3. The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
  - a. The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
  - b. **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of this approval.
  - The operator shall keep monthly records documenting that the casing annulus is fluid filled.
     A suggested format for these records is available from the BLM Carlsbad Field Office.
     Copies of those records shall be furnished at the request of a BLM authorized officer.
  - d. Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
  - a. Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz at 575-200-7902). If there is no response, notify the BLM on call drilling phone, 575-361-2822. In Lea County call 575-393-3612.
  - e. Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for approval by BLM and NMOCD with a detailed plan for correction and the anticipated date of correction. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days.
  - f. After the repairs submit a (Sundry Form 3160-5) Subsequent report, describing the repair(s) and Mechanical Integrity Test as per item 1 above.

<sup>\*</sup>COA's prepared by Paul R. Swartz