Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	October 13, 2009 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 BBS		WELL API NO. 30-025-05217
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	5. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 8000 2 District IV	1 2011 1220 South St. Francis Dr.	STATE FEE X
District IV 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505 PFC	EIVED	
SUNDRY NÖTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A		7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		T D Pope 36
PROPOSALS.) 1. Type of Well: Oil Well ☐ Gas Well ☐ Other		8. Well Number 9
2 Name of Operator		9. OGRID Number
Celero Energy II, LP		247128
3. Address of Operator 400 W. Illinois, Ste. 1601 Midland, TX 79701		10. Pool name or Wildcat
•	X /9/01	Denton; Devonian
4. Well Location Unit Letter C: 660 feet from the North line and 1650 feet from the West line		
* · · · · · · · · · · · · · · · · · · ·		
Section 36	Township 14S Range 37E 11. Elevation (Show whether DR, RKB, RT, GR,	NMPM CountyLea
	3804' GR	
		The state of the s
12. Check A	ppropriate Box to Indicate Nature of Not	ice, Report or Other Data
NOTICE OF INT	TENTION TO:	UBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL V	
TEMPORARILY ABANDON		DRILLING OPNS. P AND A
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEN	
DOWNHOLE COMMINGLE		
	OTUED: D	<u></u>
OTHER:	I I UTHER: Perf	`& acidize X
	eted operations. (Clearly state all pertinent detail	** & acidize X s, and give pertinent dates, including estimated date
13. Describe proposed or comple of starting any proposed wor	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple	s, and give pertinent dates, including estimated date
 Describe proposed or complete of starting any proposed wor proposed completion or reco 	eted operations. (Clearly state all pertinent detail.rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion.	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of
13. Describe proposed or complete of starting any proposed wor proposed completion or reconstruction of the starting and the	eted operations. (Clearly state all pertinent detail.rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10,
13. Describe proposed or complete of starting any proposed wor proposed completion or reconstruction of the starting any proposed completion or reconstruction of the starting and starting are starting as a starting and starting are starting as a starting and starting are starting as a start	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T HSCCG, 0 degree phasing, 2 SPF. Perf as follo	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' -
13. Describe proposed or complete of starting any proposed wor proposed completion or reconstant of the starting any proposed work proposed completion or reconstant of the starting of the st	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T HSCCG, 0 degree phasing, 2 SPF. Perf as follo 24' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286	s, and give pertinent dates, including estimated date completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes.
13. Describe proposed or complete of starting any proposed wor proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T "HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 &	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes.
13. Describe proposed or complete of starting any proposed wor proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the start o	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 24' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the start	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T "HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg.
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the start of the star	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T "HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V,
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the starting and proposed completion or reconstruction of the starting and proposed completion of the starting and starting and starting are starting as a starting and starting are starting and starting and starting and starting are starting and starting and starting are starting and starting are starting and star	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T" HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V,
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the start of the star	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T" HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg -
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the starting and proposed completion or reconstruction of the starting and proposed completion of the starting and starting and starting are starting as a starting and starting are starting and starting and starting and starting are starting and starting and starting are starting and starting are starting and star	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T" HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg -
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the starting and proposed completion or reconstruction of the starting and proposed completion of the starting and starting and starting are starting as a starting and starting are starting and starting and starting and starting are starting and starting and starting are starting and starting are starting and star	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 24' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 so using 11000# 50/50 100 mesh & graded rock sata AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery.	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg -
13. Describe proposed or complete of starting any proposed worth proposed completion or reconstruction of the starting any proposed worth proposed completion or reconstruction of the starting and proposed completion or reconstruction of the starting and starting an	eted operations. (Clearly state all pertinent detail rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. T" HSCCG, 0 degree phasing, 2 SPF. Perf as follo 04' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sa AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg -
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and starting an	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sate and a subject of the series of the seri	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and starting an	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 24' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 so using 11000# 50/50 100 mesh & graded rock sata AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple lows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery.	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and starting an	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sate and a subject of the series of the seri	s, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and starting an	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 & s using 11000# 50/50 100 mesh & graded rock sate and a subject of the series of the seri	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. 2 old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of
13. Describe proposed or completed of starting any proposed work proposed completion or recompleted to 10/25/11 - RIH w/ GR/CCL/CNL, 000' to 9000'. POH. RIH w/ 3 1/8' 12,450' - 32 holes, 12,394' - 12,40 10/27/11 - Pkr set @ 11,920', tail NEFE HCL 5% Xylene in 7 stage w/ 5 1/2" X 2 7/8" Baker Type TA 11/1/11 - PU GE sub pump as foll 46-A, 2) 98L Seals, 1) Mag3 gas s 9277.59', x-over, 1 jt PH-6 tbg. T Smartguard @ 11955.79'. Leave we Spud Date:	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 ses using 11000# 50/50 100 mesh segraded rock safact w/ carbide slips, 2 7/8" X 2.31F Profile Nipple slows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery. Rig Release Date:	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - D PH-6 tbg (2571.86'). Intake @ 11899.10', btm of ledge and belief. DATE 11/17/2011
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and proposed work of 1/25/11 - RIH w/ GR/CCL/CNL, 000' to 9000'. POH. RIH w/ 3 1/8' 12,450' - 32 holes, 12,394' - 12,40 10/27/11 - Pkr set @ 11,920', tail NEFE HCL 5% Xylene in 7 stages w/ 5 1/2" X 2 7/8" Baker Type TA 11/1/11 - PU GE sub pump as foll 46-A, 2) 98L Seals, 1) Mag3 gas s 9277.59', x-over, 1 jt PH-6 tbg. The Smartguard @ 11955.79'. Leave we should be sufficiently starting and	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 24' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 so using 11000# 50/50 100 mesh & graded rock so a AC w/ carbide slips, 2 7/8" X 2.31F Profile Nipple Hows: 1) stainless Smartguard, 2) TR4 456 80 Hp (separator, 3) TD850 pumps - 474 stages, 2 3/8" So TH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery. Rig Release Date:	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - D PH-6 tbg (2571.86'). Intake @ 11899.10', btm of ledge and belief. DATE 11/17/2011
13. Describe proposed or completed of starting any proposed work proposed completion or recompleted to 10/25/11 - RIH w/ GR/CCL/CNL, 000' to 9000'. POH. RIH w/ 3 1/8' 12,450' - 32 holes, 12,394' - 12,40 10/27/11 - Pkr set @ 11,920', tail NEFE HCL 5% Xylene in 7 stage w/ 5 1/2" X 2 7/8" Baker Type TA 11/1/11 - PU GE sub pump as foll 46-A, 2) 98L Seals, 1) Mag3 gas s 9277.59', x-over, 1 jt PH-6 tbg. T Smartguard @ 11955.79'. Leave we Spud Date:	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 ses using 11000# 50/50 100 mesh segraded rock safact w/ carbide slips, 2 7/8" X 2.31F Profile Nipple slows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery. Rig Release Date:	s, and give pertinent dates, including estimated date completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of eledge and belief. DATE 11/17/2011 oenergy.com PHONE: (432)686-1883
13. Describe proposed or completed of starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting any proposed work proposed completion or reconstruction of the starting and proposed work of 1/25/11 - RIH w/ GR/CCL/CNL, 000' to 9000'. POH. RIH w/ 3 1/8' 12,450' - 32 holes, 12,394' - 12,40 10/27/11 - Pkr set @ 11,920', tail NEFE HCL 5% Xylene in 7 stages w/ 5 1/2" X 2 7/8" Baker Type TA 11/1/11 - PU GE sub pump as foll 46-A, 2) 98L Seals, 1) Mag3 gas s 9277.59', x-over, 1 jt PH-6 tbg. The Smartguard @ 11955.79'. Leave we should be sufficiently starting and	eted operations. (Clearly state all pertinent detail. rk). SEE RULE 19.15.7.14 NMAC. For Multiple ompletion. FL @ 8870', correlate to log dated 4-22-1954. To HSCCG, 0 degree phasing, 2 SPF. Perf as follo 194' - 20 holes, 12,318' - 12,330' - 24 holes, 12,286 pipe @ 12,113'. Acdz new perfs 12455 - 12298 ses using 11000# 50/50 100 mesh segraded rock safact w/ carbide slips, 2 7/8" X 2.31F Profile Nipple slows: 1) stainless Smartguard, 2) TR4 456 80 Hp separator, 3) TD850 pumps - 474 stages, 2 3/8" STH w/ 81 jts PH-6, total of 82 jts 2 7/8" 7.9# L-80 well pumping to battery. Rig Release Date:	s, and give pertinent dates, including estimated date c Completions: Attach wellbore diagram of ag @ 12,600', log from 12,600' to 11,900' & 10, ws in 5 runs, 12,455' - 12,462' - 14 holes, 12,434' - ' - 12,298' - 24 holes. c old perfs 12318 - 12620 w/ 22,000 gal 15% lt, flush w/ 178 BFW. POH w/ tbg and pkr. RIH e, T-2 On/Off Tool, 282 jts 2 7/8" tbg. motor, 1310-V, 39-A, re-rated to 100 Hp, 1416-V, .N., x-over, 287 jts 2 7/8" 6.5# L-80 8rd tbg - 0 PH-6 tbg (2571.86'). Intake @ 11899.10', btm of DATE