

New Mexico Oil Conservation Division, District I

Form 3160-5
(August 2007)

HOBBS OCD

UNITED STATES

1625 N. French Drive

Hobbs, NM 88240

FORM APPROVED
OMB No. 1004-0137
Expires July 31, 2010

DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

NOV 21 2011

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE - Other instructions on page 2

1. Type of Well

☐ Oil Well☐ Gas Well☒ Other

Inj.

2. Name of Operator

Celero Energy II, LP

3a. Address

400 W. Illinois, Ste. 1601 Midland TX 79701

3b. Phone No. (include area code)

(432)686-1883

4. Location of Well (Footage, Sec., T, R, M, or Survey Description)

660' FNL & 1979' FEL

(B) Sec 17, T14S, R31E

5. Lease Serial No

NM-03210

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

8. Well Name and No.

West Cap Queen Sand Unit #2

9. API Well No.

30-005-01096

10. Field and Pool or Exploratory Area

Caprock; Queen

11. Country or Parish, State

Chaves, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleat in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

1. Spot 40 sx Class C through current tbq @ 2708'. POOH w/ tbq.

2. RBIH w/ BP & PS on workstring & tag TOC at/above 2608'. Circ salt mud to 1940'. POOH w/ tbq.

3. Perf 4 @ 1940'. RIH w/ pkr & sqz 40 sx. POOH w/ pkr. RIH w/ BP & PS on workstring & tag TOC at/above 1840'.

Circ salt mud to 1010'. POOH w/ tbq.

4. Perf 4 @ 1010'. RIH w/ pkr & sqz 40 sx. POOH w/ pkr. RIH w/ BP & PS workstring & tag TOC at/above 910'. Circ salt mud to 313'.

5. Perf 4 @ 263'. Run tbq to 313' & fill 5 1/2" & 5 1/2" by 8 5/8" to surface w/ 90 sx. POOH w/ tbq.

6. Cut off WH's, set P&A marker, clean & reclaim location.

- All plugs Class C w/ 2% CaC12

- Minimum 9.5 ppg salt mud between all plugs

APPROVED FOR 3 MONTH PERIOD
ENDING FEB 15 2012

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

Lisa Hunt

Title Regulatory Analyst

Signature

Date 10/19/2011

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

/S/ DAVID R. GLASS

Title PETROLEUM ENGINEER

Date

NOV 15 2011

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations hereon.

Office

ROSWELL FIELD OFFICE

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

NOV 22 2011


CELERO ENERGY

FIELD: Caprock
LEASE/UNIT: West Cap Queen Sand Unit
COUNTY: Chaves

DATE: Oct. 18, 2011
BY: MWM
WELL: 2
STATE: New Mexico

Location: 660' FNL & 1980' FEL, Sec 17B, T14S, R31ECM
SPUD: 7/57 COMP: 7/57
CURRENT STATUS: SI-Injector
Original Well Name: Cleat #5

KB = 4099'
GL =
API = 30-005-01096



PBTD - 2729'
TD - 2729'


CELERO ENERGY

FIELD: Caprock
LEASE/UNIT: West Cap Queen Sand Unit
COUNTY: Chaves

DATE: Oct. 17, 2011
BY: MWM
WELL: 2
STATE: New Mexico

Location: 660' FNL & 1980' FEL, Sec 17B, T14S, R31ECM
SPUD: 7/57 COMP: 7/57
CURRENT STATUS: SI-Injector
Original Well Name: Cleat #5

KB = 4099'
GL =
API = 30-005-01096



8-5/8" 22.7# J-55 @ 213' w/225 sx-calc'd TOC at surface

T-Rustler Anhy @ 1010'
T-Yates @ 1940'
R-Queen @ 2694'

TOC @ 2261'-calc'd w/enlargement = 15%; yield = 1.26 ft³/sk

Poor casing 2410'-2708'

5-1/2" 15.5# @ 2708' w/100 sx

Top of Queen @ 2694':

Queen Open Hole: 2708' - 2729' (7-57)

PBTD - 2729'
TD - 2729'

BUREAU OF LAND MANAGEMENT

Roswell Field Office

2909 West Second Street

Roswell, New Mexico 88201

(575) 627-0272

**Permanent Abandonment of Federal Wells
Conditions of Approval**

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within **ninety (90)** days from the approval date of this Notice of Intent to Abandon. **If you are unable to plug the well by the 90th day provide the BLM Roswell Field Office (RFO), prior to the 90th day, with the reason for not meeting the deadline and a date when the BLM Roswell Field Office can expect the well to be plugged. Failure to do so will result in enforcement action. Unless the well has been properly plugged, the rig shall not be removed from over the hole without prior approval.**

2. Notification: Contact the BLM Roswell Field Office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, during office hours or after office hours call (575) 627-0205. Engineer on call during office hours phone (575) 627-0275 or phone (after hours) call (575) 626-5749.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9090 feet; a 3M system for a well not deeper than 13636 feet; and a 5M system for a well not deeper than 22727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at a rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 50 feet of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either class "C" for up to 7500 feet of depth, mixed at 14.8 lbs./gal with 6.3 gallons of fresh water per sack or class "H" for deeper than 7500 feet plugs, mixed at 16.4 lbs./gal with 4.3 gallons of fresh water per sack.

6. Monument: Upon abandonment of the well, all casing shall be cut-off at the base of the cellar or 3-feet below final restored ground level (whichever is deeper). The well bore shall then be covered with a metal plate at least ¼ inch thick and welded in place. The following information shall be permanently inscribed on the dry hole marker: Well name and number, the name of the operator, the lease serial number, the surveyed location (the quarter-quarter section, township and range or other authorized survey designation acceptable to the authorized officer; such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to the BLM Roswell Field Office. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**

Following the submittal and approval of the Subsequent Report of Abandonment, a Notice of Intent for Final Abandonment with the proposed surface restoration procedure must be submitted for approval.