| | · · · · · | |
|---|---|---|
| District 1 1625 N. French Dr., Hobbs, NM 88240 District III 1301 W. Grand Avenue, Attesia, NM 88210 District III 1000 Rto Brazos Road, Aztee, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 | State of New Mexico Energy Minerals and Natural Resources Department Oil Conservation Division | Form C-144 CLEZ July 21, 2008 For closed-loop systems that only use above ground steel tanks or haul-off bins and propose to implement wate removal for closure, submit |
| District JV 1220 S St Trancis Dr., Santa Fe, NM 87505 | 1220 South St. Francis Dr. Santa Fe, NM 87505 | to implement waste removal for closure, submit to the appropriate NMOCD District Office. |
| (that only use above ground steel Instructions: Please submit one application (Form C-1 closed-loop system that only use above ground steel tum | lss or haul-off bins and propose to implement waste | nent waste remoyal for closure) a. For any application request other than for a removal for closure, please submit a Form C-144. |
| Please be advised that approval of this request does not reli environment. Nor does approval relieve the operator of its | eve the operator of liability should operations result responsibility to comply with any other applicable g | in pollution of surface water, ground water or the overnmental authority's rules, regulations or ordinances |
| n. Operator: <u>Cimarex Energy Co. of Colorado</u> | | |
| Address. 600 N Marienfeld St., Ste. 600; Midland, | | |
| Facility or well name. <u>Witherspoon 21 State Com N</u> API Number: <u>30-01-2</u> 40 351 | OCD Permit Number P | -0.3963 |
| U/L or Qtr/Qtr Section Township | 21S Range 33E County: Lea | |
| Center of Proposed Design: Latitude 32° 28'14.64' | | |
| Surface Owner. Dederal State Private Tr | | |
| | | |
| ² X Closed-loop System: Subsection H of 19 15 17 | 11 NMÁC | |
| Operation D'Drilling a new well Workover or D | | pproval of a permit or notice of intent) |
| 🗌 Above Ground Steel Tanks or 🔀 Haul-off Bins | | |
| 3. | | |
| Signs: Subsection C of 19.15.17 11 NMAC | - to be offer and encourse talenhone numbers | |
| ☐ 12"\24", 2" lettering, providing Operator's name, ☑ Signed in compliance with 19 15.3.103 NMAC | site location, and emergency telephone numbers | |
| | | |
| Closed-loop Systems Permit Application Attachme Instructions: Each of the following items must be at attached. Design Plan - based upon the appropriate requir Operating and Maintenance Plan - based upon t | tached to the application. Please indicate, by a comments of 19.15.17.11 NMAC | heck mark in the box, that the documents are |
| Closure Plan (Please complete Box 5) - based u | pon the appropriate requirements of Subsection C | Cof 19.15.17.9 NMAC and 19.15 17.13 NMAC |
| Previously Approved Design (attach copy of design | | |
| Previously Approved Operating and Maintenance 5. | | |
| Waste Removal Closure For Closed-loop Systems 7 Instructions: Please indentify the facility or facilitie. facilities are required. | <u>Fhat Utilize Aboye Ground Steel Tanks or Hau</u> s for the disposal of liquids, drilling fluids and d. | <u>I-off Bins Only</u> : (19.15.17.13.D NMAC) rill cuttings. Use attachment if more than two |
| Disposal Facility Name <u>CRI</u> | Disposal Facility Pe | rmit Number: <u>R-9166</u> |
| Disposal Facility Name. | | mit Number: |
| Will any of the proposed closed-loop system operation Yes (If yes, please provide the information belo | | at will not be used for future service and operations? |
| Required for impacted areas which will not be used for Soil Backfill and Cover Design Specifications - Re-vegetation Plan - based upon the appropriate Site Reclamation Plan - based upon the appropriate | - based upon the appropriate requirements of Sul c requirements of Subsection 1 of 19 15.17.13 NM | IAC |
| 6. | | |
| Operator Application Certification: I hereby certify that the information submitted with the | is application is true, accurate and complete to th | e best of my knowledge and belief. |
| Name (Print) | Title1 | Regulatory Analyst |
| Signature | Date1 | 4 2011 |
| e-mail address tstatten/internates.com | Telepho | ue: <u>432-620-1936</u> |
| Form C-144 CLFZ | Oil Conservation Division | DEC 0 7 2011 Page 1 pf 4 |
| | | DEL U |

| | | ۰ · · · · · · · · · · · · · · · · · · · | |
|--|---|--|--|
| 7. OCD Appro | val: Permit Application (including closure plan) Cl | | |
| OCD Repres | entative Signature: | Approval Date:6/7] | |
| Title: | PETROLEUM ENANCIÓN | DIOZALO | |
| 8. <u>Closure Rep</u> Instructions: The closure 1 | ort (required within 60 days of closure completion): Sul Operators are required to obtain an approved closure pla | n prior to implementing any closure activities and submitting the closure report. lays of the completion of the closure activities. Please do not complete this | |
| | | Closure Completion Date: | |
| Closure Rep Instructions: | ort Regarding Waste Removal Closure For Closed-loop ? | Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: iids, drilling fluids and drill cuttings were disposed. Use attachment if more than | |
| Disposal Fa | icility Name: | Disposal Facility Permit Number. | |
| Disposal Fa | cility Name: | | |
| Were the close | | ed on or in areas that will not be used for future service and operations? | |
| Site Ro | impacted areas which will not be used for future service and eclamation (Photo Documentation) ackfilling and Cover Installation sciation Application Rates and Seeding Technique | | |
| 10. | osure Certification: | | |
| I hereby certi | fy that the information and attachments submitted with this (| closure report is true, accurate and complete to the best of my knowledge and requirements and conditions specified in the approved closure plan | |
| Name (Print) | | Title | |
| Signature. | | Date: | |
| e-mail addres | S | Telephone: | |

Cimarex Energy Co. of Colorado - Closed-Loop System Design Plan

Equipment List

- Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 of 2 Centrifuges (depending on well depth)
- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

Operation and Maintenance

The Cimatex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

<u>Closure Plan</u>

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).

