Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OCD Hobbs HOBBS OCD FORM APPROVED OMB NO 1004-0135 Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS

SUNDRY Do not use th abandoned we	•	RTS ON WELLS drill or to re-enter an EC 1 D) for such proposals		5. Lease Serial No NMNM93 6 If Indian, Allottee of	or Tribe Name	
	PLICATE - Other instruc	tions on reverse side. REC	EIVED	7. If Unit or CA/Agre	ement, Name and/or No	
1. Type of Well Gas Well Ot				8. Well Name and No. CHOLLA 18 FED		
2. Name of Operator EOG RESOURCES INCORP	Contact ORATEDE-Mail. stan_wagn	STAN WAGNER er@eogresources com		9. API Well No 30-025-40257-0	00-X1	
3a Address MIDLAND, TX 79702	3b. Phone No. (include area code) Ph: 432.686.3689 Fx: 432.686.3696		10 Field and Pool, or Exploratory CORBIN Bone Spring-			
4. Location of Well (Footage, Sec., 7 Sec 18 T18S R33E NESE 16	11. County or Parish, and State LEA COUNTY, NM					
12. CHECK APP	ROPRIATE BOX(ES) TO	INDICATE NATURE OF	NOTICE, R	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent Subsequent Report Final Abandonment Notice	☐ Acidize ☐ Alter Casing ☐ Casing Repair ☐ Change Plans ☐ Convert to Injection	☐ Deepen ☐ Fracture Treat ☐ New Construction ☐ Plug and Abandon ☐ Plug Back	☐ Production (Start/Resume) ☐ Reclamation ☐ Recomplete ☐ Temporarily Abandon ☐ Water Disposal		□ Water Shut-Off □ Well Integrity ☑ Other Drilling Operations	
13 Describe Proposed or Completed Op If the proposal is to deepen direction	eration (clearly state all pertinen ally or recomplete horizontally,	it details, including estimated starting give subsurface locations and measing the subsurface locations and measing the subsurface locations and measing the subsurface locations are subsurface locations.	ng date of any pured and true v	proposed work and appro- ertical depths of all pertir	ximate duration thereof, nent markers and zones	

Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

EOG Resources requests a variance to drill this well using a co-flex line between the BOP and the choke manifold (instead of using a 4" OD steel line).

SEE ATTACHED FOR CONDITIONS OF APPROVAL

	ne foregoing is true and correct Electronic Submission #124129 verifie For EOG RESOURCES INCOR Committed to AFMSS for processing by DEBO	PORAT	ED. sent to the Hobbs		
Name (Printed/Typed)	STAN WAGNER	Title	REGULATORY ANALYST		
Signature	(Electronic Submission)	Date	11/28/2011		
	THIS SPACE FOR FEDERA	L OR	STATE OFFICE USE		
Approved By CHRISTO	OPHER WALLS	TitleF	PETROLEUM ENGINEER		Date 12/05/2011
which would entitle the app	ny, are attached. Approval of this notice does not warrant or ds legal or equitable title to those rights in the subject lease licant to conduct operations thereon.		Hobbs (T DEC	1 3 2011
Title 18 U S.C. Section 100 States any false, fictitious	1 and Title 43 U.S.C. Section 1212, make it a crime for any p or fraudulent statements or representations as to any matter w	erson kn ithin its	owingly and willfully to make to any jurisdiction.	department or agen	cy of the United

Manufacturer: Midwest Hose & Specialty

Serial Number: SN#90067

Length: 35'

Size: OD = 8" ID = 4"

Ends: Flanges Size: 4-1/16°

WP Rating: 10,000 psi Anchors required by manfacturer: No

MIDWEST

HOSE AND SPECIALTY INC.

INTERNAL HYDROSTATIC TEST REPORT								
Customer: CACTUS		P.O. Number: RIG 23						
Asset # M10761 HOSE SPECIFICATIONS								
Туре: Сн	OKE LIN	E		Length:	35'			
I.D.	4"		O.D.	8"	INCHES			
WORKING PRES	SURE	TEST PRESSUR	E	BURST PRESSURE				
10,000	PSI	15,000	PSI	İ.	PSI			
	COUPLINGS							
Type of End Fitting 4 1/16 10K FLANGE								
Type of Coupling: SWEDGED			MANUFACTURED BY MIDWEST HOSE & SPECIALTY					
	PROCEDURE							
TIME HELD AT TEST PRESSURE ACTUAL BURST PRESSURE:					_			
COMMENTS:		MIN.			0 <i>PSI</i>			
M10761 Hose is covered with steel armour cover and wraped with fire resistant vermiculite coated fiberglass insulation rated for 1500 degrees complete with lifting eyes								
Date: 6/6/2	′	Tested By: BOBBY FINK		Approved: MENDI J				

Co-Flex line Conditions of Approval

Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be swapped with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).