1000 Rio Brazie Road, Azias, NM \$7.110	State of New Mexico gy Minerals and Natural Resources Department Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-144 CLEZ July 21, 2008 For closed-loop systems that only use above ground steel tanks or haut-off bins and propose to implement waste removal for closure, submit to the appropriate NMOCD District Office.	
<u>Closed-Loop System Permit or Closure Plan Application</u> (that only use above ground steel tanks or haul-off bins and propose to implement waste removal for closure)			
Typ Instructions: Please submit one application (Form C-144 Cl closed-loop system that only use above ground steel tanks or Please be advised that approval of this request does not relieve th environment. Nor does approval telieve the operator of its respon	haul-off bins and propose to implement waste e operator of liability should operations result i	removal for closure, please submit a Form C-144. in pollution of surface water, ground water or the	
Derator Chnarex Energy Co.	OGRID # 215099		
Address' 600 N Manenfeld St., Ste 600, Midland, TX 79701			
Facility or well name:Coriander "AOC" State No_6			
API Number. 30-947-025-40367	OCD Permit Number	1-04000	
U/L or Qtr/Qtr A Section 1 Township 23S Range 32E County. Lea			
Center of Proposed Design. Latitude <u>32° 20' 24 66" N</u> Longitude <u>103° 37' 22 64" W</u> NAD <sup>1</sup> [1927 [X] 1983			
Surface Owner: 🗌 Federal 🔲 State 🖾 Private 🛄 Tribal Trust or Indian Allotment			
<ul> <li>Closed-loop System: Subsection H of 19.15.17.11 NMAC</li> <li>Operation: Duffing a new well Workover or Duffing (Applies to activities which require prior approval of a permit or notice of intent) P&amp;A</li> <li>Above Ground Steel Tanks or Haul-off Bins</li> <li>Signs: Subsection C of 19.15.17.11 NMAC</li> <li>12"x 24", 2" lettering, providing Operator's name, site location, and emergency telephone numbers</li> <li>Signed in compliance with 19.15.3.103 NMAC</li> </ul>			
4			
Closed-loop Systems Permit Application Attachment Checklist:       Subsection B of 19.15 17 9 NMAC         Instructions:       Each of the following items must be attached to the application. Please indicate, by a check mark in the box, that the documents are attached.         Design Plan - based upon the appropriate requirements of 19.15 17.11 NMAC         Operating and Maintenance Plan - based upon the appropriate requirements of 19.15.17.12 NMAC         Closure Plan (Please complete Box 5) - based upon the appropriate requirements of Subsection C of 19.15.17.9 NMAC and 19.15.17.13 NMAC         Previously Approved Design (attach copy of design)       API Number.         Previously Approved Operating and Maintenance Plan       API Number:			
5 Waste Removal Closure For Closed-loop Systems That 1 Instructions: Please indentify the facility of facilities for th facilities are required.			
Disposal Facility Name:CR1		mit Number <b>N_1-000</b> 6	
Disposal Facility Name		mit Number	
Will any of the proposed closed-loop system operations and Ves (If yes, please provide the information below)		t will not be used for future service and operations?	
Required for impacted areas which will not be used for future         Soil Backfill and Cover Design Specifications base         Re-vegetation Plan - based upon the appropriate require         Site Reclamation Plan - based upon the appropriate reduction	d upon the appropriate requirements of Sub rements of Subsection 1 of 19.15.17.13 NM.	AC	
6 Operator Application Certification: I hereby certify that the information submitted with this app	heation is true, accurate and complete to the	best of my knowledge and belief	
Name (Print)	Title: R	egulatory Analyst	
Signature:	Date:12.	13.2011	
e-mail address <u>tstathem@cimhred.com</u>	1elephor Oil Conservation Division	Page Lof 4	

7 <u>OCD Approva</u> l:  Permit Application (including closure plan) Closure Plan (only)			
OCD Representative Signature: Approval Date:Approval Date:			
Title:	OCD Permit Number: <u>P1-04000</u>		
8. <u>Closure Report (required within 60 days of closure completion)</u> : Subsection K of 19.15.17.13 NMAC Instructions: Operators are required to obtain an approved closure plan prior to implementing any closure activities and submitting the closure report. The closure report is required to be submitted to the division within 60 days of the completion of the closure activities. Please do not complete this section of the form until an approved closure plan has been obtained and the closure activities have been completed.			
Closure Completion Date:			
<sup>9.</sup> Closure Report Regarding Waste Removal Closure For Closed-loop Systems That Utilize Above Ground Steel Tanks or Haul-off Bins Only: Instructions: Please indentify the facility or facilities for where the liquids, drilling fluids and drill cuttings were disposed. Use attachment if more than two facilities were utilized.			
Disposal Facility Name:	Disposal Facility Permit Number:		
Disposal Facility Name	1		
Were the closed-loop system operations and associated activities performed on or in areas that will not be used for future service and operations? Yes (If yes, please demonstrate compliance to the items below) No			
Required for impacted areas which will not be used for future service and operations:         Site Reclamation (Photo Documentation)         Soil Backfilling and Cover Installation         Re-vegetation Application Rates and Seeding Technique			
<ul> <li>10. <u>Operator Closure Certification</u>:         I hereby certify that the information and attachments submitted with this closure report is true, accurate and complete to the best of my knowledge and belief. I also certify that the closure complies with all applicable closure requirements and conditions specified in the approved closure plan.     </li> </ul>			
Name (Print): Title:			
Signature	Daie:		
e-mail address:	Telephone:		

.

2 . 4

1

i

## Equipment List

- Primary Shakers
- Mud Cleaner hydro-cyclones
- 1 or 2 Centrifuges (depending on well depth)
- De-watering system with pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing (may not be necessary for shallower wells)
- Drying Augur
- Sump Drying Augur
- Sump
- Cuttings Boxes
- Reserve Fluids Tank Farm
- Wire Mesh Trash Enclosure (spent motor oils kept in separate containers and later sent to approved landfill)

## **Operation and Maintenance**

The Cimarex Zero Discharge system is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This ensures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

These closed loop operations can be monitored by our service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and tested for all regulated toxic materials. If found they are removed and disposed of per regulatory requirements.

## <u>Closure Plan</u>

During drilling operations, all liquids, drilling fluids, and cuttings will be hauled off via CRI (Controlled Recovery Incorporated, Permit R-9166).

