

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised August 1, 2011

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. <u>30-025-35424</u>
1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☒		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Devon Energy Production Company, LP		6. State Oil & Gas Lease No.
3. Address of Operator 20 North Broadway, Oklahoma City, OK 73102		7. Lease Name or Unit Agreement Name OUTLAND STATE UNIT
4. Well Location Unit Letter <u>C</u> : <u>1650</u> feet from the <u>South</u> line and <u>990</u> feet from the <u>East</u> line Section <u>2</u> Township <u>21S</u> Range <u>34E</u> NMPM <u>Lea</u> County		8. Well Number <u>6</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3720' KB; 3703' GL		9. OGRID Number <u>6137</u>
		10. Pool name or Wildcat Wildcat Wolfcamp

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Wellbore Plug & Abandonment Operations: 11/3/11-12/12/11:

- 11/3/11: MIRU. Circulated wellbore w/9.5# mud.
- Spot 36 sx cmt at 6590'. Tagged TOC @ 6393'.
- Spot 25 sx cmt at 6393'. Tagged TOC @ 6345'
- Spot 25 sx cmt at 6345'. ETOC at 6095'. No tag.
- Cut 5-1/2" casing at 5965'. POOH and lay down casing. Spot 80 sx cmt at 6015'. Tag TOC at 5718'. (9-5/8" casing @ 5765')
- Spot 35 sx cmt at 4250'. Tag TOC at 4137'.
- Spot 35 sx cmt at 3680'. ETOC at 3572'. No tag.
- Spot 35 sx cmt at 1939'. Tag TOC at 1832'.
- Spot 35 sx cmt at 1507'. Tag TOC at 1395'. (13-3/8" casing @ 1443')
- 11/17/11: Spot 35 sx cmt surf plug at 105'.
- 12/12/11: Dry hole marker in place. Wellbore plugged & abandoned.

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.cmnrd.state.nm.us/ocd.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ronnie Slack TITLE Operations Technician DATE 12/12/11

Type or print name Ronnie Slack E-mail address: Ronnie.Slack@dvn.com PHONE: 405-552-4615
For State Use Only

APPROVED BY [Signature] TITLE STATE NOTARY DATE 12-14-2011

Conditions of Approval (if any):

DEC 14 2011

DEVON ENERGY PRODUCTION COMPANY LP

Well Name: OUTLAND STATE UNIT #6		Field: WILSON	
Location: 1650' FSL & 990' FEL; SEC 2-21S-R34E		County: LEA	State: NM
Elevation: 3720' KB; 3703' GL; 17' KB to GL		Spud Date: 6/20/01	Compl Date: 8/27/01
API#: 30-025-35424	Prepared by: Ronnie Slack	Date: 12/12/11	Rev:

PLUG & ABANDONMENT ACTUAL

17-1/2" hole
13-3/8", 54.5#, J55, @ 1443'
Cmt'd w/1160 sx, cmt to surf.

DV tool @ 3630'

12-1/4" hole
9-5/8", 40#, N80 & HC-K55, LT&C @ 5,765'
Cmt'd w/2000 sx, cmt to surf Drift - 8.679"

5-1/2" csg parted @ 6,360'.

TOC @ 10450' (CBL-8/21/01)

MORROW (8/26/01)
12900' - 13010' ; 13016' - 13026'
13098' - 13105'; 13108' - 13112'
13115' - 13117'; 13136' - 13139'
13151' - 13155'

8-3/4" Hole
5-1/2", 17#, HCP-110, LTC, @ 13,570'
Cmt'd w/700 sx
Coupling OD - 6 050"

P&A Actual
Spot 35 sx cmt @ 105' to Surf. (11/17/11)
Cut wellhead off BGL
Dry hole marker in place. (12/12/11)

P&A Actual
Spot 35 sx cmt @ 1507'. Tag TOC @ 1395'. (11/17/11)

P&A Actual
Spot 35 sx cmt @ 1939'. Tag TOC @ 1832'. (11/16/11)

P&A Actual
Spot 35 sx cmt @ 3680'. ETOC @ 3572'. No tag.

P&A Actual
Spot 35 sx cmt @ 4250'. Tag TOC 4137'. (11/15/11)

P&A Actual
Spot 80 sx cmt @ 6015'. Tag TOC 5718'. (11/15/11)
Cut 5-1/2" @ 5965', POOH. (11/11/11)

P&A Actual
Spot 25 sx cmt @ 6345'. ETOC @ 6095'. (11/9/11)
Spot 25 sx cmt @ 6393'. Tagged @ 6345'. (11/8/11)
Spot 36 sx cmt @ 6590'. Tagged @ 6393'. (11/5/11)

Tagged TOC @ 8415'. (5/24/11)
25 sx cmt @ 8,465'. (5/23/11).
Apprvd by E.L. Gonzales (5/24/11)

~ 3-7/8" by 1-3/4" tapered mill stuck in 5-1/2" csg from 8,465' - 8,469' (4').

2-3/8" tbg cut off @ 12,706'(5/5/11)
Swab mandrel, sinker bar and 5' of sand line ontbg plug.
Tbg plug in "F" nipple @ 12,774' (10/21/10)

F Nipple (1.81 ID) @ 12,774 w/ tbg plug installed
1 jt 2-3/8" tbg (32 07')
On/Off w/1.81 profile @ 12,807
Arrowset 1X Packer @ 12808 (7.25") (run 8/25/01)
2-3/8" pup (10 1')
F Nipple (1 81 ID) @ 12,826
1 jt 2-3/8" tbg (32.10')
R Nipple (1 81 ID) 1 76 no go @ 12,859
1 81 Owens mech gun release @ 12,892
1 jt 2-3/8" tbg (31.95')
Bar vent assembly (1 32')
1 jt 2-3/8" tbg (32 07')
No go sub
1 jt 2-3/8" tbg (32 11')
Mech firing head
TCP stim guns for perms 12,998-13,139 (157')

13,570' TD

13,484' PBTD