

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
October 13, 2009

WELL API NO. 30-025-40178 ✓	
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/> ✓	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name Collins Heirs ✓	
8. Well Number 1 ✓	
9. OGRID Number 018100 ✓	
10. Pool name or Wildcat Nadine, West, Abo ✓	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/> ✓	
2. Name of Operator Primero Operating, Inc. ✓	
3. Address of Operator PO Box 1433, Roswell, NM 88202-1433	
4. Well Location Unit Letter K : 1650 feet from the S line and 1700 feet from the W line Section 4 Township 20S Range 38E NMPM Lea County ✓	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4258 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Commence drilling a 12.25" hole at 2:00 pm 11/4/11.

Set 1568' of 8 5/8" 24# J-55 casing @ 1568', casing was equipped with Texas pattern shoe, insert float and centralizers on every 4th joint. 8 5/8" casing was cemented with 533 sx lead cement (35:65:4%gel) and 200 sx tail cement (Class C w/ 2% CaCl). Circulated 200 sx to surface, bump plug @ 3:17 am, 11/7/2011.

A 7 7/8" hole was drilled to 7700' (TD @ 6:30 am, 11/26/2011)

Set 7689' of 5 1/2" 17# L-80 casing equipped with a Float Shoe, Float Collar and a DV tool @ 5011', 10 centralizers were spaced over prospective payzones. The 5 1/2" casing was cemented in two stages:

1st stage: 520 sx 50:50:2 POZ, plug down at 1:21 am, 11/28/11, circulate out 107 sx

2nd stage: 900 sx Lead (35:65:6: POZ) and 300 sx Tail (50:50:2 POZ), Circulate 55 sx, plug down 8:46 am, 11/28/11

Spud Date:

11/4/2011

Rig Release Date:

11/29/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE **President**

DATE **12/11/2011**

Type or print name **Phelps White**

E-mail address: **pwiv@zianet.com**

PHONE: **575 622 1001**

For State Use Only

APPROVED BY:

TITLE

DATE

DEC 15 2011

Conditions of Approval (if any):

DEC 15 2011