HOBBS OCD FORM APPROVED OM B No 1004-0137 Expires March 31, 2007 Form 3160-5 UNITED STATES DEC 27 EPARTMENT OF THE INTERIOR (February 2005) BUREAU OF LAND MANAGEMENT 5. Lease Senal No SUNDRY NOTICES AND REPORTS ON WELLS

Do, not use this form for proposals to drill or to re-enter an NMNM 078148 If Indian, Allottee or Tribe Name abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No SUBMIT IN TRIPLICATE- Other instructions on reverse side. Type of Well Oil Well 🗆 **✓** Other Gas Well 🗆 Well Name and No. French, 9004 JV-P #3 2 Name of Operator BTA Oil Producers LLC API Well No. 30=025=31206=00=S1 3a Address 3b Phone No (include area code) 432-682-3753 104 S. Pecos, Midland, TX 79701 10 Field and Pool, or Exploratory Area Corbin, Wolfcamp South 4 Location of Well (Footage, Sec., T., R, M, or Survey Description) 11 County or Parish, State UL -H-, Sec. 24, T18S-R32E 1980' FNL & 510' FEL Lea Co., NM 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Acidize Water Shut-Off Production (Start/Resume) Deepen Notice of Intent Well Integrity Alter Casing Reclamation Fracture Treat Other Check for possible Casing Repair New Construction Recomplete Subsequent Report tbg leak, MIT Change Plans Plug and Abandon ☐ Temporanly Abandon Final Abandonment Notice Convert to Injection Plug Back Water Disposal 13 Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No on file with BLM/BIA Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection) 11/16-17/2011 MIRU on well, NU BOP. Unseat packer and POOH w/tubing. Found hole in nickel plated collar on packer. PU exchanged packer and RIH w/plastic coated tubing. Set packer @ 10,284'. Load backside w/packer fluid and pressure test to 500#, held good. RU chart recorder and pressure test well to 500# for 1 hour, witnessed by BLM rep., held good. ACCEPTED FOR RECORD Copy of chart attached. Like submittal to State. DEC 2 0 2011 SEE ATTACHED FOR /s/ JD Whitlock Jr CONDITIONS OF APPROVAL BUREAU OF LAND MANAGEMENT CARLSBAD FIELD OFFICE I hereby certify that the foregoing is true and correct Name (Printed/Typed)

Title Regulatory Administrator

Date 11/28/2011

Date:

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)


Signature

Pam/Inskeep

MW/OCD 12-28-2011

Title

Office



Conditions of Approval

BTA Oil Producers LLC French, 9004 JV-P #3 API 3002531206

December 08, 2011

- 1) Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
 - a) The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
 - b) Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
 - c) At least 24 hours before the test: In Eddy County email Paul R. Swartz <u>paul_swartz@blm.gov</u>, (phone 575-200-7902). If there is no response phone 575-361-2822. In Lea County email Andy Cortez <u>andy_cortez@blm.gov</u>, (phone 575-393-3612 or 575-631-5801). Note the contact notification method, time, & date in your subsequent report.
 - d) Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
 - e) Use of tubing internal protection, on/off tubing equipment just above the packer, and a profile nipple installation is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore workover.
 - f) Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2) Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
 - a) Approved injection pressure compliance is required.
 - b) If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
 - c) When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
 - i) Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
- 3) Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.
- 4) The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.
- 5) The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
- 6) **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of beginning injection.

- 7) The operator shall keep monthly records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.
- 8) Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
- 9) Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz <u>paul swartz@blm.gov</u> phone 575-200-7902). If there is no response phone 575-361-2822.
- 10) Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for planned well work involving a formation change, casing repair/replacement, and injection well fracture treatment for approval by BLM and NMOCD. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days. Packer and tubing repair (normal maintance procedures) do not require a NOI, but a subsequent sundry needs to be filed. http://www.blm.gov/nm/st/en/prog/energy/oil and gas.html (see CFR § 3162.3-2 43 & CFR § 3160.0-9 (c)(1)).
- 11) Submit a (Sundry Form 3160-5) subsequent report (daily reports) describing all wellbore activity and Mechanical Integrity Test as per item 1) above. Include the date(s) of the well work, and the setting depths of required equipment: tubing, one on/off tool, one profile nipple, and a single packer.

PRS 120811

Use of Form 3160-5 "Sundry Notices and Reports on Wells"

§ 43 CFR 3162.3-2 Subsequent Well Operations.

- (a) A proposal for further well operations shall be submitted by the operator on Form 3160–5 for approval by the authorized officer prior to commencing operations to redrill, deepen, perform casing repairs, plug-back, alter casing, perform fracturing jobs, recomplete in a different interval, perform water shut off, commingling production between intervals and/or conversion to injection. If there is additional surface disturbance, the proposal shall include a surface use plan of operations. A subsequent report on these operations also will be filed on Form 3160–5. The authorized officer may prescribe that each proposal contain all or a portion of the information set forth in \$3162.3–1 of this title.
- (b) Unless additional surface disturbance is involved and if the operations conform to the standard of prudent operating practice, prior approval is not required for routine fracturing or acidizing jobs, or recompletion in the same interval; however, a subsequent report on these operations must be filed on Form 3160–5.
- (c) No prior approval or a subsequent report is required for well cleanout work, routine well maintenance, or bottom hole pressure surveys.

[47 FR 47765, Oct. 27, 1982. Redesignated and amended at 48 FR 36583–36586, Aug. 12, 1983, further amended at 52 FR 5391, Feb. 20, 1987; 53 FR 17363, May 16, 1988; 53 FR 22847, June 17, 1988]

§ 43 CFR 3160.0-9 (c)(1) Information collection.

(c)(1) The information collection requirements contained in part 3160 have been approved by the Office of Management and Budget under 44 U.S.C. 3507 and assigned the following Clearance Numbers:

Operating Forms

Form No.	Name and filing date	OMB No.
3160-3	Application for Permit to Drill, Deepen, Plug Back, or Fracture—Filed 30 days prior	1004–0136
3160–4	With Completion of Recompletion Report and Log-Due 30 days after well completion	1004-0137
3160–5	Sundry Notice and Reports on Wells—Subsequent report due 30 days after operations completed	1004–0135

The information will be used to manage Federal and Indian oil and gas leases. It will be used to allow evaluation of the technical, safety, and environmental factors involved with drilling and producing oil and gas on Federal and Indian oil and gas leases. Response is mandatory only if the operator elects to initiate drilling, completion, or subsequent operations on an oil and gas well, in accordance with 30 U.S.C. 181 *et seq.*

§ 3162.4-1 (c) Well records and reports.

Not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160–5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed.

NM Fed Regs & Forms - http://www.blm.gov/nm/st/en/prog/energy/oil and gas.html