

District I

1625 N French Dr, Hobbs, NM 88249

District II

1301 W Grand Ave, Artesia, NM 88210

District III

1000 Rio Brazos Rd, Aztec, NM 87410

District IV

1220 S St Francis Dr, Santa Fe, NM 87505

HOBBS OGD

JAN 17 2012

RECEIVED

Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30 025 38318

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

BO-2052-0004

7. Lease Name or Unit Agreement Name

NORTH MONUMENT G/SA UNIT

8. Well Number 364

9. OGRID Number

873

10. Pool name or Wildcat

Eunice Monument; Grayburg-San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: ☒ Well ☐ Gas Well ☐ Other

2. Name of Operator

APACHE CORPORATION

3. Address of Operator

303 VETERANS AIRPARK LN, STE 3000; MIDLAND, TX 79705

4. Well Location

Unit Letter N : 10 feet from the S line and 1420 feet from the W line

Section 19 Township 19S Range 37E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3675' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

OTHER: PERF, ACIDIZE ADDITIONAL GRAYBURG PAY ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ P AND A ☐

CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. MIRU PU. TOH w/rods & pmp. ND WH. NU BOP. TOH w/tbg.

2. RU WL. RIH w/ gauge ring/junk basket on WL to 3870'. Set RBP on WL @ 3870'. Load hole & tst RBP to 1000 psi. Perf Grayburg @ 3801-3809', 3814-3834', 3838-3846' & 3850-3858' w/2 spf, 120 deg phasing, Total = 96 shots.

3. TIH w/tbg & retrievable pkr w/RBP retrieving head. Spot 15% NEFE HCL acid across perfs 3801-3858'. TOH w/3700'. Reverse excess acid into tbg. Set pkr @ +/- 3700'. Hold 500 psi on annulus.

4. Acidize perfs 3801-3858' w/3000 gals 15%-NEFE HCL and ball sealers.

5. Swab tst perfs 3801-3858'.

6. Release pkr & RBP. TOH.

7. TIH w/prod. tbg. ND BOP. NU WH. Run pmp & rods.

8. Put well on tst.

Spud Date: 06/01/2007

Rig Release Date: 06/08/2007

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Beverly Hatfield*

TITLE Sr. Staff Regulatory Tech

DATE

Type or print name Bev Hatfield

E-mail address: beverly.hatfield@apachecorp.com

PHONE: 432-818-1906

For State Use Only

APPROVED BY:

*[Signature]*

TITLE

PETROLEUM ENGINEER

DATE

JAN 17 2012

Conditions of Approval (if any):

JAN 23 2012

*COA*