Submit 1 Copy To Appropriate District	State of New Me	xico	Form C-103		
Office <u>District I</u> 1625 N. French Dr., Hobbs, NM4883406 AAA	Energy, Minerals and Natu	ral Resources	October 13, 2009 WELL API NO. 30-025-40336		
1625 N. French Dr., Hobbs, NM 8835 OCD District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION		5. Indicate Type of Lease		
District III 1000 Rto Brazos Rd, Aztec, JAN74107 201	2 1220 South St. Fran		STATE FEE		
1220 S. St. Francis Dr., Santa Fe, NM	,	505	6. State Oil & Gas Lease No.		
	S AND REPORTS ON WELLS		7. Lease Name or Unit Agreement Name		
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH			WEST TATUM STATE UNIT <38936>		
PROPOSALS.) 1. Type of Well: Oil Well 🛛 Gas Well 🗌 Other			8. Well Number 001H		
2. Name of Operator	E CORPORATION		9. OGRID Number 873		
3. Address of Operator 303 VET	ERANS AIR PARK LANE, ST ND, TEXAS 79705	E 3000	10. Pool name or Wildcat WILDCAT; ABO <97019>		
4. Well Location			/		
	from the <u>SOUTH</u> line and				
Section 26 Township 12S Range 35E NMPM County LEA 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 11. Elevation (Show whether DR, RKB, RT, GR, etc.)					
4	043 GR				
12. Check App	propriate Box to Indicate N	ature of Notice,	Report or Other Data		
NOTICE OF INTE	INTION TO:	SUB	SEQUENT REPORT OF:		
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR					
	CHANGE PLANS 🛛	COMMENCE DRI CASING/CEMEN			
OTHER:		OTHER:	<u>a</u>		
13. Describe proposed or complete of starting any proposed work)	ed operations. (Clearly state all j	pertinent details, and C. For Multiple Cou	d give pertinent dates, including estimated date mpletions: Attach wellbore diagram of		
proposed completion or recom		-			
1/12/12: Due to geologic cond	cerns in the ABO formation, Apa	che Corp proposes	to suspend current operations while further		
evaluations of the logs & sidewall cores can be completed. Apache Corp proposes to set Bridge Plug within 100' of intermediate casing shoe, set @ 4363'. After bridge plug is set, casing will be tested to 1000psi & be charted.					
This procedure was d	iscussed with Paul Kautz @ the		<i>.</i> .		
so more 11-liz/n					
TA EXMES 4/12/n					
	/				
					
Spud Date: /2//8///	Rig Release Da	ate:			
		L			
I hereby certify that the information abo	ove is true and complete to the b	est of my knowledg	e and belief.		
ρ .	0 10				
SIGNATURE Sorena of	Horz TITLE SU	pv of Drlg Service	<u>s</u> DATE <u>1/12/2012</u>		
Type or print name _Vicki Brown					
APPROVED BY:	TITLE	ETHER EGH ENN	DATE JAN 17 2017		
Conditions of Approval (if any):			····		

.

~		r al
JAN	23	20120