Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIO BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease	Serial	No.
NMNM-1	25057	•

SUNDRY NOTICES AND REPORTS ON WELLS		6. If Indian, Allottee or Tribe Name			
Do not use this form for proposals to drill or to re-enter and					
Abandon	ed well. Use Form	3160-3 (APD) for such pro	oposals		
SUBMIT IN TRIPLICATE – Other instructions on page 21408BS		7. If Unit of CA/Agreement, Name and/or No. EBDU			
1. Type of Well		Other JAN 1	8 5015		No. INKARD UNIT 116 <35023>/
2. Name of Operator APACHE C	ORPORATION <873>		CEIVED	9. API Well No. 30-025-40268	
3. Address		3b. Phone No. (include a led	(Code)	10. Field and Pool o	r Exploratory Area
303 VETERANS	AIRPARK LN, #3000 , TX 79705	432-818-1117 / 432-818		EUICE; BLI-TU-D	RI, NORTH <22900>
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State			
3630' FSL & 1760' FEL, LOT:15, SEC 1, T21S, R37E, NMPM		LEA COUNTY, N	vi /		
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA					
TYPE OF SUBMISSION	TYPE OF ACTION				
Notice of IntentSubsequent ReportFinal Abandonment Notice	Acidize Alter Casing Casing Repair Change Plans Convert to Injection	Deepen Facture Treat New Construction Plug and Abandon Plug Back	Production (Start/Resume) Reclamation Recomplete Temporarily Abandon Water Disposal		Water Shut-Off Well Integrity Other DRILLING OPS: CASING & CEMENT REPORT
Attached the Bond under which t	tional or recomplete horizon he work will be performed o	pertinent details, including estimated tally, give subsurface locations and nor provide the Bond No on file with I ation results in a multiple completion	neasured and to BLM/BIA Re	true vertical depths of all pe equired subsequent reports	must be filed within 30 days

Bond No: BLM-CO-1463 12/10/2011 - SPUD

12/11/2011 - 8-5/8" Surface, Hole sz. 12-1/4" Run & set 8-5/8" 24# J-55 STC csg to 1630'.

12/12/2011 - Cement with:

determined that the site is ready for final inspection

<u>Lead</u>: 550 sx Class C w/2% CaCl, 0.25% CF, 3#/sx LCM-1, 0.005 gps FP-6L, 4% Bentonite (13.5 ppg, 1.75 yld)

testing has been completed Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has

Comp Strengths: 12 hr - 402 psi 24 hr - 608 psi 72 hr - 1340 psi

Tail: 300 sx Class C w/1% CaCl, 0.13 #/sx CF, 0.005 gps FP-6L

(14.8 ppg, 1.33 yld)

Compressive Strengths: 12 hr - 859 psi

Circ 196 sx cmt to surf 24 hr - 1427 psi

12/19/2011 - Drl F/ 7224' - T/7244' TD. RU Baker Atlas Loggers.

12/20/2011 - 5-1/2" Production, Hole sz. 7-7/8" Run & set 5-1/2" 17# L-80/J-55 LTC csg to 7244'. Cement with:

Lead: 1050 sx (50:50) Poz (Fly ash): Class C w/5% NaCl, 0.13 #/sx CF, 3 #/sx LCM-1, 0.5% FL-52, 0.005 gps FP-6L, 10%

Bentonite, 0.2% Sodium Metasilicate

Compressive Strengths: 12 hr – 450 psi

(11.8 ppg, 2.47 yld

Compressive Strengths: **12 hr** – 259 psi **24 hr** – 798 psi **72 hr** – 1405 psi N

Tail: 410 sx (50:50) Poz (Fly ash): Class C w/5% NaCl, 0.13#/sx CF, 0.2% CD-32, B / sx 4 CM-1

(14.2 ppg 1.3 yld) 6L, 2% Bentonite, 0.1% Sodium Metasilicate

12/20/2011 - RR

24 psi - 1875 psi

Circ 185 sx cmt to surf. JAN 1 4 2012

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) VICKI BROWN	itle DRILLING TECH				
Signature Wicki Brows	Date 1/3/2012				
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by					
	Title	Date			
Conditions of approval, if any, are attached Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon	Office				
Title 18 U>S C Section 1001 and Title 43 U S C Section 1212, make it a crime for any pany false, fictitious or fraudulent statements or representations as to any matter within its		ment or agency of the United States			

(Instructions on page 2)