

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

October 13, 2009

JAN 26 2012

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.
Santa Fe, NM 87505

RECEIVED

WELL API NO.

30-025-29244

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

PEOPLES 33 STATE

8. Well Number: 001

9. OGRID Number 269324

10. Pool name or Wildcat

GRAYBURG JACKSON; SR-Q-G-SA-W

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
LINN OPERATING INC.

3. Address of Operator
600 TRAVIS, SUITE 5100, HOUSTON, TEXAS 77002

4. Well Location

Unit Letter L; 1980 feet from the S line and 660 feet from the W line
Section 33 Township 18S Range 35E NMPM LEA County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3.911'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

PLEASE SEE ATTACHED

Approved for plugging of well bore only.
Liability under bond is retained pending receipt
of C-103 (Subsequent Report of Well Plugging)
which may be found at OCD Web Page under
Forms, www.cmrnd.state.nm.us/ocd.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Terry B. Callahan

TITLE: REGULATORY SPECIALIST III DATE JANUARY 25, 2012

Type or print name TERRY B. CALLAHAN E-mail address: tcallahan@linnenergy.com PHONE: 281-840-4272

For State Use Only

APPROVED BY:

Markus Bacon

TITLE Compliance Officer DATE 1/26/2012

Conditions of Approval (if any):

JAN 26 2012

PEOPLES 33 STATE 001
API #30-025-29244
ITEM #13 FROM C-103 SUBSEQUENT

- 12/08/11 MIRU plugging equipment. NU BOP.
- 12/09/11 RIH w/bid and scrapper to 11056'. POH w/ 25 stds.
- 12/12/11 Finish POH w/ bit & scrapper. RIH w/ 5-1/2 CIBP on tbq. Set plug @ 11016'. Circ 100 bbls mud laden fluid, spot 25 sx cmt on top of plug. POH w/ 1500'. WOC.
- 12/13/11 Tagged plug @ 10850'. POH w/ tbq. Perf'd csg @ 10050'. RIH w/ pkr on tbq. Set pkr @ 9500'. Sqz'd 40 sx cmt. WOC. Tried to release pkr. Would not release. SDFN.
- 12/14/11 RIH w/ tbq cutter. Did not fire. Work tbq free. POH w/ tbq. Stand back 7650', lay rest down. Total out of hole 9430'. Pkr & 2 jts in hole. Load hole w/ 240 bbls of mud laden fluid. Perf'd csg @ 7650. SDFN.
- 12/15/11 Per Maxie Brown w/ OCD, RIH open ended to 7700'. Spot 35 sx cmt. Pull out of cement 1500'. WOC. Tagged plug @ 7438'. POH. Perf'd csg @ 7070'. RIH open ended to 7120 and spot 35 sx cmt. POH 1500' WOC, SDFN.
- 12/16/11 Tagged plug @ 6837'. POH w/ tbq. Perf'd csg @ 6050'. RIH w/ packer & set at 5600'. Sqz'd 35 sx cmt. Pressured up to 1400 psi. WOC.
- 12/19/11 Tagged plug @ 5810'. POH w/ tbq. Rigged up csg jacks. Worked csg off slips, SDFN.
- 12/20/11 RIH w/ cutter & cut 5-1/2 csg. RD jacks. POH w/ 73 jts of csg. SDFN.
- 12/21/11 Finished LD csg. (92 jts 3940') NU BOP & wellhead. RIH w/ tbq to 4000'. Load hole w/ mud laden fluid. Spot 50 sx cmt. POH 1500'. WOC. Tagged plug @ 3800'. POH to 3400'. Spot 50 sx cmt. POH to 1830'. SDFN.
- 12/22/11 Load hole w/ mud laden fluid. Spot 50 sx @ 1830'. POH to 465'. Spot 50 sx. Pull out of cmt. WOC. Tagged plug @ 260'. POH to 60'. Circ 20 sxs cmt to surface. ND BOP. Rigged down, moved off.
- 12/29/11 Move in welder and backhoe. Dug out cellar, cut off wellhead, welded on Dry Hole Marker. Back filled cellar, cut off deadmen. Clean location, moved off

Current Wellbore Schematic

Well Name. Peoples 33 State 1
 Location. Lea County, NM
 L-33-18S-35E 1980 FSL 660 FWL □
 API # 30-025-29244
 Elevations GROUND. 3911'
 KB
 Depths (KB) PBTD 11,171'
 TD 11,232'

Date Prepared 8-Sep-11 D Gonzales
 Last Updated
 Spud Date 5/23/85
 RR Date
 Spud Date to RR Date
 Completion Start Date.
 Completion End Date
 Completion Total Days.
 Co-ordinates

