

District I -- (575) 393-6161
1625 N French Dr., Hobbs, NM 88240
District II -- (575) 748-1283
811 S First St., Artesia, NM 88210
District III -- (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV -- (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OGD

Geology, Minerals and Natural Resources

FEB 08 2012

CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

RECEIVED

WELL API NO.	30-025-29712
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	HUDGENS
8. Well Number	1
9. OGRID Number	147179
10. Pool name or Wildcat	SWD; WOLFCAMP
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	3883' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other SWD ☒

2. Name of Operator
Chesapeake Operating, Inc.

3. Address of Operator
P.O. Box 18496
Oklahoma City, OK 73154-0496

4. Well Location
Unit Letter J : 1980' feet from the South line and 1980' feet from the East line
Section 11 Township 16 S Range 36 E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Please find work performed in the plug and abandonment on this well from 1/31/12 through 2/03/12.

01/13/12: HELD PJSM -- MIRU BASIC PLUGGING RIG - CONDUCTED RIG INSPECTION DUG OUT CELLAR - SPOTTED EQUIPMENT - N/D WELLHEAD - N/U BOP - RELEASED PACKER - TOH LAYING DOWN (305) JOINTS 2 3/8" TUBING - SECURED WELL & SDFN.

02/01/12: HELD PJSM - MIRU BASIC WIRELINE RIH WITH CIBP - SET CIBP @ 10,507' - RIH WITH WIRELINE BAILER & DUMPED 35' CLASS "H" CEMENT ON TOP OF CIBP - P/U RIH WITH 2ND CIBP & SET @ 9,654' - RIH WITH WIRELINE BAILER & DUMPED 35' CLASS "H" CEMENT ON TOP OF CIBP - RDMO WIRELINE RACKED & TALLIED (310) JOINTS 2 3/8" L-80 WORK STRING - P/U & START TRIPPING IN - RAN (131) JOINTS COULD NOT GET PAST OBSTRUCTION - SDFN

(Cont. Page 2)

Spud Date:

Rig Release Date:

Approved for plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OGD Web Page under Forms, www.emnrd.state.nm.us/ogd.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Bryan Arrant TITLE Regulatory Specialist II DATE 02/07/2012

Type or print name Bryan Arrant E-mail address: bryan.arrant@chk.com PHONE: (405)935-3782
For State Use Only

APPROVED BY: [Signature] TITLE Staff DATE 2-9-2012

Conditions of Approval (if any):

Plug and Abandonment Cont.

**HUDGENS 1
Section 11, T-16-S R-36-E
1980' FSL & 1980' FEL, NMPM
LEA CO., NEW MEXICO
API # 30-025-29712**

02/02/12:

HELD PJSM, WORKED TBG PAST TIGHT SPOT IN CASING (4,000') TAGGED TOC @ 9,600' - POH TO 9,548' & CIRCULATED MUD PULLED TUBING TO 6,006' - LAID DOWN (115) JOINTS - SPOTTED 25 SX CLASS "C" CEMENT - PULLED TUBING TO 4,524 LAID DOWN (48) JOINTS - SPOTTED 25SX CLASS "C" CEMENT - PULLED & STOOD BACK 30 JOINTS - SECURED WELL & SDFN

02/03/12:

HELD PJSM, TAGGED TOC @ 4,269' PULLED TUBING TO 2,002' - LAID DOWN (74) JOINTS - SPOTTED 25 SX CLASS "C" CEMENT - PULLED TUBING TO 1,108' LAID DOWN (29) JOINTS - SPOTTED 25 SX CLASS "C" CEMENT - PULLED & STOOD BACK 20 JOINTS - WOC TAGGED TOC @ 854' - PULLED TBG TO 478' - LAID DOWN (20) JOINTS - SPOTTED 35 SX CLASS "C" CEMENT PULLED TBG TO 492' - SPOTTED 100 SX 2% CALCIUM TO SURFACE - N/D BOP - LAID DOWN ALL TBG RDMO ALL WORKED OK'D BY MAXEY BROWN, NMOCD WELL P&A ON 2/03/12.