Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

CHOPPS OCD

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

	expires.	July	ЭΙ,
Lease Ser	ial No.		
LIKEL OO	204050		

SUNDRY NOTICES AND REPORTS ON WELLS	- 1	r
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals. ৭ ७ २००२	·	6. I

6.	If Indian, Allottee or Tribe Name	

					
SUBMIT IN TRIPLICATE - Other instructions on revers				. If Unit or CA/Agree	ment, Name and/or No
1 Type of Well	RECEIVE	8	8. Well Name and No RUBY FEDERAL 6		
Oil Well Gas Well Oth					,
2 Name of Operator CONOCOPHILLIPS COMPAN	Contact BRIA IY E-Mail: brian d.maiorino(N MAIORINO @conocophillips.com		API Well No. 30-025-40395-00	
3a. Address 3300 N "A" ST BLDG 6 MIDLAND, TX 79705	Phone No. (include area code 432-688-6913	e) 1	10 Field and Pool, or Exploratory MALJAMAR		
4. Location of Well (Footage, Sec., T	., R., M , or Survey Description)		1	1 County or Parish, a	nd State
Sec 17 T17S R32E SWSW 994FSL 236FWL				LEA COUNTY, N	MM /
12. CHECK APPE	ROPRIATE BOX(ES) TO INC	DICATE NATURE OF	NOTICE, REP	ORT, OR OTHER	R DATA .
TYPE OF SUBMISSION		ТҮРЕ О	F ACTION		
Notice of Intent	□ Acidize	Deepen	Production	(Start/Resume)	☐ Water Shut-Off
_	☐ Alter Casing	☐ Fracture Treat	☐ Reclamation	on	☐ Well Integrity
☐ Subsequent Report	☐ Casing Repair	☐ New Construction	Recomple	te	Other
Final Abandonment Notice	☐ Change Plans	Plug and Abandon	☐ Temporari	ly Abandon	Change to Original A PD
	Convert to Injection	☐ Plug Back	□ Water Dis	posal	10
testing has been completed. Final Aldetermined that the site is ready for f ConocoPhillips Company resp Production Csg will be set @ Production Cmt will be as follo Lead:1000 Sx 50:50 Poz C 52	pectfully request to drill to a de 7174'-7219' Dws 200'-surface, 11.8 ppg, 2640 cu	y after all requirements, inclupth of 7229' MD on the uFt, +10% Bentonite +8	Ruby Federal # Approv Ibs/sx Salt+ 07	have been completed, a 16. (al Subject to Gene (Special Stipulatio	and the operator has
volume, Yield 2.64 cuft/sx Tail: 650 sx Class H 7174'-72	CM if needed, Excess = 220% 19' to 5200', 16.4 ppg, 696 cuft 0.2 antifoam, excess = 100%	+ 0.2% Fluid loss add	litive + 0.3% ed on guage ho		
14 I hereby certify that the foregoing is	Electronic Submission #13079 For CONOCOPHILI	JPS COMPANY, sent to	the Hobbs	,	APPROVAL
Committed to AFMSS for processing by DEBO Name (Printed/Typed) BRIAN MAIORINO		•	·		
Signature (Electronic S	Submission) THIS SPACE FOR F	Date 02/14/2			·
	THIS OF AGE FOR FI	TOTAL ON STATE		. /	
Approved By TED MORGAN	TitlePETROLE	EUM ENGINEE	R / M	Date 02/23/2012	
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conditions.	Office Hobbs				
Title 18 U S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a crime statements or representations as to any	for any person knowingly ar matter within its jurisdiction	nd willfully to maken.	e to any department or	agency of the United

Additional data for EC transaction #130796 that would not fit on the form

32. Additional remarks, continued

Everything else will stay the same according to the originally approved APD

Ruby Federal 6 ConocoPhillips Company 30-025-40395 February 22, 2012 Conditions of Approval

Summary of Current Status:

- Currently approved for TD at 6953' with TOC for 5-1/2" casing to surface.
- Operator estimates Top of Tubb at 6763', and states the deepest perforation is to be 10' above it.
- BLM estimates the Top Abo at 7485'

NOTE: The Field and Pool for the Ruby Federal is Maljamar: Yeso, West. The Yeso includes the Glorieta, Paddock, Blinebry, Tubb, and Drinkard. The Operator states it is necessary to drill deeper for the purpose of evaluating the Drinkard formation. In the same phone call, the Operator also confirmed the well is still a vertical well.

Requests:

Sundry dated 2/14/2012 includes the following:

- Revise the planned TD of 6953' to now be at 7289'. (±196' above the Top Abo)
- Revise the depth range of the 5-1/2" shoe to be between 7174' 7219' (±336' deeper, and approximately 266' above the estimated top Abo.)
- TOC for the 5-1/2" casing is still intended to be surface.

Conditions of Approval:

Terms of original APD COA and already approved sundries shall continue to be applicable for this well, with the following revisions to also apply:

Operator is to consider the Abo top when deepening the originally approved TD of the well. Bursts of high pressure may occur if the Abo is penetrated. Use of the mud logging unit (now approved as an option in the original APD) may benefit the Operator when drilling in the proximity of the Abo top.

TMM 02/23/2012