Form 3160-5 " (August 2007)

1. Type of Well

(Instructions on page 2)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137

Expires: July 31, 2010

5. Lease Serial No. LC 032096B

8. Well Name and No.

**SUNDRY NOTICES AND REPORTS ON WELLS** 

SUBMIT IN TRIPLICATE - Other instructions on page 2.


Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals ED

6. If Indian, Allottee or Tribe Name

MAR 2 2 2013

7. If Unit of CA/Agreement, Name and/or No.

🔲 Oil Well 🔲 Gas W	rell ✓ Other Injecti	on /		3. Well Name and N East Blinebry Drin		
2. Name of Operator Apache Corporation		-	Ģ	9. API Well No. 30-025-06481		
3a. Address 303 Veterans Airpark Lane, Suite 3000 Midland, TX 79705	!	Phone No. <i>(include area c</i> . 2/818-1062		10. Field and Pool or Eunice; B-T-D, No	r	
4. Location of Well (Footage, Sec., T.,R.,M., or Survey Description)				11. Country or Parish, State		
1980' FSL & 330' FEL ULI Sec 11 T21S R37E	./			Lea County, NM	✓	
12. CHEC	K THE APPROPRIATE BOX(	ES) TO INDICATE NATUI	RE OF NOTICE	E, REPORT OR OT	HER DATA	
TYPE OF SUBMISSION		T	YPE OF ACTION	NC		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Produc	ction (Start/Resume)	<ul><li></li></ul>	
✓ Subsequent Report	Casing Repair	New Construction	Recom	plete	Other PARTED PACKER	
Final Abandonment Notice	Change Plans Convert to Injection	☐ Plug and Abandon☐ Plug Back		orarily Abandon Disposal		
the proposal is to deepen directions Attach the Bond under which the v	ally or recomplete horizontally, york will be performed or provided operations. If the operation of Abandonment Notices must be f	give subsurface locations and le the Bond No. on file with results in a multiple complet	d measured and BLM/BIA. Re ion or recomple	I true vertical depths equired subsequent retion in a new interv	al, a Form 3160-4 must be filed once	
A possible leak was detected on this	s well. Apache performed the	e following:				
1/20/2012 MIRUSU LD parted pact 1/21/2012 Attempt to fish dual pack 1/23/2012 Fish packer. 1/24/2012 Bit & scraper run. 1/25/2012 PU RIH tag for fill; start 0/1/26/2012 CO to PBTD @ 6780'. F 1/27/2012 POOH w/packer & prep	cer. CO. RIH w/pkr & WS to 5623', set for acid job. gal HCL & 1950# Rock Salt. test.	· ·		-	·	
Chart Attached SEE A	MACHEO OR	OERS		acc w/	cept for record attached OAC 128/2012 PRI	
				02,	28/2012 PRS	
14. I hereby certify that the foregoing is to	rue and correct. Name (Printed/T)	vped)				
Reesa Holland		Title Sr. Stat	ff Engr Tech	<u></u>		
Signature ROSa	bland	Date 02/08/2	2012	ACCE	PTED FOR RECORD	
	THIS SPACE FO	OR FEDERAL OR S	TATE OFF	ICE USE		
Approved by		Title	•		MAR 19 202 Sal JD Whitlock J	
Conditions of approval, if any, are attached that the applicant holds legal or equitable entitle the applicant to conduct of erations	itle to those rights in the subject le	ase which would Office			EAU OF LAND MANAGEMENT	
Title 18 U.S.C. Section 1001 and Title 43 fictitious or fraudulent statements or repre			and willfully to	make to any departm	ent or agency of the United States any false.	



## **Order of the Authorized Officer**

# Apache Corporation East Blinebry Drinkard Unit #020 API 3002506481

February 28, 2012

## Well with a Packer - Operations

- 1) Conduct a Mechanical Integrity Test of the tubing/casing annulus after a tubing, packer or casing seal is established. Repair that seal any time more than five barrels of packer fluid is replaced within 30 days.
  - a) The minimum test pressure should be 500 psig for 30 minutes or 300 psig for 60 minutes, with 200 psig differentials between tubing and casing pressure (at test time) but no more than 70% of casing burst pressure as described by Onshore Order 2.III.B.1.h. (The tubing or reservoir pressure may need to be reduced). An alternate method for a BLM approved MIT is to have the fluid filled system open to atmospheric pressure and have a loss of less than five barrels in 30 days witnessed by a BLM authorized officer.
  - b) Document the pressure test on a calibrated recorder chart registering within 25 to 85 per cent of its full range. Greater than 10% pressure leakoff will be viewed as a failed MIT. Less than 10% pressure leakoff will be evaluated site specifically and may restrict injection approval.
  - c) At least 24 hours before the test: In Eddy County email Paul R. Swartz <u>paul\_swartz@blm.gov</u>, (phone 575-200-7902). If there is no response phone 575-361-2822. In Lea County email Andy Cortez <u>andy\_cortez@blm.gov</u>, (phone 575-393-3612 or 575-631-5801). Note the contact notification method, time, & date in your subsequent report.
  - d) Submit a subsequent Sundry Form 3160-5 relating the MIT activity. Include a copy of the recorded MIT pressure chart. List the name of the BLM witness, or the notified person and date of notification. NMOCD is to retain the original recorded MIT chart.
  - e) Use of tubing internal protection, tubing on/off equipment just above the packer, and an in line tubing check valve below the packer or between the on/off tool and packer is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore workover.
  - f) Submit the original subsequent sundry with three copies to BLM Carlsbad.
- 2) Compliance with a NMOCD Administrative Order is required, submit documentation of that authorization.
  - a) Approved injection pressure compliance is required.
  - b) If injection pressure exceeds the approved pressure you are required to reduce that pressure and notify the BLM within 24 hours.
  - c) When injection pressure is within 50 psig of the maximum pressure, install automation equipment that will prevent exceeding that maximum.
    - i) Submit a subsequent report (Sundry Form 3160-5) describing the installed automation equipment within 30 days.
- 3) Other unexplained significant variations of rate or pressure to be reported within 5 days of notice.
- 4) The casing/tubing annulus is required to be monitored for communication with injection fluid or loss of casing integrity.

- 5) The annulus is to be maintained full of packer fluid at atmospheric pressure. Installation of equipment that will display on site, continuous open to the air fluid level is required. A BLM inspector may request verification of this fluid level at any time.
- 6) **Submit a subsequent report (Sundry Form 3160-5)** describing the installation of packer fluid level monitoring equipment within 30 days of beginning injection.
- 7) The operator shall keep monthly records documenting that the casing annulus is fluid filled. A suggested format for these records is available from the BLM Carlsbad Field Office. Copies of those records shall be furnished at the request of a BLM authorized officer.
- 8) Loss of packer fluid above five barrels per month requires notification of the BLM authorized officer within 5 days.
- 9) Gain of annular fluid requires notification within 24 hours. Cease injection and maintain a production casing pressure of Opsia. Notify the BLM's authorized officer (Paul R. Swartz <u>paul swartz@blm.gov</u> phone 575-200-7902). If there is no response phone 575-361-2822.
- 10) Also submit to this office a (Sundry Form 3160-5) Notice of Intent (NOI) for planned well work involving a formation change, casing repair/replacement, and injection well fracture treatment for approval by BLM and NMOCD. Verbal approval for the plan may be given by a BLM authorized officer, with the NOI filed within five business days. Packer and tubing repair (normal maintance procedures) do not require a NOI, but a subsequent sundry needs to be filed. <a href="http://www.blm.gov/nm/st/en/prog/energy/oil">http://www.blm.gov/nm/st/en/prog/energy/oil</a> and gas.html (see CFR § 3162.3-2 43 & CFR § 3160.0-9 (c)(1)).
  - a) Submit a (Sundry Form 3160-5) subsequent report (daily reports) describing all wellbore activity and Mechanical Integrity Test as per item 1) above. Include the date(s) of the well work, and the setting depths of required equipment: internally corrosive protected tubing, tubing on/off equipment just above the packer, and an in line tubing check valve below the packer or between the on/off tool and packer is required. The setting depths and descriptions of each are to be included in the subsequent sundry. List (by date) descriptions of daily activity of any previously unreported wellbore workover.

PRS

## Use of Form 3160-5 "Sundry Notices and Reports on Wells"

## § 43 CFR 3162.3-2 Subsequent Well Operations.

- a) A proposal for further well operations shall be submitted by the operator on Form 3160–5 for approval by the authorized officer prior to commencing operations to redrill, deepen, perform casing repairs, plug-back, alter casing, perform nonroutine fracturing jobs, recomplete in a different interval, perform water shut off, commingling production between intervals and/or conversion to injection. If there is additional surface disturbance, the proposal shall include a surface use plan of operations. A subsequent report on these operations also will be filed on Form 3160–5. The authorized officer may prescribe that each proposal contain all or a portion of the information set forth in §3162.3–1 of this title.
- (b) Unless additional surface disturbance is involved and if the operations conform to the standard of prudent operating practice, prior approval is not required for routine fracturing or acidizing jobs, or recompletion in the same interval; however, a subsequent report on these operations must be filed on Form 3160–5.
- (c) No prior approval or a subsequent report is required for well cleanout work, routine well maintenance, or bottom hole pressure surveys.

[47 FR 47765, Oct. 27, 1982. Redesigned and amended at 48 FR 36583–36586, Aug. 12, 1983, further amended at 52 FR 5391, Feb. 20, 1987; 53 FR 17363, May 16, 1988; 53 FR 22847, June 17, 1988]

## § 43 CFR 3160.0-9 (c)(1) Information collection.

(c)(1) The information collection requirements contained in part 3160 have been approved by the Office of Management and Budget under 44 U.S.C. 3507 and assigned the following Clearance Numbers:

#### **Operating Forms**

Form No.	Name and filing date	
3160–3	Application for Permit to Drill, Deepen, or Plug Back—Filed 30 days prior to planned action	1004-0136
3160–4	With Completion of Recompletion Report and Log—Due 30 days after well completion	1004-0137
3160-5	Sundry Notice and Reports on Wells—Subsequent report due 30 days after operations completed	1004-0135

The information will be used to manage Federal and Indian oil and gas leases. It will be used to allow evaluation of the technical, safety, and environmental factors involved with drilling and producing oil and gas on Federal and Indian oil and gas leases. Response is mandatory only if the operator elects to initiate drilling, completion, or subsequent operations on an oil and gas well, in accordance with 30 U.S.C. 181 et seq.

#### § 3162.4-1 (c) Well records and reports.

Not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160–5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed.

NM Fed Regs & Forms - http://www.blm.gov/nm/st/en/prog/energy/oil\_and\_gas.html