

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
October 13, 2009

HOBBS OCD

OIL CONSERVATION DIVISION

APR 09 2012

1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-04335 40335
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name East Caprock SWD
8. Well Number 5
9. OGRID Number 164070
10. Pool name or Wildcat SWD; Devonian (96101)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other SWD

2. Name of Operator
Paladin Energy Corp.

3. Address of Operator
10290 Monroe Drive, Suite 301, Dallas TX 75229

4. Well Location

Unit Letter B : 930 feet from the North line and 2290 feet from the East line
Section 14 Township 12-S Range 32-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4,356

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/13-14/12- RU Casing Crew ran 93 jts 8.8750, 32#, J-55, STC casing from 3902' to surface. Mix & pump 955 sks/350 bbls of 12.8 lead followed by 200 sks/48 bbls of 14.8 tail. Plug w/238 bbls of fresh water. Bump plug to 500 over hold pressure for 5 min and bled back 1.5 bbls - floats held. RD. Schlumberger.. Circulated 53 bbls/151 sks of cement to surface.

Spud Date: 03/05/12

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Ann Westberry TITLE Manager, Corporate Support DATE 04/04/12

Type or print name Ann Westberry E-mail address: awestberry@paladinenergy.com PHONE: 214-654-0132 X4

For State Use Only

APPROVED BY: [Signature] TITLE STAFF MGR DATE 4-9-2012
Conditions of Approval (if any):

APR 10 2012