

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
HOBBS OCD
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505
APR 30

Form C-103
October 13, 2009

RECEIVED	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	7. Lease Name or Unit Agreement Name B T LANEHART
2. Name of Operator BETTIS, BOYLE & STOVALL	8. Well Number 004
3. Address of Operator P.O BOX 1240, GRAHAM, TX 76450	9. OGRID Number 002175
4. Well Location Unit Letter <u>B</u> : <u>990</u> feet from the <u>NORTH</u> line and <u>2310</u> feet from the <u>EAST</u> line Section <u>21</u> Township <u>25S</u> Range <u>37E</u> NMPM LEA County	10. Pool name or Wildcat Tansill Yates 7 Rvrs.
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3075 GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

B M JUSTIS B #7 12-1/2" SURFACE @ 100'; 8-1/4" 32# SURFACE @ 1226' W/ 308 SX; 7" PRODUCTION CASING @ 2956', CEMENT'D WITH 100 SX., 5-3/16" LINER @ 2933-3103', CMT'D WITH 20 SX.
PERFS: 2956-3034'

MIRU BCM & ASSOCIATES, INC.

MOVE IN 250 BBL. STEEL REVERSE TANK

DRILL OUT CMT & SAND TO 2983' (50' into liner)

TAG CEMENT @ TOP OF LINER @ 2777'. CIRCULATE HOLE WITH MUD LADEN FLUIDS

SPOT 25 SX CMT at 2983'. WOC & TAG. CIRC W/ MUD LADEN FLUID

AT 2625', PERF & SQUEEZE WITH 35 SX., WOC & TAG

AT 1276', PERF & SQUEEZE WITH 35 SX., WOC & TAG

AT 400', PERF & CIRCULATE TO SURFACE; HAUL LIQUIDS IN TANK TO SWD AS SET OUT IN C-144
PLACE DRY HOLE MARKER ON WELL.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kyle Berend TITLE Regulatory Analyst DATE 04/26/12

Type or print name Kyle Berend E-mail address: kberend@bbsoil.com PHONE: 940-549-0780

For State Use Only

APPROVED BY: Mark Whitaker TITLE Compliance Officer DATE 5-1-2012

Conditions of Approval (if any):

MAY 02 2012

BETIS, BOYLE & TOVALH

WELL BORE DIAGRAM

B.T. LANEBART No. 4

30-025-11681

